

Equipment	Operating frequency	RF Power generated by equipment (watts)	Field strength limit (uV/m)	Distance (meters)
Ultrasonic .....	Below 490 kHz .....	Below 500 .....	2,400/F(kHz) .....	300
		500 or more .....	2,400/F(kHz) × SQRT(power/500).	<sup>3</sup> 300
	490 to 1,600 kHz .....	Any .....	24,000/F(kHz) .....	30
	Above 1,600 kHz .....	Any .....	15 .....	30
Induction cooking ranges .....	Below 90 kHz .....	Any .....	1,500 .....	<sup>4</sup> 30
	On or above 90 kHz .....	Any .....	300 .....	<sup>4</sup> 30

<sup>1</sup> Field strength may not exceed 10 μV/m at 1600 meters. Consumer equipment operating below 1000 MHz is not permitted the increase in field strength otherwise permitted here for power over 500 watts.

<sup>2</sup> Reduced to the greatest extent possible.

<sup>3</sup> Field strength may not exceed 10 μV/m at 1600 meters. Consumer equipment is not permitted the increase in field strength otherwise permitted here for over 500 watts.

<sup>4</sup> Induction cooking ranges manufactured prior to February 1, 1980, shall be subject to the field strength limits for miscellaneous ISM equipment.

(c) The field strength limits for RF lighting devices shall be the following:

Frequency (MHz)	Field strength limit at 30 meters (μV/m)
Non-consumer equipment:	
30-88 .....	30
88-216 .....	50
216-1000 .....	70
Consumer equipment:	
30-88 .....	10
88-216 .....	15
216-1000 .....	20

NOTES

1. The tighter limit shall apply at the boundary between two frequency ranges.

2. Testing for compliance with these limits may be made at closer distances, provided a sufficient number of measurements are taken to plot the radiation pattern, to determine the major lobes of radiation, and to determine the expected field strength level at 30, 300, or 1600 meters. Alternatively, if measurements are made at only one closer fixed distance, then the permissible field strength limits shall be adjusted using 1/d as an attenuation factor.

[50 FR 36070, Sept. 5, 1985, as amended at 51 FR 17970, May 16, 1986; 52 FR 43197, Nov. 10, 1987]

§ 18.307 Conduction limits.

For the following equipment, when designed to be connected to the public utility (AC) power line the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies shall not exceed the limits in the following tables. Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at

the power terminal using a 50 μH/50 ohms line impedance stabilization network (LISN).

(a) All Induction cooking ranges and ultrasonic equipment:

Frequency of emission (MHz)	Conducted limit (dBμV)	
	Quasi-peak	Average
0.009-0.05 .....	110 .....	—
0.05-0.15 .....	90-80* .....	—
0.15-0.5 .....	66 to 56* .....	56 to 46*
0.5-5 .....	56 .....	46
5-30 .....	60 .....	50

\* Decreases with the logarithm of the frequency.

(b) All other part 18 consumer devices:

Frequency of emission (MHz)	Conducted limit (dBμV)	
	Quasi-peak	Average
0.15-0.5 .....	66 to 56* .....	56 to 46*
0.5-5 .....	56 .....	46
5-30 .....	60 .....	50

\* Decreases with the logarithm of the frequency.

(c) RF lighting devices:

Frequency (MHz)	Maximum RF line voltage measured with a 50 uH/50 ohm LISN (uV)
Non-consumer equipment:	
0.45 to 1.6 .....	1,000
1.6 to 30 .....	3,000
Consumer equipment:	
0.45 to 2.51 .....	250
2.51 to 3.0 .....	3,000
3.0 to 30 .....	250

(d) If testing with a quasi-peak detector demonstrates that the equipment complies with the average limits specified in the appropriate table in this section, additional testing to demonstrate compliance using an average detector is not required.

**§ 18.309**

**47 CFR Ch. I (10–1–14 Edition)**

(e) These conduction limits shall apply only outside of the frequency bands specified in § 18.301.

(f) For ultrasonic equipment, compliance with the conducted limits shall preclude the need to show compliance with the field strength limits below 30 MHz unless requested by the Commission.

(g) The tighter limits shall apply at the boundary between two frequency ranges.

[50 FR 36067, Sept. 5, 1985, as amended at 52 FR 43198, Nov. 10, 1987; 64 FR 37419, July 12, 1999; 67 FR 45671, July 10, 2002]

**§ 18.309 Frequency range of measurements.**

(a) For field strength measurements:

Frequency band in which device operates (MHz)	Range of frequency measurements	
	Lowest frequency	Highest frequency
Below 1.705 .....	Lowest frequency generated in the device, but not lower than 9 kHz.	30 MHz.
1.705 to 30 .....	Lowest frequency generated in the device, but not lower than 9 kHz.	400 MHz.
30 to 500 .....	Lowest frequency generated in the device or 25 MHz, whichever is lower.	Tenth harmonic or 1,000 MHz, whichever is higher.
500 to 1,000 .....	Lowest frequency generated in the device or 100 MHz, whichever is lower.	Tenth harmonic.
Above 1,000 .....	.....do .....	Tenth harmonic or highest detectable emission.

(b) For conducted powerline measurements, the frequency range over which the limits are specified will be scanned.

[50 FR 36070, Sept. 5, 1985, as amended at 51 FR 17971, May 16 1986]

**§ 18.311 Methods of measurements.**

The measurement techniques which will be used by the FCC to determine compliance with the technical requirements of this part are set out in FCC Measurement Procedure MP-5, "Methods of Measurements of Radio Noise Emissions from ISM equipment". Although the procedures in MP-5 are not mandated, manufacturers are encouraged to follow the same techniques which will be used by the FCC.

**PART 19—EMPLOYEE RESPONSIBILITIES AND CONDUCT**

**Subpart A—General Provisions**

- Sec.
- 19.735-101 Purpose.
- 19.735-102 Cross-reference to ethics and other conduct related regulations.
- 19.735-103 Definitions.
- 19.735-104 Delegations.
- 19.735-105 Availability of ethics and other conduct related regulations and statutes.
- 19.735-106 Interpretation and advisory service.

19.735-107 Disciplinary and other remedial action.

**Subpart B—Employee Responsibilities and Conduct**

- 19.735-201 Outside employment and other activity prohibited by the Communications Act.
- 19.735-202 Financial interests prohibited by the Communications Act.
- 19.735-203 Nonpublic information.

AUTHORITY: 5 U.S.C. 7301; 47 U.S.C. 154 (b), (i), (j), and 303(r).

SOURCE: 61 FR 56112, Oct. 31, 1996, unless otherwise noted.

**Subpart A—General Provisions**

**§ 19.735-101 Purpose.**

The regulations in this part prescribe procedures and standards of conduct that are appropriate to the particular functions and activities of the Commission, and are issued by the Commission under authority independent of the uniform Standards of Ethical Conduct for Employees of the Executive Branch at 5 CFR part 2635 or otherwise in accordance with 5 CFR 2635.105(c).