

requesting an extension of time to construct those facilities.

(b) *Technical data.* The following data, associated with FCC Form 601, are required as indicated for each application. Applications for a paging geographic area authorization must not contain Schedule B. Other type of applications may contain as many Schedule Bs as are necessary for the intended purpose.

(1) For each transmitting antenna site to be added, deleted or modified, the following are required: an indication of the desired database action, the Commission location number, if any, the street address or other description of the transmitting antenna site, the city, county and state, the geographic coordinates (latitude and longitude), correct to ±1 second, of the transmitting antenna site (NAD83), and in the case of a proposed relocation of a transmitting antenna, the Commission location number and geographic coordinates, correct to ±1 second, of the transmitting antenna site (NAD83) to which the geographic coordinates of the current location are referenced.

(2) For each transmitting antenna site to be added, deleted or modified, the following supplementary information is required: An indication as to whether or not the transmitting antenna site is within 200 kilometers (124 miles) of the U.S.-Mexico border, and an indication as to whether or not the transmitting antenna site is North of Line A or East of Line C. Line A and Line C are defined in §2.1 of this chapter. For each adjacent geographic area within 200 kilometers (124 miles) of each transmitting antenna site to be added, deleted or modified, the geographic area designator and name, and the shortest distance (in kilometers) to the boundary of that geographic area.

(3) The height (in meters) above average terrain of the center of radiation of the antenna, the beamwidth of the main lobe of the horizontal radiation pattern of the electric field of the antenna, the height (in meters) to the tip of the antenna above ground level, a polar plot of the horizontal gain pattern of the antenna, the antenna gain in the maximum lobe and the electric field polarization of the wave emitted

by the antenna when installed as proposed.

(i) The center frequency of the requested channel, the transmitter classification (e.g. base, fixed mobile), the designator for any non-standard emission type to be used, including bandwidth and modulation type, and the maximum effective radiated power.

(ii) For each of the eight cardinal radials, the antenna height above the average elevation along the radial, and the effective radiated power of each transmitter in the direction of the radial.

(iii) For each transmitter proposed to transmit on a channel reserved for point-to-multipoint operation involving transmission to four or more points of communications (i.e. base transmitters), the following is required for each point of communication: an indication of the desired database action, the location (city or town, state), and the geographical coordinates (latitude and longitude, NAD 83).

(c) Upon request by an applicant, licensee, or the Commission, a part 22 applicant or licensee of whom the request is made shall furnish the antenna type, model, and the name of the antenna manufacturer to the requesting party within ten (10) days of receiving written notification.

[62 FR 11635, Mar. 12, 1997, as amended at 63 FR 68945, Dec. 14, 1998; 64 FR 53240, Oct. 1, 1999]

PAGING OPERATION

§ 22.531 Channels for paging operation.

The following channels are allocated for assignment to base transmitters that provide paging service, either individually or collectively under a paging geographic area authorization. Unless otherwise indicated, all channels have a bandwidth of 20 kHz and are designated by their center frequencies in MegaHertz.

Low VHF Channels			
35.20	35.46	43.20	43.46
35.22	35.50	43.22	43.50
35.24	35.54	43.24	43.54
35.26	35.56	43.26	43.56
35.30	35.58	43.30	43.58
35.34	35.60	43.34	43.60
35.38	35.62	43.38	43.62
35.42	35.66	43.42	43.66

§ 22.535

47 CFR Ch. I (10–1–14 Edition)

	High VHF Channels		
152.24	152.84	158.10	158.70
	UHF Channels		
931.0125	931.2625	931.5125	931.7625
931.0375	931.2875	931.5375	931.7875
931.0625	931.3125	931.5625	931.8125
931.0875	931.3375	931.5875	931.8375
931.1125	931.3625	931.6125	931.8625
931.1375	931.3875	931.6375	931.8875
931.1625	931.4125	931.6625	931.9125
931.1875	931.4375	931.6875	931.9375
931.2125	931.4625	931.7125	931.9625
931.2375	931.4875	931.7375	931.9875

(a)–(b) [Reserved]

(c) Upon application using FCC Form 601, common carriers may be authorized to provide one-way paging service using the leased subcarrier facilities of broadcast stations licensed under part 73 of this chapter.

(d) Occasionally in case law and other formal and informal documents, the low VHF channels have been referred to as “lowband” channels, and the high VHF channels have been referred to as “guardband” channels.

(e) Pursuant to the U.S.-Canada Interim Coordination Considerations for 929–932 MHz, as amended, only the following UHF channels may be assigned in the continental United States North of Line A or in the State of Alaska East of Line C, within the indicated longitudes:

(1) From longitude W.73° to longitude W.75° and from longitude W.78° to longitude W.81°:

931.0125	931.1125	931.1875	931.2625
931.0375	931.1375	931.2125	931.8625
931.0625	931.1625	931.2375	

(2) From longitude W.81° to longitude W.85°:

931.0125	931.2125	931.3875	931.5875
931.0375	931.2375	931.4125	931.6125
931.0625	931.2625	931.4625	931.6375
931.1125	931.2875	931.4875	931.8625
931.1375	931.3125	931.5125	
931.1625	931.3375	931.5375	
931.1875	931.3625	931.5625	

(3) Longitudes other than specified in paragraphs (e)(1) and (e)(2) of this section:

931.0125	931.1625	931.2875	931.4125
931.0375	931.1875	931.3125	931.4625
931.0625	931.2125	931.3375	931.8625
931.1125	931.2375	931.3625	
931.1375	931.2625	931.3875	

(4) At any longitude, with authorization condition requiring coordinated,

shared use and equal access by licensees in both countries:

931.4375	931.8875	931.9125	931.9375
----------	----------	----------	----------

(f) For the purpose of issuing paging geographic authorizations, the paging geographic areas used for UHF channels are the MEAs, and the paging geographic areas used for the low and high VHF channels are the EAs (see § 22.503(b)).

[59 FR 59507, Nov. 17, 1994, as amended at 59 FR 59954, Nov. 21, 1994; 62 FR 11635, Mar. 12, 1997; 63 FR 68945, Dec. 14, 1998; 64 FR 33784, June 24, 1999; 70 FR 19309, Apr. 13, 2005]

§ 22.535 Effective radiated power limits.

The effective radiated power (ERP) of transmitters operating on the channels listed in § 22.531 must not exceed the limits in this section.

(a) *Maximum ERP.* The ERP must not exceed the applicable limits in this paragraph under any circumstances.

Frequency range (MHz)	Maximum ERP (Watts)
35–36	600
43–44	500
152–159	1400
931–932	3500

(b) *Basic power limit.* Except as provided in paragraph (d) of this section, the ERP of transmitters on the VHF channels must not exceed 500 Watts.

(c) *Height-power limit.* Except as provided in paragraph (d) of this section, the ERP of transmitters on the VHF channels must not exceed the amount that would result in an average distance to the service contour of 32.2 kilometers (20 miles). The average distance to the service contour is calculated by taking the arithmetic mean of the distances determined using the procedures specified in § 22.537 for the eight cardinal radial directions, excluding cardinal radial directions for which 90% or more of the distance so calculated is over water.

(d) *Encompassed interfering contour areas.* Transmitters are exempt from the basic power and height-power limits of this section if the area within their interfering contours is totally encompassed by the interfering contours of operating co-channel base transmitters controlled by the same licensee.