

**Federal Communications Commission**

**§ 22.561**

with §22.165 and notwithstanding paragraphs (e) and (f) of this section, signal boosters operating on the 931 MHz channels with an antenna HAAT not exceeding 30 meters (98 feet) are deemed to have as a service contour a circle with a radius of 1.0 kilometer (0.6 mile) and as an interfering contour a circle with a radius of 10 kilometers (6.2 miles).

[59 FR 59507, Nov. 17, 1994, as amended at 61 FR 31051, June 19, 1996]

**§ 22.559 Paging application requirements.**

In addition to information required by subparts B and D and §22.529, applications for authorization to operate a paging transmitter on the channels listed in §22.531, other than applications for a paging geographic area authorization, must contain the applicable supplementary information described in this section.

(a) *Interference exhibit.* Except as provided in paragraph (b) of this section, an exhibit demonstrating compliance with §22.537 with regard to protected transmitters is required for applications to operate a transmitter on the VHF channels. This exhibit must:

(1) Identify each protected transmitter located within 109 kilometers (68 miles) of the proposed transmitter in directions in which the distance to the interfering contour is 76.5 kilometers (47.5 miles) or less, and within 178 kilometers (111 miles) of the proposed transmitter in directions in which the distance to the interfering contour exceeds 76.5 kilometers (47.5 miles).

(2) For each protected transmitter identified, show the results of distance calculations indicating that there would be no overlap of service and interfering contours, or alternatively, indicate that the licensee of or applicant for the protected transmitter and/or the applicant, as required, have agreed in writing to accept any interference resulting from operation of the proposed transmitter.

(b) *Encompassment exhibit.* An exhibit showing that the area within the interfering contour of the proposed transmitter would be totally encompassed by interfering contours of operating co-channel base transmitters controlled

by the applicant is required for applications to operate a transmitter with ERP exceeding the basic power and height-power limits of §22.535. For VHF transmitters, this encompassment exhibit may substitute for the interference exhibit required in paragraph (a) of this section.

[59 FR 59507, Nov. 17, 1994, as amended at 62 FR 11636, Mar. 12, 1997]

**ONE-WAY OR TWO-WAY MOBILE OPERATION**

**§ 22.561 Channels for one-way or two-way mobile operation.**

The following channels are allocated for paired assignment to transmitters that provide (or support other transmitters that provide) one-way or two-way public land mobile service, either individually or collectively under a paging geographic area authorization. The paging geographic areas used for these channels are the EAs (*see* §22.503(b)(3)). These channels may be assigned for use by mobile or base transmitters as indicated, and or by fixed transmitters (including control, repeater or other fixed transmitters). The mobile channels may also be assigned for use by base or fixed transmitters under certain circumstances (*see* §22.567(h)). Unless otherwise indicated, all channels have a bandwidth of 20 kHz and are designated by their center frequencies in MegaHertz.

Base	Mobile	Base	Mobile
<b>VHF Channels</b>			
152.03 .....	158.49	152.57 .....	157.83
152.06 .....	158.52	152.60 .....	157.86
152.09 .....	158.55	152.63 .....	157.89
152.12 .....	158.58	152.66 .....	157.92
152.15 .....	158.61	152.69 .....	157.95
152.18 .....	158.64	152.72 .....	157.98
152.21 .....	158.67	152.75 .....	158.01
152.51 .....	157.77	152.78 .....	158.04
152.54 .....	157.80	152.81 .....	158.07
<b>UHF Channels</b>			
454.025 .....	459.025	454.350 .....	459.350
454.050 .....	459.050	454.375 .....	459.375
454.075 .....	459.075	454.400 .....	459.400
454.100 .....	459.100	454.425 .....	459.425
454.125 .....	459.125	454.450 .....	459.450
454.150 .....	459.150	454.475 .....	459.475
454.175 .....	459.175	454.500 .....	459.500
454.200 .....	459.200	454.525 .....	459.525