

§ 22.653

47 CFR Ch. I (10–1–14 Edition)

§ 22.653 Eligibility.

Only licensees already authorized to provide trunked mobile service or their successors in interest are eligible to apply for additional use of these channels for trunked mobile service, and then only in the urban areas already authorized.

§ 22.657 Transmitter locations.

The purpose of the rules in paragraphs (a) and (b) of this section is to define the areas in which the 470–512 MHz channels are allocated for public mobile use. The purpose of the rules in paragraphs (c) through (f) of this section is to reduce the likelihood that interference to television reception from public mobile operations on these channels will occur. The protected TV station locations specified in paragraphs (d), (e)(1) and (f) of this section are the locations of record as of September 1974, and these do not change even though the TV stations may have been subsequently relocated.

(a) *Base transmitter locations.* Base transmitter locations must be within 80 kilometers (50 miles) of the designated locations in this paragraph. Mobile transmitters must not be operated at locations more than 129 kilometers (80 miles) from the designated locations in this paragraph. Note: All coordinates are referenced to North American Datum 1983 (NAD83).

Urban area	N. latitude	W. longitude
Houston, TX	29°45'26.8"	95°21'37.8"
New York, NY-NE NJ	40°45'06.4"	73°59'37.5"

(b) *Mobile area of operation.* Mobile transmitters must not be operated at locations more than 48 kilometers (30 miles) from all associated base stations.

(c) *Protection from intermodulation interference.* Base transmitter locations must be at least 1.6 kilometers (1 mile) from the current main transmitter locations of all TV stations transmitting on TV channels separated by 2, 3, 4, 5, 7, or 8 TV channels from the TV channel containing the frequencies on which the base station will transmit. This requirement is intended to reduce the likelihood of intermodulation interference.

(d) Adjacent channel protection from mobile transmitters. Base transmitter locations must be at least 145 kilometers (90 miles) from the applicable protected TV station locations specified in this paragraph. This requirement is intended to provide a 0 dB minimum desired to undesired signal strength ratio at the Grade B contour of an adjacent channel TV station. Note: All coordinates are referenced to North American Datum 1983 (NAD83).

Control transmitter frequency range	Protected TV station location	TV channel
470–476 MHz.	Lancaster, PA, 40°15'45.3" N. Lat. 76°27'47.9" W. Long..	(15)
476–482 MHz.	Scranton, PA, 41°10'58.3" N. Lat. 75°52'19.7" W. Long..	(16)

(e) *Co-channel protection from mobile transmitters.* Base transmitter locations must be at least the distance specified in paragraph (e)(2) of this section from the applicable protected TV station locations specified in paragraph (e)(1) of this section. This requirement is intended to provide a 40 dB minimum desired to undesired signal strength ratio at the Grade B contour of a co-channel TV station.

(1) The protected TV station locations are as follows (all coordinates are referenced to North American Datum 1983 (NAD83)):

Control transmitter frequency range	Protected TV station location
470–476 MHz.	Washington, DC, 38°57'17.4" N. Lat. 77°00'15.9" W. Long.
476–482 MHz.	Lancaster, PA, 40°15'45.3" N. Lat. 76°27'47.9" W. Long.

(2) The required minimum distance depends upon the effective radiated power (ERP) of the most powerful mobile transmitter(s) in the system:

Mobile unit ERP (watts)	Minimum distance	
	Kilometers	Miles
60	193	(120)
50	185	(115)
25	177	(110)
10	169	(105)
5	161	(100)

(f) *Co-channel protection from base transmitters with high antennas.* This