

(3) *Exhibit III—engineering.* This exhibit must contain the data and methodology used to calculate the CGSA and service area boundary.

(4) *Exhibit IV—channel plan.* This exhibit must show which specific channels (or groups) are to be used at each cell site. Any necessary table for converting channel numbers to center frequencies must be provided.

(5) [Reserved]

(6) *Exhibit VI—service proposal.* This exhibit must describe the services proposed for subscribers and roamers, including the proposed method for handling complaints.

(7) *Exhibit VII—cellular design.* This exhibit must show that the proposed system design complies with cellular system design concepts, and must describe the method proposed to expand the system in a coordinated fashion as necessary to address changing demand for cellular service.

(8) *Exhibit VIII—blocking level.* This exhibit must disclose the blocking probability or other criteria to be used to determine whether it is necessary to take measures to increase system capacity to maintain service quality.

(9) *Exhibit IX—start-up expenses.* This exhibit must disclose in detail the projected cost of construction and other initial expenses of the proposed system, and how the applicant intends to meet these expenses and the costs of operation for the first year.

(10) *Exhibit X—interconnection arrangements.* This exhibit is required for applicants that provide public landline message telephone service in any portion of the proposed CGSA. This exhibit must describe exactly how the proposed system would interconnect with the landline network. The description must be of sufficient detail to enable a competitor to connect with the landline system in exactly the same manner, if the competitor so chooses.

(b) *Existing systems—major modifications.* Licensees making major modifications pursuant to §1.929(a) and (b) of this chapter, must file FCC Form 601 and need only contain the exhibits required by paragraphs (a)(1) through (a)(3) of this section.

(c) *Existing systems—minor modifications.* Licensees making minor modifications pursuant to §1.929(k) of this

chapter—in which the modification causes a change in the CGSA boundary (including the removal of a transmitter or transmitters)—must notify the FCC (using FCC Form 601) and include full-sized maps, reduced maps, and supporting engineering exhibits as described in paragraphs (a)(1) through (3) of this section. If the modification involves a contract SAB extension, it must include a statement as to whether the five-year build-out for the system on the relevant channel block in the market into which the SAB extends has elapsed, and as to whether the SAB extends into any unserved area in that market.

[59 FR 59507, Nov. 17, 1994, as amended at 59 FR 59954, Nov. 21, 1994; 63 FR 68951, Dec. 14, 1998; 64 FR 53241, Oct. 1, 1999; 70 FR 61059, Oct. 20, 2005]

#### § 22.955 Canadian condition.

Pursuant to an agreement between the FCC and the Department of Communications in Canada, authorizations for cellular systems within 72 kilometers (45 miles) of the U.S.-Canadian border must have the following condition attached:

This authorization is subject to the condition that, in the event that cellular systems using the same channel block as granted herein are authorized in adjacent territory in Canada, coordination of any of your transmitter installations which are within 72 kilometers (45 miles) of the U.S.-Canadian border shall be required to eliminate any harmful interference that might otherwise exist and to insure continuance of equal access to the channel block by both countries.

#### § 22.957 Mexican condition.

Pursuant to an agreement between the United States and Mexico, FCC authorizations for cellular systems within 72 kilometers (45 miles) of the United States-Mexican border must have the following condition attached:

This authorization is subject to the condition that, in the event cellular systems using the same frequencies granted herein are authorized in adjacent territory in Mexico, coordination of your transmitter installations which are within 72 kilometers (45 miles) of the United States-Mexico border shall be required to eliminate any harmful interference that might otherwise exist and to ensure continuance of equal access to the frequencies by both countries. The operator of

**§ 22.959**

this system shall not contract with customers in Mexico, and further, users of the system must be advised that operation of a mobile unit in Mexico is not permitted at this time without the express permission of the Mexican government. The above conditions are subject to modification pending further notice from the FCC.

**§ 22.959 Rules governing processing of applications for initial systems.**

Pending applications for authority to operate the first cellular system on a channel block in an MSA or RSA market continue to be processed under the rules governing the processing of such applications that were in effect when those applications were filed, unless the Commission determines otherwise in a particular case.

**§ 22.960 Cellular unserved area radiotelephone licenses subject to competitive bidding.**

Mutually exclusive initial applications for cellular unserved area Phase I and Phase II licenses filed after July 26, 1993 are subject to competitive bidding. The general competitive bidding procedures set forth in part 1, subpart Q of this chapter will apply unless otherwise provided in this subpart.

[67 FR 45367, July 9, 2002]

**§§ 22.961–22.967 [Reserved]**

**§ 22.969 Cellular RSA licenses subject to competitive bidding.**

Mutually exclusive applications for initial authorization for the following Cellular Rural Service Areas filed after the effective date of this rule are subject to competitive bidding procedures as prescribed by Sections 22.228 and 22.229: 332A—Polk, AR; 582A—Barnes, ND; 672A—Chambers, TX; and 727A—Ceiba, PR.

[67 FR 11434, Mar. 14, 2002]

**§ 22.970 Unacceptable interference to part 90 non-cellular 800 MHz licensees from cellular radiotelephone or part 90–800 MHz cellular systems.**

(a) *Definition.* Except as provided in 47 CFR 90.617(k), unacceptable interference to non-cellular part 90 licensees in the 800 MHz band from cellular radiotelephone or part 90–800 MHz cellular systems will be deemed to occur when the below conditions are met:

**47 CFR Ch. I (10–1–14 Edition)**

(1) A transceiver at a site at which interference is encountered:

(i) Is in good repair and operating condition, and is receiving:

(A) A median desired signal of –104 dBm or higher, as measured at the R.F. input of the receiver of a mobile unit; or

(B) A median desired signal of –101 dBm or higher, as measured at the R.F. input of the receiver of a portable *i.e.* hand-held unit; and, either

(ii) Is a voice transceiver:

(A) With manufacturer published performance specifications for the receiver section of the transceiver equal to, or exceeding, the minimum standards set out in paragraph (b) of this section, below; and;

(B) Receiving an undesired signal or signals which cause the measured Carrier to Noise plus interference (C/(I+N)) ratio of the receiver section of said transceiver to be less than 20 dB, or,

(iii) Is a non-voice transceiver receiving an undesired signal or signals which cause the measured bit error rate (BER) (or some comparable specification) of the receiver section of said transceiver to be more than the value reasonably designated by the manufacturer.

(2) Provided, however, that if the receiver section of the mobile or portable voice transceiver does not conform to the standards set out in paragraph (b) of this section, then that transceiver shall be deemed subject to unacceptable interference only at sites where the median desired signal satisfies the applicable threshold measured signal power in paragraph (a)(1)(i) of this section after an upward adjustment to account for the difference in receiver section performance. The upward adjustment shall be equal to the increase in the desired signal required to restore the receiver section of the subject transceiver to the 20 dB C/(I+N) ratio of paragraph (a)(1)(ii)(B) of this section. The adjusted threshold levels shall then define the minimum measured signal power(s) in lieu of paragraphs (a)(1)(i) of this section at which the licensee using such non-compliant transceiver is entitled to interference protection.

(b) *Minimum receiver requirements.* Voice transceivers capable of operating