

§ 25.205

(h) ESV transmissions in the 5925–6425 MHz (Earth-to-space) band shall not exceed an e.i.r.p. spectral density towards the radio-horizon of 17 dBW/MHz, and shall not exceed an e.i.r.p. towards the radio-horizon of 20.8 dBW. The ESV network shall shut-off the ESV transmitter if the e.i.r.p. spectral density towards the radio-horizon or e.i.r.p. towards the radio-horizon are exceeded.

(i) Within 125 km of the TDRSS sites identified in § 25.222(d), ESV transmissions in the 14.0–14.2 GHz (Earth-to-space) band shall not exceed an e.i.r.p. spectral density towards the horizon of 12.5 dBW/MHz, and shall not exceed an e.i.r.p. towards the horizon of 16.3 dBW.

(j) Within 125 km of the Tracking and Data Relay System Satellite (TDRSS) sites identified in § 25.226(c), VMES transmissions in the 14.0–14.2 GHz (Earth-to-space) band shall not exceed an EIRP spectral density towards the horizon of 12.5 dBW/MHz, and shall not exceed an EIRP towards the horizon of 16.3 dBW.

(k) Within radio line-of-sight of the Tracking and Data Relay System Satellite (TDRSS) sites identified in § 25.227(c), ESAA transmissions in the 14.0–14.2 GHz (Earth-to-space) band shall not exceed an EIRP spectral density towards or below the horizon of 12.5 dBW/MHz, and shall not exceed an EIRP towards or below the horizon of 16.3 dBW.

[48 FR 40255, Sept. 6, 1983, as amended at 58 FR 13420, Mar. 11, 1993; 61 FR 52307, Oct. 7, 1996; 62 FR 61457, Nov. 18, 1997; 66 FR 10623, Feb. 16, 2001; 70 FR 4784, Jan. 31, 2005; 70 FR 32255, June 2, 2005; 72 FR 50029, Aug. 29, 2007; 74 FR 57098, Nov. 4, 2009; 78 FR 8427, Feb. 6, 2013; 78 FR 14927, Mar. 8, 2013; 79 FR 8322, Feb. 12, 2004]

§ 25.205 Minimum angle of antenna elevation.

(a) Earth station antennas shall not normally be authorized for transmission at angles less than 5° measured from the horizontal plane to the direction of maximum radiation. However, upon a showing that the transmission path will be seaward and away from land masses or upon special showing of need for lower angles by the applicant, the Commission will consider authorizing transmissions at angles between 3° and 5° in the pertinent directions. In

47 CFR Ch. I (10–1–14 Edition)

certain instances, it may be necessary to specify minimum angles greater than 5° because of interference considerations.

(b) ESVs making a special showing requesting angles of elevation less than 5° measured from the horizontal plane to the direction of maximum radiation pursuant to (a) of this Section must still meet the effective isotropically radiated power (e.i.r.p.) and e.i.r.p. density towards the horizon limits contained in § 25.204(h) and (i).

(c) VMESs making a special showing requesting angles of elevation less than 5° measured from the horizontal plane to the direction of maximum radiation pursuant to (a) of this section must still meet the EIRP and EIRP density towards the horizon limits contained in § 25.204(j).

(d) While on the ground, ESAAs shall not be authorized for transmission at angles less than 5° measured from the plane of the horizon to the direction of maximum radiation. While in flight there is no minimum angle of antenna elevation.

[70 FR 4784, Jan. 31, 2005, as amended at 74 FR 57099, Nov. 4, 2009; 78 FR 14927, Mar. 8, 2013]

§ 25.206 Station identification.

The requirement to transmit station identification is waived for all radio stations licensed under this part with the exception of earth stations subject to the requirements of § 25.281.

[79 FR 8322, Feb. 12, 2014]

§ 25.207 Cessation of emissions.

Space stations shall be made capable of ceasing radio emissions by the use of appropriate devices (battery life, timing devices, ground command, etc.) that will ensure definite cessation of emissions.

§ 25.208 Power flux density limits.

(a) In the band 3650–4200 MHz, the power flux density at the Earth's surface produced by emissions from a space station for all conditions and for all methods of modulation shall not exceed the following values:

–152 dB(W/m²) in any 4 kHz band for angles of arrival between 0 and 5 degrees above the horizontal plane;

Federal Communications Commission

§ 25.208

–152+(δ –5)/2 dB(W/m²) in any 4 kHz band for angles of arrival δ (in degrees) between 5 and 25 degrees above the horizontal plane; and
–142 dB(W/m²) in any 4 kHz band for angles of arrival between 25 and 90 degrees above the horizontal plane

These limits relate to the power flux density which would be obtained under assumed free-space propagation conditions.

(b) In the bands 10.95–11.2 and 11.45–11.7 GHz for GSO FSS space stations and 10.7–11.7 GHz for NGSO FSS space stations, the power flux-density at the Earth's surface produced by emissions from a space station for all conditions and for all methods of modulation shall not exceed the lower of the following values:

(1) –150 dB(W/m²) in any 4 kHz band for angles of arrival between 0 and 5 degrees above the horizontal plane; –150 + (δ –5)/2 dB(W/m²) in any 4 kHz band for angles of arrival (δ) (in degrees) between 5 and 25 degrees above the horizontal plane; and –140 dB(W/m²) in any 4 kHz band for angles of arrival between 25 and 90 degrees above the horizontal plane; or

(2) –126 dB(W/m²) in any 1 MHz band for angles of arrival between 0 and 5 degrees above the horizontal plane; –126 + (δ –5)/2 dB(W/m²) in any 1 MHz band for angles of arrival (δ) (in degrees) between 5 and 25 degrees above the horizontal plane; and –116 dB(W/m²) in any 1 MHz band for angles of arrival between 25 and 90 degrees above the horizontal plane.

–115 – X dB(W/m²+MHz) for 0° ≤ δ < 5°
–115 – X + ((10+X)/20)(δ –5) dB(W/m²+MHz) for 5° ≤ δ < 25°
–105 dB(W/m²+MHz) for 25° ≤ δ < 90°

Where:

δ : is the angle of arrival above the horizontal plane; and

X is defined as a function of the number of satellites in the non-GSO FSS constellation, n, as follows:

for n ≤ 50 X = 0 (dB)
for 50 < n ≤ 288 X = (5/119) (n – 50) (dB)
for n > 288 X = (1/69) (n + 402) (dB)

(f) [Reserved]

(g) In the 10.7–11.7 GHz and 11.7–12.2 GHz bands, the single-entry equivalent

NOTE TO PARAGRAPH (b): These limits relate to the power flux density, which would be obtained under assumed free-space propagation conditions.

(c) In the 17.7–17.8 GHz, 18.3–18.8 GHz, 19.3–19.7 GHz, 22.55–23.00 GHz, 23.00–23.55 GHz, and 24.45–24.75 GHz frequency bands, the power flux density at the Earth's surface produced by emissions from a space station for all conditions for all methods of modulation shall not exceed the following values:

(1) –115 dB (W/m²) in any 1 MHz band for angles of arrival between 0 and 5 degrees above the horizontal plane.

(2) –115 + 0.5 (δ –5) dB (W/m²) in any 1 MHz band for angles of arrival δ (in degrees) between 5 and 25 degrees above the horizontal plane.

(3) –105 dB (W/m²) in any 1 MHz band for angles of arrival between 25 and 90 degrees above the horizontal plane.

(d) In addition to the limits specified in paragraph (c) of this section, the power flux-density across the 200 MHz band 18.6–18.8 GHz produced at the Earth's surface by emissions from a space station under assumed free-space propagation conditions shall not exceed –95 dB (W/m²) for all angles of arrival. This limit may be exceeded by up to 3 dB for no more than 5% of the time.

(e) In the 18.8–19.3 GHz frequency band, the power flux-density at the Earth's surface produced by emissions from a space station for all conditions and for all methods of modulation shall not exceed the following values:

power-flux density in the space-to-Earth direction (EPFD_{down}), at any point on the Earth's surface, produced by emissions from all co-frequency space stations of a single non-geostationary-satellite orbit (NGSO) system operating in the Fixed-Satellite Service (FSS) shall not exceed the following limits for the given percentages of time. Tables 1G and 2G follow:

TABLE 1G—SINGLE-ENTRY EPFD_{down} LIMITS FOR PROTECTION OF 0.6, 1.2, 3 AND 10 METER GSO FSS EARTH STATION ANTENNAS^{1 2}

| Frequency band (GHz) for International Allocations | Single-entry EPFD _{down} dB(W/m ²) | Percentage of time during which EPFD _{down} level may not be exceeded | Reference bandwidth (kHz) | Reference antenna diameter and reference radiation pattern ³ |
|--|--|--|---------------------------|---|
| 10.7–11.7 in all Regions; 11.7–12.2 in Region 2; 12.2–12.5 in Region 3; and 12.5–12.75 in Regions 1 and 3. | –175.4 –174 –170.8 –165.3 –160.4 –160 –160 | 0 90 99 99.73 99.991 99.997 100 | 40 | 60 cm, Recommendation ITU-R S.1428. |
| 10.7–11.7 in all Regions; 11.7–12.2 in Region 2; 12.2–12.5 in Region 3; and 12.5–12.75 in Regions 1 and 3. | –181.9 –178.4 –173.4 –173 –164 –161.6 –161.4 –160.8 –160.5 –160 –160 | 0 99.5 99.74 99.857 99.954 99.984 99.991 99.997 99.997 99.9993 100 | 40 | 1.2 m, Recommendation ITU-R S.1428. |
| 10.7–11.7 in all Regions; 11.7–12.2 in Region 2; 12.2–12.5 in Region 3; and 12.5–12.75 in Regions 1 and 3. | –190.45 –189.45 –187.45 –182.4 –182 –168 –164 –162 –160 –160 | 0 90 99.5 99.7 99.855 99.971 99.988 99.995 99.999 100 | 40 | 3 m, Recommendation ITU-R S.1428. |
| 10.7–11.7 in all Regions; 11.7–12.2 in Region 2; 12.2–12.5 in Region 3; and 12.5–12.75 in Regions 1 and 3. | –195.45 –195.45 –190 –190 –172.5 –160 –160 | 0 99 99.65 99.71 99.99 99.998 100 | 40 | 10 m, Recommendation ITU-R S.1428. |

¹ In addition to the limits shown in Table 1G, the limits shown in Table 2G shall apply to all antenna sizes greater than 60 cm in the frequency bands listed in Table 1G.

² For each reference antenna diameter, the limit consists of the complete curve on a plot which is linear in decibels for the EPFD levels and logarithmic for the time percentages, with straight lines joining the data points.

³ The earth station antenna reference radiation patterns are to be used only for the calculation of interference from NGSO FSS systems into GSO FSS systems.

TABLE 2G—SINGLE-ENTRY EPFD_{down} LIMITS RADIATED BY NON-GSO FSS SYSTEMS AT CERTAIN LATITUDES

| 100% of the time EPFD _{down} dB(W/(m ² /40 kHz)) | Latitude (North or South in degrees) |
|--|--------------------------------------|
| –160 | 0 < Latitude ≤57.5. |
| –160 + 3.4 (57.5 – Latitude)/4 | 57.5 < Latitude ≤63.75 |
| –165.3 | 63.75 ≤ Latitude |

NOTE TO PARAGRAPH (g): These limits relate to the equivalent power flux density, which would be obtained under free-space propagation conditions, for all conditions and for all methods of modulation.

(h) In the 10.7–11.7 GHz and 11.7–12.2 GHz bands, the aggregate equivalent

power-flux density in the space-to-Earth direction (EPFD_{down}), at any point on the Earth's surface, produced by emissions from all co-frequency space stations of all non-geostationary-satellite orbit systems operating in the Fixed-Satellite Service (FSS) shall not

exceed the following limits for the given percentages of time. Tables 1H and 2H follow:

TABLE 1H—AGGREGATE EPFD_{down} LIMITS FOR PROTECTION OF 0.6, 1.2, 3 AND 10 METER GSO FSS EARTH STATION ANTENNAS ¹

| Frequency band (GHz) for International Allocations | Aggregate EPFD _{down} dB(W/m ²) | Percentage of time during which EPFD _{down} may not be exceeded | Reference bandwidth (kHz) | Reference antenna diameter and reference radiation pattern ² |
|--|--|---|---------------------------|---|
| 10.7–11.7 in all Regions; 11.7–12.2 in Region 2; 12.2–12.5 in Region 3; and 12.5–12.75 in Regions 1 and 3. | –170 –168.6 –165.3 –160.4 –160 –160 | 0 90 99 99.97 99.99 100 | 40 | 60 cm, Recommendation ITU-R S.1428. |
| 10.7–11.7 in all Regions; 11.7–12.2 in Region 2; 12.2–12.5 in Region 3; and 12.5–12.75 in Regions 1 and 3. | –176.5 –173 –164 –161.6 –164.4 –160.8 –160.5 –160 –160 | 0 99.5 99.84 99.945 99.97 99.99 99.99 99.9975 100 | 40 | 1.2 m, Recommendation ITU-R S.1428. |
| 10.7–11.7 in all Regions; 11.7–12.2 in Region 2; 12.2–12.5 in Region 3; and 12.5–12.75 in Regions 1 and 3. | –185 –184 –182 –168 –164 –162 –160 –160 | 0 90 99.5 99.9 99.96 99.982 99.997 100 | 40 | 3 m, Recommendation ITU-R S.1428. |
| 10.7–11.7 in all Regions; 11.7–12.2 in Region 2; 12.2–12.5 in Region 3; and 12.5–12.75 in Regions 1 and 3. | –190 –190 –166 –160 –160 | 0 99 99.99 99.998 100 | 40 | 10 m, Recommendation ITU-R S.1428. |

¹ In addition to the limits shown in Table 1H, the aggregate EPFD_{down} limits shown in Table 2H shall apply to all antenna sizes greater than 60 cm in the frequency bands listed in Table 1H.

² The earth station antenna reference patterns are to be used only for the calculation of interference from NGSO FSS systems into GSO FSS systems.

TABLE 2H—SINGLE-ENTRY EPFD_{down} LIMITS RADIATED BY NON-GSO FSS SYSTEMS AT CERTAIN LATITUDES

| 100% of the time EPFD _{down} dB(W/(m ² /40 kHz)) | Latitude (North or South in degrees) |
|--|--------------------------------------|
| –160 | 0 < Latitude ≤ 57.5 |
| –160 + 3.4 (57.5 – Latitude)/4 | 57.5 < Latitude ≤ 63.75 |
| –165.3 | 63.75 ≤ Latitude |

NOTE TO PARAGRAPH (h): These limits relate to the equivalent power flux density, which would be obtained under free-space propagation conditions, for all conditions and for all methods of modulation.

(i) In the 10.7–11.7 GHz and 11.7–12.2 GHz bands, the additional operational equivalent power-flux density, in the space-to-Earth direction, (additional

operational EPFD_{down}) at any point on the Earth's surface, produced by actual operational emissions from all co-frequency space stations of a non-geostationary-satellite orbit (NGSO) system operating in the Fixed-Satellite Service (FSS) shall not exceed the following operational limits for the given percentages of time:

ADDITIONAL OPERATIONAL LIMITS ON THE EPFD_{down} RADIATED BY NON-GSO FSS SYSTEMS INTO 3 M AND 10 M GSO FSS EARTH STATION ANTENNAS

| EPFD _{down} dB(W/(m ² /40 kHz)) | Percentage of time during which EPFD _{down} may not be exceeded | Receive GSO earth station antenna diameter (m) |
|---|--|--|
| –182 | 99.9. | 3. |
| –179 | 99.94. | |
| –176 | 99.97. | |
| –171 | 99.98. | |
| –168 | 99.984 | |
| –165 | 99.993. | |
| –163 | 99.999. | |
| –161.25 | 99.99975. | |
| –161.25 | 100. | |
| –185 | 99.97. | 10. |
| –183 | 99.98. | |
| –179 | 99.99. | |
| –175 | 99.996. | |
| –171 | 99.998 | |
| –168 | 99.999. | |
| –166 | 99.9998. | |
| –166 | 100. | |

NOTE TO PARAGRAPH (i): These limits relate to the equivalent power flux density, which is obtained under free-space propagation conditions, for all conditions and for all methods of modulation.

(j) In the 10.7–11.7 GHz and 11.7–12.2 GHz bands, the operational equivalent power-flux density, in the space-to-Earth direction, (operational EPFD_{down})

at any point on the Earth's surface, produced by actual operational emissions from the in-line co-frequency space station of a non-geostationary-satellite orbit (NGSO) system operating in the Fixed-Satellite Service (FSS) shall not exceed the following operational limits for 100% of the time:

OPERATIONAL LIMITS TO THE EPFD_{down} RADIATED BY NON-GSO FSS SYSTEMS IN CERTAIN FREQUENCY BANDS¹

| Frequency band (GHz) for international allocations | EPFD _{down} dB(W/m ²) | Percentage of time during which EPFD _{down} may not be exceeded | Reference bandwidth (kHz) | Receive GSO earth station antenna diameter ² (m) | Orbital inclination of GSO satellite (degrees) |
|--|---|--|---------------------------|---|--|
| Prior to 31 December 2005: 10.7–11.7 in all Regions; 11.7–12.2 in Regions 2; 12.2–12.5 in Region 3; and 12.5–12.75 in Regions 1 and 3 | –163 –166 –167.5 –169.5 100 40 | 3 6 9 ≥18 ≤2.5 | | | |
| Prior to 31 December 2005: 10.7–11.7 in all Regions; 11.7–12.2 in Region 2; 12.2–12.5 in Region 3; and 12.5–12.75 in Regions 1 and 3 | –160 –163 –164.5 –166.5 100 40 | 3 6 9 ≥18 >2.5 and ≤4.5 | | | |

OPERATIONAL LIMITS TO THE EPFD_{down} RADIATED BY NON-GSO FSS SYSTEMS IN CERTAIN
FREQUENCY BANDS ¹—Continued

| Frequency band (GHz) for International allocations | EPFD _{down} dB(W/m ²) | Percentage of time dur- ing which EPFD _{down} may not be exceeded | Reference bandwidth (kHz) | Receive GSO earth station an- tenna di- ameter ² (m) | Orbital inclination of GSO satellite (degrees) |
|--|--|---|---------------------------------|---|--|
| From 31 December 2005: 10.7–11.7 in all Regions; 11.7–12.2 in Region 2; 12.2–12.5 in Region 3; and 12.5–12.75 in Regions 1 and 3 | – 161.25 – 164 – 165.5 – 167.5 100 40 | 3 6 9 ≥18 ≤2.5 | | | |
| From 31 December 2005: 10.7–11.7 in all Regions; 11.7–12.2 in Region 2; 12.2–12.5 in Region 3; and 12.5–12.75 in Regions 1 and 3 | – 158.25 – 161 – 162.5 – 164.5 100 40 | 3 6 9 ≥18 >2.5 and ≤4.5 | | | |

¹The operational limits on the EPFD_{down} radiated by non-GSO FSS systems shall be the values given in Table 2G or this table, whichever are the more stringent.

²For antenna diameters between the values given in this table, the limits are given by linear interpolation using a linear scale for EPFD_{down} in decibels and a logarithmic scale for antenna diameter in meters.

NOTE TO PARAGRAPH (j): These limits relate to the operational equivalent power flux-density which would be obtained under free-space propagation conditions, for all conditions, for all methods of modulation and for the specified inclined GSO FSS operations.

(k) In the 12.75–13.15 GHz, 13.2125–13.25 GHz and 13.75–14.5 GHz bands, the equivalent power flux-density, in the Earth-to-space direction, (EPFD_{up}) pro-

duced at any point on the geostationary satellite orbit (GSO) by the emissions from all co-frequency earth stations in a non-geostationary satellite orbit Fixed-Satellite Service (NGSO FSS) system, for all conditions and for all methods of modulation, shall not exceed the following limits for the specified percentages of time limits:

LIMITS TO THE EPFD_{up} RADIATED BY NGSO FSS SYSTEMS IN CERTAIN FREQUENCY BANDS

| Frequency band (GHz) for International Allocations | EPFD _{up} dB(W/m ²) | Percentage of time dur- ing which EPFD _{up} may not be exceeded | Reference bandwidth (kHz) | Reference antenna beam- width and reference radi- ation pattern ¹ |
|--|---|---|---------------------------------|--|
| 12.5–12.75; 12.75–13.25; 13.75–14.5 | – 160 | 100 | 40 | 4° ITU-R S.672–4, Ls= – 20 |

¹For the case of L_s = – 10, the values a = 1.83 and b = 6.32 should be used in the equations in the Annex of Recommendation ITU-R S.672–4 for single-feed circular beams. In all cases of L_s, the parabolic main beam equation should start at zero.

NOTE TO PARAGRAPH (k): These limits relate to the uplink equivalent power flux density, which would be obtained under free-space propagation conditions, for all conditions and for all methods of modulation.

(l) In the 11.7–12.2 GHz and 12.5–12.75 GHz bands in Region 3, 11.7–12.5 GHz bands in Region 1, and 12.2–12.7 GHz band in Region 2, the single-entry

equivalent power-flux density, in the space-to-Earth direction, (EPFD_{down}), at any point on the Earth's surface, produced by emissions from all co-frequency space stations of a single non-geostationary-satellite orbit (NGSO) system operating in the Fixed-Satellite

§ 25.208

47 CFR Ch. I (10–1–14 Edition)

Service (FSS) shall not exceed the following limits in Tables 1L and 2L for the given percentages of time:

TABLE 1L—SINGLE-ENTRY EPFD_{down} LIMITS FOR PROTECTION OF 30, 45, 60, 90, 120, 180, 240 AND 300 CM GSO BSS EARTH STATION ANTENNAS^{1 2 3 5}

| Frequency band (GHz) for international allocations | EPDF _{down} dB(W/m ²) | Percentage of time during which EPFD _{down} level may not be exceeded | Reference bandwidth (kHz) | Reference antenna diameter and reference radiation pattern ⁴ |
|--|---|--|---------------------------|---|
| 11.7–12.5 in Region 1; 1.7–12.2 and 12.5–12.75 in Region 3; 12.2–12.7 in Region 2. | –165.841 | 0 | 40 | 30 cm Recommendation ITU-R BO.1443 Annex 1 |
| | –165.541 | 25 | | |
| | –164.041 | 96 | | |
| | –158.6 | 98.857 | | |
| | –158.6 | 99.429 | | |
| | –158.33 | 99.429 | | |
| | –158.33 | 99.429 | | |
| | | 100 | | |
| | –175.441 | 0 | | |
| | –172.441 | 66 | | |
| 11.7–12.5 in Region 1; 1.7–12.2 and 12.5–12.75 in Region 3; 12.2–12.7 in Region 2. | –169.441 | 97.75 | 40 | 45 cm Recommendation ITU-R BO.1443 Annex 1 |
| | –164 | 99.357 | | |
| | –160.75 | 99.809 | | |
| | –160 | 99.986 | | |
| | –160 | 100 | | |
| | | | | |
| 11.7–12.5 in Region 1; 1.7–12.2 and 12.5–12.75 in Region 3; 12.2–12.7 in Region 2. | –176.441 | 0 | 40 | 60 cm Recommendation ITU-R BO. 1443 Annex 1 |
| | –173.191 | 97.8 | | |
| | –167.75 | 99.371 | | |
| | –162 | 99.886 | | |
| | –161 | 99.943 | | |
| | –160.2 | 99.971 | | |
| | –160 | 99.997 | | |
| | –160 | 100 | | |
| 11.7–12.5 in Region 1; 1.7–12.2 and 12.5–12.75 in Region 3; 12.2–12.7 in Region 2. | –178.94 | 0 | 40 | 90 cm Recommendation ITU-R BO.1443 Annex 1 |
| | –178.44 | 33 | | |
| | –176.44 | 98 | | |
| | –171 | 99.429 | | |
| | –165.5 | 99.714 | | |
| | –163 | 99.857 | | |
| | –161 | 99.943 | | |
| | –160 | 99.991 | | |
| | –160 | 100 | | |
| 11.7–12.5 in Region 1; 1.7–12.2 and 12.5–12.75 in Region 3; 12.2–12.7 in Region 2. | –182.44 | 0 | 40 | 120 cm Recommendation ITU-R BO.1443 Annex 1 |
| | –180.69 | 90 | | |
| | –179.19 | 98.9 | | |
| | –178.44 | 98.9 | | |
| | –174.94 | 99.5 | | |
| | –173.75 | 99.68 | | |
| | –173 | 99.68 | | |
| | –169.5 | 99.85 | | |
| | –167.8 | 99.915 | | |
| | –164 | 99.94 | | |
| | –161.9 | 99.97 | | |
| | –161 | 99.99 | | |
| | –160.4 | 99.998 | | |
| | –160 | 100 | | |
| 11.7–12.5 in Region 1; 1.7–12.2 and 12.5–12.75 in Region 3; 12.2–12.7 in Region 2. | –184.941 | 0 | 40 | 180 cm ³ Recommendation ITU-R BO.1443 Annex 1 |
| | –184.101 | 33 | | |
| | –181.691 | 98.5 | | |
| | –176.25 | 99.571 | | |
| | –163.25 | 99.946 | | |
| | –161.5 | 99.974 | | |
| | –160.35 | 99.993 | | |
| | –160 | 99.999 | | |
| | –160 | 100 | | |

TABLE 1L—SINGLE-ENTRY EPFD_{down} LIMITS FOR PROTECTION OF 30, 45, 60, 90, 120, 180, 240 AND 300 CM GSO BSS EARTH STATION ANTENNAS^{1 2 3 5}—Continued

| Frequency band (GHz) for international allocations | EPFD _{down} dB(W/m ²) | Percentage of time during which EPFD _{down} level may not be exceeded | Reference bandwidth (kHz) | Reference antenna diameter and reference radiation pattern ⁴ |
|--|--|--|---------------------------|---|
| 11.7–12.5 in Region 1; 1.7–12.2 and 12.5–12.75 in Region 3; 12.2–12.7 in Region 2. | –187.441 –186.341 –183.441 –178 –161.4 –161.9 –160.5 –160 –160 | 0 33 99.25 99.786 99.957 99.983 99.994 99.999 100 | 40 | 240 cm ² Recommendation ITU-R BO.1443 Annex 1 |
| 11.7–12.5 in Region 1; 1.7–12.2 and 12.5–12.75 in Region 3; 12.2–12.7 in Region 2. | –191.941 –189.441 –185.941 –180.5 –173 –167 –162 –160 –160 | 0 33 99.5 99.857 99.914 99.951 99.983 99.991 100 | 40 | 300 cm Recommendation ITU-R BO.1443 Annex 1 |

¹For BSS antenna diameters 180 cm, 240 cm and 300 cm, in addition to the single-entry limits shown in Table 1L, the limits in Table 2L shall also apply in the frequency band listed in Table 1L.

²For 240 cm GSO BSS earth station antennas located in Alaska, communicating with GSO BSS satellites at the 91° W.L., 101° W.L., 110° W.L., 119° W.L. and 148° W.L. nominal orbital locations with elevation angles greater than 5°, –167 dB(W/(m²/40 kHz)) single-entry 100% of the time operational EPFD_{down} limit also applies to receive antennas.

³For 180 cm GSO BSS earth station antennas located in Hawaii communicating with GSO BSS satellites that are operational as of December 30, 1999 at the 110° W.L., 119° W.L. and 148° W.L. nominal orbital positions, –162.5 dB(W/(m²/40 kHz)) single-entry 100% of the time operational EPFD_{down} limit also applies.

⁴Under the section reference pattern of Annex 1 to Recommendation ITU-R BO.1443 shall be used only for the calculation of interference from non-GSO FSS systems into BSS systems.

⁵For each reference antenna diameter, the limit consists of the complete curve on a plot which is linear in decibels for the EPFD levels and logarithmic for the time percentages, with straight line joining the data points.

TABLE 2L—SINGLE-ENTRY EPFD_{down} LIMITS RADIATED BY NON-GSO FSS SYSTEMS AT CERTAIN LATITUDES

| 100% of the time EPFD _{down} dB(W/(m ² /40 kHz)) | Latitude (North or South in degrees) |
|--|--------------------------------------|
| –160.0 | 0 ≤ Latitude ≤ 57.5 |
| –160.0 + 3.4 (57.5 – Latitude)/4 | 57.5 ≤ Latitude ≤ 63.75 |
| –165.3 | 63.75 ≤ Latitude |

NOTE TO PARAGRAPH (1): These limits relate to the equivalent power flux density, which would be obtained under free-space propagation conditions, for all conditions and for all methods of modulation.

(m) In the 11.7–12.2 GHz and 12.5–12.75 GHz bands in Region 3, 11.7–12.5 GHz bands in Region 1, and 12.2–12.7 GHz band in Region 2, the aggregate equivalent power-flux density, in the space-

to-Earth direction, (EPFD_{down}) at any point on the Earth's surface, produced by emissions from all co-frequency space stations of all non-geostationary-satellite orbit systems operating in the Fixed-Satellite Service (FSS) shall not exceed the following limits in Tables 1M and 2M for the given percentages of time:

TABLE 1M—AGGREGATE EPFD_{down} LIMITS FOR PROTECTION OF 30, 45, 60, 90, 120, 180, 240 AND 300 CM GSO BSS EARTH STATION ANTENNAS ^{1 2 3 5}

| Frequency band (GHz) for international allocations | EPFD _{down} dB (W/m ²) | Percentage of time dur- ing which EPFD _{down} level may not be ex- ceeded | Reference bandwidth (kHz) | Reference antenna diame- ter, and reference radiation pattern ⁴ |
|---|---|--|---------------------------------|--|
| 11.7–12.5 in Region 1; 11.7–12.2 and 12.5–12.75 in Region 3; 12.2–12.7 in Region 2. | – 160.4 – 160.1 – 158.6 – 158.6 – 158.33 – 158.33 | 0 25 96 98 98 100 | 40 | 30 cm Recommendation ITU-R BO.1443 Annex 1. |
| 11.7–12.5 in Region 1; 11.7–12.2 and 12.5–12.75 in Region 3; 12.2–12.7 in Region 2. | – 170 – 167 – 164 – 160.75 – 160 – 160 | 0 66 97.75 99.33 99.95 100 | 40 | 45 cm Recommendation ITU-R BO.1443 Annex 1. |
| 11.7–12.5 in Region 1; 11.7–12.2 and 12.5–12.75 in Region 3; 12.2–12.7 in Region 2. | – 171 – 168.75 – 167.75 – 162 – 161 – 160.2 – 160 – 160 | 0 90 97.8 99.6 99.8 99.9 99.99 100 | 40 | 60 cm Recommendation ITU-R BO.1443 Annex 1. |
| 11.7–12.5 in Region 1; 11.7–12.2 and 12.5–12.75 in Region 3; 12.2–12.7 in Region 2. | – 173.75 – 173 – 171 – 165.5 – 163 – 161 – 160 – 160 | 0 33 98 99.1 99.5 99.8 99.97 100 | 40 | 90 cm Recommendation ITU-R BO.1443 Annex 1. |
| 11.7–12.5 in Region 1; 11.7–12.2 and 12.5–12.75 in Region 3; 12.2–12.7 in Region 2. | – 177 – 175.25 – 173.75 – 173 – 169.5 – 167.8 – 164 – 161.9 – 161 – 160.4 – 160 | 0 90 98.9 98.9 99.5 99.7 99.82 99.9 99.965 99.993 100 | 40 | 120 cm Recommendation ITU-R BO.1443 Annex 1. |
| 11.7–12.5 in Region 1; 11.7–12.2 and 12.5–12.75 in Region 3; 12.2–12.7 in Region 2. | – 179.5 – 178.66 – 176.25 – 163.25 – 161.5 – 160.35 – 160 – 160 | 0 33 98.5 99.81 99.91 99.975 99.995 100 | 40 | 180 cm Recommendation ITU-R BO.1443 Annex 1. |
| 11.7–12.5 in Region 1; 11.7–12.2 and 12.5–12.75 in Region 3; 12.2–12.7 in Region 2. | – 182 – 180.9 – 178 – 164.4 – 161.9 – 160.5 – 160 – 160 | 0 33 99.25 99.85 99.94 99.98 99.995 100 | 40 | 240 cm Recommendation ITU-R BO.1443 Annex 1. |

TABLE 1M—AGGREGATE EPFD_{down} LIMITS FOR PROTECTION OF 30, 45, 60, 90, 120, 180, 240 AND 300 CM GSO BSS EARTH STATION ANTENNAS^{1 2 3 5}—Continued

| Frequency band (GHz) for international allocations | EPFD _{down} dB (W/m ²) | Percentage of time dur- ing which EPFD _{down} level may not be ex- ceeded | Reference bandwidth (kHz) | Reference antenna diame- ter, and reference radiation pattern ⁴ |
|---|--|--|---------------------------------|--|
| 11.7–12.5 in Region 1; 11.7–12.2 and 12.5–12.75 in Region 3; 12.2–12.7 in Region 2. | –186.5 –184 –180.5 –173 –167 –162 –160 –160 | 0 33 99.5 99.7 99.83 99.94 99.97 100 | 40 | 300 cm Recommendation ITU-R BO.1443 Annex 1. |

¹ For BSS antenna diameters 180 cm, 240 cm and 300 cm, in addition to the aggregate limit shown in Table 1M, the limits in Table 2M shall also apply.

² For 240 cm GSO BSS earth station antennas located in Alaska, communicating with GSO BSS satellites at the 91° W.L., 101° W.L., 110° W.L., 119° W.L. and 148° W.L. nominal orbital locations with elevation angles greater than 5°, –167 dB(W/(m²/40 kHz)) aggregate 100% of the time operational EPFD_{down} limit also applies to receive antennas.

³ For 180 cm GSO BSS earth station antennas located in Hawaii communicating with GSO BSS satellites that are operational as of December 30, 1999 at the 110° W.L., 119° W.L. and 148° W.L. nominal orbital positions, –162.5 dB(W/(m²/40 kHz)) aggregate 100% of the time operational EPFD_{down} limit also applies.

⁴ Under the section reference pattern of Annex 1 to Recommendation ITU-R BO.1443 shall be used only for the calculation of interference from non-GSO FSS systems into GSO BSS systems.

⁵ For each reference antenna diameter, the limit consists of the complete curve on a plot which is linear in decibels for the EPFD levels and logarithmic for the time percentages, with straight line joining the data points.

TABLE 2M—AGGREGATE EPFD_{down} LIMITS RADIATED BY NON-GSO FSS SYSTEMS AT CERTAIN LATITUDES

| 00% of the time EPFD _{down} dB(W/(m ² /40 kHz)) | Latitude (North or South in degrees) |
|---|--------------------------------------|
| 160.0 | 0 ≤ Latitude ≤ 57.5. |
| 160.0 + 3.4 (57.5 – Latitude)/4 | 57.5 ≤ Latitude ≤ 63.75. |
| 165.3 | 63.75 ≤ Latitude . |

NOTE TO PARAGRAPH (m): These limits relate to the equivalent power flux density, which would be obtained under free-space propagation conditions, for all conditions and for all methods of modulation.

(n) The power-flux density at the Earth's surface produced by emissions from a space station in the Fixed-Sat-

ellite Service (space-to-Earth), for all conditions and for all methods of modulation, shall not exceed the limits given in Table N. These limits relate to the power flux-density which would be obtained under assumed free-space conditions.

TABLE N—LIMITS OF POWER-FLUX DENSITY FROM SPACE STATIONS IN THE BAND 6700–7075 MHz

| Frequency band | Limit in dB (W/m ²) for angle of arrival (δ) above the horizontal plane | | | Reference band-width |
|---------------------|---|-----------------------|------------|----------------------|
| | 0°–5° | 5°–25° | 25°–90° | |
| 6700–6825 MHz | –137 | –137 + 0.5(δ–5) | –127 | 1 MHz. |
| 6825–7075 MHz | –154 | –154 + 0.5(δ–5) | –144 | 4 kHz. |
| | and | and | and | |
| | –134 | –134 + 0.5(δ–5) | –124 | 1 MHz. |

(o) In the band 12.2–12.7 GHz, for NGSO FSS space stations, the specified low-angle power flux-density at the Earth's surface produced by emissions from a space station shall not be exceeded into an operational MVDDS receiver:

(1) –158 dB(W/m²) in any 4 kHz band for angles of arrival between 0 and 2 degrees above the horizontal plane; and

(2) –158 + 3.33(δ–2) dB(W/m²) in any 4 kHz band for angles of arrival (δ) (in degrees) between 2 and 5 degrees above the horizontal plane.

NOTE TO PARAGRAPH (o): These limits relate to the power flux density, which would be obtained under assumed free-space propagation conditions.

(p) The power flux-density at the Earth's surface produced by emissions from a space station in either the Earth exploration-satellite service in the band 25.5–27 GHz or the inter-satellite service in the band 25.25–27.5 GHz for all conditions and for all methods of modulation shall not exceed the following values:

–115 dB(W/m²) in any 1 MHz band for angles of arrival between 0 and 5 degrees above the horizontal plane;

–115 + 0.5(–5) dB(W/m²) in any 1 MHz band for angles of arrival between 5 and 25 degrees above the horizontal plane;

–105 dB(W/m²) in any 1 MHz band for angles of arrival between 25 and 90 degrees above the horizontal plane.

These limits relate to the power flux-density which would be obtained under assumed free-space propagation conditions.

(q) In the band 37.5–40.0 GHz, the power flux-density at the Earth's surface produced by emissions from a geostationary space station for all methods of modulation shall not exceed the following values.

(1) This limit relates to the power flux-density which would be obtained under assumed free space conditions (that is, when no allowance is made for propagation impairments such as rain-fade):

–139 dB(W/m²) in any 1 MHz band for angles of arrival between 0 and 5 degrees above the horizontal plane;

–139 + 4/3 (δ–5) dB(W/m²) in any 1 MHz band for angles of arrival δ (in degrees) between 5 and 20 degrees above the horizontal plane; and

–119 + 0.4 (δ–20) dB(W/m²) in any 1 MHz band for angles of arrival δ (in degrees) between 20 and 25 degrees above the horizontal plane;

–117 dB(W/m²) in any 1 MHz band for angles of arrival between 25 and 90 degrees above the horizontal plane;

(2) This limit relates to the maximum power flux-density which would be obtained anywhere on the surface of the Earth during periods when FSS system raises power to compensate for

rain-fade conditions at the FSS Earth station:

–127 dB(W/m²) in any 1 MHz band for angles of arrival between 0 and 5 degrees above the horizontal plane;

–127 + 4/3 (δ–5) dB(W/m²) in any 1 MHz band for angles of arrival δ (in degrees) between 5 and 20 degrees above the horizontal plane; and

–107 + 0.4 (δ–20) dB(W/m²) in any 1 MHz band for angles of arrival δ (in degrees) between 20 and 25 degrees above the horizontal plane;

–105 dB(W/m²) in any 1 MHz band for angles of arrival between 25 and 90 degrees above the horizontal plane.

NOTE TO PARAGRAPH (q): The conditions under which satellites may exceed the power flux-density limits for normal free space propagation described in paragraph (p)(1) to compensate for the effects of rain fading are under study and have therefore not yet been defined. Such conditions and the extent to which these limits can be exceeded will be the subject of a further rulemaking by the Commission on the satellite service rules.

(r) In the band 37.5–40.0 GHz, the power flux-density at the Earth's surface produced by emissions from a non-geostationary space station for all methods of modulation shall not exceed the following values:

(1) This limit relates to the power flux-density which would be obtained under assumed free space conditions (that is, when no allowance is made for propagation impairments such as rain-fade):

–132 dB(W/m²) in any 1 MHz band for angles of arrival between 0 and 5 degrees above the horizontal plane;

–132 + 0.75 (δ–5) dB(W/m²) in any 1 MHz band for angles of arrival δ (in degrees) between 5 and 25 degrees above the horizontal plane; and

–117 dB(W/m²) in any 1 MHz band for angles of arrival between 25 and 90 degrees above the horizontal plane;

(2) This limit relates to the maximum power flux-density which would be obtained anywhere on the surface of the Earth during periods when FSS system raises power to compensate for rain-fade conditions at the FSS Earth station:

–120 dB(W/m²) in any 1 MHz band for angles of arrival between 0 and 5 degrees above the horizontal plane;

–120 + 0.75 (δ –5) dB(W/m²) in any 1 MHz band for angles of arrival δ (in degrees) between 5 and 25 degrees above the horizontal plane; and

–105 dB(W/m²) in any 1 MHz band for angles of arrival between 25 and 90 degrees above the horizontal plane.

NOTE TO PARAGRAPH (r): The conditions under which satellites may exceed these power flux-density limits for normal free space propagation described in paragraph (q)(1) to compensate for the effects of rain fading are under study and have therefore not yet been defined. Such conditions and the extent to which these limits can be exceeded will be the subject of a further rule-making by the Commission on the satellite service rules.

(s) In the 40.0–40.5 GHz band, the power flux density at the Earth's surface produced by emissions from a space station for all conditions and for all methods of modulation shall not exceed the following values:

–115 dB(W/m²) in any 1 MHz band for angles of arrival between 0 and 5 degrees above the horizontal plane;

–115 + 0.5 (δ –5) dB(W/m²) in any 1 MHz band for angles of arrival δ (in degrees) between 5 and 25 degrees above the horizontal plane; and

–105 dB(W/m²) in any 1 MHz band for angles of arrival between 25 and 90 degrees above the horizontal plane;

NOTE TO PARAGRAPH (s): These limits relate to the power flux-density that would be obtained under assumed free-space propagation conditions.

(t) In the band 40.5–42.0 GHz, the power flux density at the Earth's surface produced by emissions from a non-geostationary space station for all conditions and for all methods of modulation shall not exceed the following values:

–115 dB(W/m²) in any 1 MHz band for angles of arrival between 0 and 5 degrees above the horizontal plane;

–115 + 0.5 (δ –5) dB(W/m²) in any 1 MHz band for angles of arrival δ (in degrees) between 5 and 25 degrees above the horizontal plane; and

–105 dB(W/m²) in any 1 MHz band for angles of arrival between 25 and 90 degrees above the horizontal plane;

NOTE TO PARAGRAPH (t): These limits relate to the power flux density that would be obtained under assumed free-space propagation conditions.

(u) In the band 40.5–42.0 GHz, the power flux-density at the Earth's surface produced by emissions from a geostationary space station for all conditions and for all methods of modulation shall not exceed the following values:

–120 dB(W/m²) in any 1 MHz band for angles of arrival between 0 and 5 degrees above the horizontal plane;

–120 + (δ –5) dB(W/m²) in any 1 MHz band for angles of arrival δ (in degrees) between 5 and 15 degrees above the horizontal plane;

–110 + 0.5 (δ –15) dB(W/m²) in any 1 MHz band for angles of arrival δ (in degrees) between 15 and 25 degrees above the horizontal plane; and

–105 dB(W/m²) in any 1 MHz band for angles of arrival between 25 and 90 degrees above the horizontal plane;

NOTE TO PARAGRAPH (u): These limits relate to the power flux-density that would be obtained under assumed free-space propagation conditions.

(v) In the band 2496–2500 MHz, the power flux-density at the Earth's surface produced by emissions from non-geostationary space stations for all conditions and all methods of modulation shall not exceed the following values (these values are obtained under assumed free-space propagation conditions):

(1) –144 dB (W/m²) in 4 kHz for all angles of arrival between 0 and 5 degrees above the horizontal plane; –144 dB (W/m²) + 0.65(δ – 5) in 4 kHz for all angles of arrival between 5 and 25 degrees above the horizontal plane; and

–131 dB (W/m²) in 4 kHz and for all angles of arrival between 25 and 90 degrees above the horizontal plane.

(2) –126 dB (W/m²) in 1 MHz for all angles of arrival between 0 and 5 degrees above the horizontal plane; –126 dB (W/m²) + 0.65(δ – 5) in 1 MHz for all angles of arrival between 5 and 25 degrees above the horizontal plane; and

–113 dB (W/m²) in 1 MHz and for all angles of arrival between 25 and 90 degrees above the horizontal plane.

(w) The power flux density at the Earth's surface produced by emissions from a 17/24 GHz BSS space station operating in the 17.3–17.7 GHz band for all conditions and all methods of modulation must not exceed the regional power flux density levels prescribed in

§ 25.209

paragraphs (w)(1) through (4) of this section.

(1) In the region of the contiguous United States, located south of 38° North Latitude and east of 100° West Longitude: -115 dBW/m²/MHz.

(2) In the region of the contiguous United States, located north of 38° North Latitude and east of 100° West Longitude: -118 dBW/m²/MHz.

(3) In the region of the contiguous United States, located west of 100° West Longitude: -121 dBW/m²/MHz.

(4) For all regions outside of the contiguous United States including Alaska and Hawaii: -115 dBW/m²/MHz.

NOTE TO PARAGRAPH (w): These limits pertain to the power flux-density that would be obtained under assumed free-space propagation conditions.

[48 FR 40255, Sept. 6, 1983]

| | | | |
|--------------------------------|-----------|-----------|----------------|
| 29-25log ₁₀ θ | dBi | For | 1.5° ≤ θ ≤ 7° |
| 8 | dBi | For | 7° < θ ≤ 9.2° |
| 32-25log ₁₀ θ | dBi | For | 9.2° < θ ≤ 48° |
| - 10 | dBi | For | 48° < θ ≤ 180° |

where θ is the angle in degrees from the axis of the main lobe, and dBi refers to dB relative to an isotropic radiator. For the purposes of this section, the peak gain of an individual sidelobe may not exceed the envelope defined above for θ between 1.5 and 7.0 degrees. For θ greater than 7.0 degrees, the envelope may be exceeded by no more than 10% of the sidelobes, provided no individual

EDITORIAL NOTE: For FEDERAL REGISTER citations affecting § 25.208, see the List of CFR Sections Affected, which appears in the Finding Aids section of the printed volume and at www.fdsys.gov.

§ 25.209 Earth station antenna performance standards.

(a) Except as provided in paragraph (f) of this section, the gain of any antenna to be employed in transmission from an earth station in the Fixed-Satellite Service shall lie below the relevant envelope defined in paragraphs (a)(1) through (4) of this section:

(1) In the plane of the geostationary satellite orbit as it appears at the particular earth station location, for earth stations not operating in the 20/30 GHz band or conventional Ku-band:

sidelobe exceeds the gain envelope given above by more than 3 dB.

(2) In the plane of the geostationary satellite orbit as it appears at the particular earth station location, for earth stations operating in the 20/30 GHz band or conventional Ku-band:

| | | | |
|--------------------------------|-----------|-----------|----------------|
| 29-25log ₁₀ θ | dBi | For | 1.5° ≤ θ ≤ 7° |
| 8 | dBi | For | 7° < θ ≤ 9.2° |
| 32-25log ₁₀ θ | dBi | For | 9.2° < θ ≤ 48° |
| - 10 | dBi | For | 48° < θ ≤ 85° |
| 0 | dBi | For | 85° < θ ≤ 180° |

(3) In all other directions, or in the plane of the horizon including any out-of-plane potential terrestrial interference paths, for all earth stations not

operating in the 20/30 GHz band or conventional Ku-band:

Outside the main beam, the gain of the antenna shall lie below the envelope defined by:

| | | | |
|--------------------------------|-----------|-----------|----------------|
| 32-25log ₁₀ θ | dBi | For | 3° < θ ≤ 48° |
| - 10 | dBi | For | 48° < θ ≤ 180° |

where θ and dBi are defined above. For the purposes of this section, the envelope may be exceeded by no more than 10% of the

sidelobes provided no individual sidelobe exceeds the gain envelope given above by more than 6 dB. The region of the main reflector