

§ 25.213

47 CFR Ch. I (10–1–14 Edition)

is within ± 1 MHz of one of the frequencies specified in § 25.211(a).

(c)(1) An earth station that is not subject to licensing under § 25.134, § 25.222, § 25.226, or § 25.227 may be routinely licensed for analog transmissions in the 14.0–14.5 GHz band with bandwidths up to 200 kHz (or up to 1 MHz for command carriers at the band edge) if the equivalent diameter of the transmitting antenna is 1.2 meters or greater, input power spectral density into the antenna will not exceed -8 dBW/4 kHz, transmitted satellite carrier EIRP density will not exceed 17 dBW/4 kHz, and the application includes certification pursuant to § 25.132(a)(1) of conformance with the antenna performance standards in § 25.209(a) and (b).

(2) An earth station that is not subject to licensing under § 25.134, § 25.222, § 25.226, or § 25.227 may be routinely licensed for digital transmission, including digital video transmission, in the 14.0–14.5 GHz band if the equivalent diameter of the transmitting antenna is 1.2 meters or greater, input power spectral density into the antenna will not exceed -14 dBW/4 kHz, transmitted satellite carrier EIRP density will not exceed $+10.0$ dBW/4 kHz, and the application includes certification pursuant to § 25.132(a)(1) of conformance with the antenna performance standards in § 25.209(a) and (b).

(d) An earth station that is not subject to licensing under § 25.134 or § 25.221 may be routinely licensed for digital transmission in the 5925–6425 MHz band or analog transmission in that band with carrier bandwidths up to 200 kHz (or up to 1 MHz for command carriers at the band edge) if the equivalent diameter of the transmit antenna is 4.5 meters or greater, the application includes certification pursuant to § 25.132(a)(1) of conformance with the antenna performance standards in § 25.209(a) and (b), and maximum power density into the antenna will not exceed $+0.5$ dBW/4 kHz for analog carriers or $-2.7 - 10\log(N)$ dBW/4 kHz for digital carriers. For digital transmission with frequency division multiple access (FDMA) or time division multiple access (TDMA), N is equal to one. For digital transmission with code division multiple access (CDMA), N is the max-

imum number of co-frequency simultaneously transmitting earth stations in the same satellite receiving beam.

(e) An applicant for authority for an earth station in the Fixed-Satellite Service proposing to transmit digital signals or analog signals in bandwidths up to 200 kHz (or up to 1 MHz for command carriers at the band edge) and to operate with transmitted satellite carrier EIRP densities, and/or maximum antenna input power densities in excess of those specified in applicable provisions of paragraph (c) or (d) of this section or operate with a smaller antenna than specified in a relevant provision of those paragraphs must comply with the requirements in § 25.218 or § 25.220, unless the application is subject to licensing pursuant to § 25.221, § 25.222, § 25.226, or § 25.227.

(f) In the 24.75–25.25 GHz band, an earth station that meets the antenna gain pattern requirements set forth in § 25.209(a) and (b) of this part may be routinely licensed if the maximum power density into the antenna does not exceed 3.5 dBW/MHz.

[58 FR 13421, Mar. 11, 1993, as amended at 62 FR 5931, Feb. 10, 1997; 62 FR 51378, Oct. 1, 1997; 70 FR 32256, June 2, 2005; 70 FR 33376, June 8, 2005; 72 FR 50030, Aug. 29, 2007; 73 FR 70902, Nov. 24, 2008; 78 FR 8428, Feb. 6, 2013; 79 FR 8323, Feb. 12, 2014]

§ 25.213 Inter-Service coordination requirements for the 1.6/2.4 GHz Mobile-Satellite Service.

(a) Protection of the radio astronomy service in the 1610.6–1613.8 MHz band against interference from 1.6/2.4 GHz Mobile-Satellite Service systems.

(1) *Protection zones.* All 1.6/2.4 GHz Mobile-Satellite Service systems shall be capable of determining the position of the user transceivers accessing the space segment through either internal radiodetermination calculations or external sources such as LORAN-C or the Global Positioning System.

(i) In the band 1610.6–1613.8 MHz, within a 160 km radius of the following radio astronomy sites:

Observatory	Latitude (DMS)	Longitude (DMS)
Arecibo, PR	18 20 46	66 45 11
Green Bank Telescope, WV	38 25 59	79 50 24
	38 26 09	79 49 42
Very Large Array, NM	34 04 43	107 37 04
Owens Valley, CA	37 13 54	118 17 36

Federal Communications Commission

§ 25.213

Observatory	Latitude (DMS)	Longitude (DMS)
Ohio State, OH	40 15 06	83 02 54

(ii) In the band 1610.6–1613.8 MHz, within a 50 km radius of the following sites:

Observatory	Latitude (DMS)	Longitude (DMS)
Pile Town, NM	34 18 04	108 07 07
Los Alamos, NM	35 46 30	106 14 42
Kitt Peak, AZ	31 57 22	111 36 42
Ft. Davis, TX	30 38 06	103 56 39
N. Liberty, IA	41 46 17	91 34 26
Brewster, WA	48 07 53	119 40 55
Owens Valley, CA	37 13 54	118 16 34
St. Croix, VI	17 45 31	64 35 03
Mauna Kea, HI	19 48 16	155 27 29
Hancock, NH	42 56 01	71 59 12

(iii) Out-of-band emissions of a mobile earth station licensed to operate within the 1610.0–1626.5 MHz band shall be attenuated so that the power flux density it produces in the 1610.6–1613.8 MHz band at any radio astronomy site listed in paragraph (a)(1) (i) or (ii) of this section shall not exceed the emissions of a mobile earth station operating within the 1610.6–1613.8 MHz band at the edge of the protection zone applicable for that site. As an alternative, a mobile earth station shall not operate during radio astronomy observations within the 1613.8–1615.8 MHz band within 100 km of the radio astronomy sites listed in paragraph (a)(1)(i) of this section, and within 30 km of the sites listed in paragraph (a)(1)(ii) of this section, there being no restriction on a mobile earth station operating within the 1615.8–1626.5 MHz band.

(iv) For airborne mobile earth stations operating in the 1610.0–1626.5 MHz band, the separation distance shall be the larger of the distances specified in paragraph (a)(1) (i), (ii) or (iii) of this section, as applicable, or the distance, d, as given by the formula:

$$d \text{ (km)} = 4.1 \text{ square root of (h)}$$

where h is the altitude of the aircraft in meters above ground level.

(v) Smaller geographic protection zones may be used in lieu of the areas specified in paragraphs (a)(1) (i), (ii), (iii), and (iv) of this section if agreed to by the Mobile-Satellite Service licensee and the Electromagnetic Spectrum Management Unit (ESMU), Na-

tional Science Foundation, Washington, D.C. upon a showing by the Mobile-Satellite Service licensee that the operation of a mobile earth station will not cause harmful interference to a radio astronomy observatory during periods of observation.

(vi) The ESMU shall notify Mobile-Satellite Service space station licensees authorized to operate mobile earth stations in the 1610.0–1626.5 MHz band of periods of radio astronomy observations. The Mobile-Satellite systems shall be capable of terminating operations within the frequency bands and protection zones specified in paragraphs (a)(1)(i) through (iv) of this section, as applicable, after the first position fix of the mobile earth station either prior to transmission or, based upon its location within the protection zone at the time of initial transmission of the mobile earth station. Once the Mobile-Satellite Service system determines that a mobile earth station is located within an RAS protection zone, the Mobile-Satellite Service system shall immediately initiate procedures to relocate the mobile earth station operations to a non-RAS frequency.

(vii) A beacon-actuated protection zone may be used in lieu of fixed protection zones in the 1610.6–1613.8 MHz band if a coordination agreement is reached between a mobile-satellite system licensee and the ESMU on the specifics of beacon operations.

(viii) Additional radio astronomy sites, not located within 100 miles of the 100 most populous urbanized areas as defined by the United States Census Bureau at the time, may be afforded similar protection one year after notice to the mobile-satellite system licensees by issuance of a public notice by the Commission.

(2) Mobile-Satellite Service space stations transmitting in the 1613.8–1626.5 MHz band shall take whatever steps necessary to avoid causing harmful interference to the radio astronomy facilities listed in paragraphs (a)(1)(i) and (ii) of this section during periods of observation.

(3) Mobile-Satellite Service space stations operating in the 2483.5–2500 MHz frequency band shall limit spurious emission levels in the 4990–5000

§ 25.214

47 CFR Ch. I (10–1–14 Edition)

MHz band so as not to exceed -241 dB ($\text{W/m}^2/\text{Hz}$) at the surface of the Earth.

(4) The Radioastronomy Service shall avoid scheduling radio astronomy observations during peak MSS/RDSS traffic periods to the greatest extent practicable.

(b) If a Mobile-Satellite Service space station operator in the 2496–2500 MHz band intends to operate at power levels that exceed the PFD limits in § 25.208(v), or if actual operations routinely exceed these PFD limits, we require the Mobile-Satellite Service operator to receive approval from each operational BRS system in the affected geographical region.

[59 FR 53329, Oct. 21, 1994, as amended at 61 FR 9945, Mar. 12, 1996; 67 FR 61816, Oct. 2, 2002; 71 FR 35188, June 19, 2006; 78 FR 8428, Feb. 6, 2013]

§ 25.214 Technical requirements for space stations in the Satellite Digital Audio Radio Service and associated terrestrial repeaters.

(a) [Reserved]

(b) Each system authorized under this section will be conditioned upon construction, launch and operation milestones as outlined in § 25.144(b). The failure to meet any of the milestones contained in an authorization will result in its cancellation, unless such failure is due to circumstances beyond the licensee's control or unless otherwise determined by the Commission upon proper showing by the licensee in any particular case.

(c) Frequency assignments will be made for each satellite DARS system as follows:

(1) Exclusive SDARS licenses are limited to the 2320–2345 MHz segment of the 2310–2360 MHz allocated bandwidth for SDARS;

(2) Two, 12.5 MHz frequency assignments are available for satellite DARS: 2320.0–2332.5 MHz and 2332.5–2345.0 MHz;

(3) Satellite DARS licensees may reduce their assigned bandwidth occupancy to provide telemetry beacons in their exclusive frequency assignments;

(4) Each licensee may employ cross polarization within its exclusive frequency assignment and/or may employ cross polarized transmissions in frequency assignments of other satellite DARS licensees under mutual agree-

ment with those licensees. Licensees who come to mutual agreement to use cross-polarized transmissions shall apply to the Commission for approval of the agreement before coordination is initiated with other administrations by the licensee of the exclusive frequency assignment; and

(5) Feeder uplink networks are permitted in the following Fixed-Satellite Service frequency bands: 7025–7075 MHz and 6725–7025 MHz (101° W.L. orbital location only).

(d) *Power limit for SDARS terrestrial repeaters.* (1) SDARS terrestrial repeaters must be operated at a power level less than or equal to 12-kW average EIRP, with a maximum peak-to-average power ratio of 13 dB.

(2) SDARS repeaters are permitted to operate at power levels above 12-kW average EIRP, unless a potentially affected WCS licensee provides written notice that it intends to commence commercial service within the following 365 days. Starting 180 days after receipt of such written notice, SDARS repeaters within the area notified by the potentially affected WCS licensee must be operated at a power level less than or equal to 12-kW average EIRP, with a maximum peak-to-average power ratio of 13 dB.

(3) For the purpose of this section, a WCS licensee is potentially affected if it is authorized to operate a base station in the 2305–2315 MHz or 2350–2360 MHz bands within 25 kilometers of a repeater seeking to operate with a power level greater than that prescribed in paragraph (d)(1) of this section.

[62 FR 11106, Mar. 11, 1997, as amended at 75 FR 45068, Aug. 2, 2010; 78 FR 8429, Feb. 6, 2013; 78 FR 9619, Feb. 11, 2013; 79 FR 8323, Feb. 12, 2014]

§ 25.215 [Reserved]

§ 25.216 Limits on emissions from mobile earth stations for protection of aeronautical radionavigation-satellite service.

(a) The e.i.r.p. density of emissions from mobile earth stations placed in service on or before July 21, 2002 with assigned uplink frequencies between 1610 MHz and 1660.5 MHz shall not exceed -70 dBW/MHz, averaged over any 2 millisecond active transmission interval, in the band 1559–1587.42 MHz.