

## § 27.1215

### § 27.1215 BRS grandfathered leases.

(a) All leases of current BRS spectrum entered into prior to January 10, 2005 and in compliance with rules formerly contained in part 21 of this chapter may continue in force and effect, notwithstanding any inconsistency between such leases and the rules applicable to spectrum leasing arrangements set forth in this chapter. Such leases entered into pursuant to the former part 21 of this chapter may be renewed and assigned in accordance with the terms of such lease. All spectrum leasing arrangements leases entered into after January 10, 2005, pursuant to the rules set forth in part 1 and part 27 of this chapter must comply with the rules in those parts.

### § 27.1216 Grandfathered E and F group EBS licenses.

(a) Except as noted in paragraph (b) of this section, grandfathered EBS licensees authorized to operate E and F group co-channel licenses are granted a geographic service area (GSA) on July 19, 2006. The GSA is the area bounded by a circle having a 35 mile radius and centered at the station's reference coordinates, and is bounded by the chord(s) drawn between intersection points of that circle and those of respective adjacent market, co-channel licensees.

(b) If there is more than 50 percent overlap between the calculated GSA of a grandfathered EBS license and the protected service area of a co-channel BRS license, the licensees shall not be immediately granted a geographic service area. Instead, the grandfathered EBS license and the co-channel BRS licensee must negotiate in good faith to reach a solution that accommodates the communication needs of both licensees. If the co-channel licensees reach a mutually agreeable solution on or before October 17, 2006, then the GSA of each co-channel license shall be as determined pursuant to the agreement of the parties. If a mutually agreeable solution between co-channel licensees is not reached on or before October 17, 2006, then each co-channel licensee shall receive a GSA

## 47 CFR Ch. I (10–1–14 Edition)

determined pursuant to paragraph (a) of this section and § 27.1206(a).

[71 FR 35191, June 16, 2006]

### § 27.1217 Competitive bidding procedures for the Broadband Radio Service.

Mutually exclusive initial applications for BRS licenses in the 2500–2690 MHz band are subject to competitive bidding. The general competitive bidding procedures set forth in part 1, subpart Q of this chapter will apply unless otherwise provided in this subpart.

[73 FR 26041, May 8, 2008]

### § 27.1218 Designated entities.

(a) *Eligibility for small business provisions.* (1) A small business is an entity that, together with all attributed parties, has average gross revenues that are not more than \$40 million for the preceding three years.

(2) A very small business is an entity that, together with all attributed parties, has average gross revenues that are not more than \$15 million for the preceding three years.

(3) An entrepreneur is an entity that, together with all attributed parties, has average gross revenues that are not more than \$3 million for the preceding three years.

(b) *Bidding credits.* (1) A winning bidder that qualifies as a small business, as defined in this section, or a consortium of small businesses, may use a bidding credit of 15 percent, as specified in § 1.2110(f)(2)(iii) of this chapter, to lower the cost of its winning bid on any of the licenses in this subpart.

(2) A winning bidder that qualifies as a very small business, as defined in this section, or a consortium of very small businesses, may use a bidding credit of 25 percent, as specified in § 1.2110(f)(2)(ii) of this chapter, to lower the cost of its winning bid on any of the licenses in this subpart.

(3) A winning bidder that qualifies as an entrepreneur, as defined in this section, or a consortium of entrepreneurs, may use a bidding credit of 15 percent, as specified in § 1.2110(f)(2)(i) of this chapter, to lower the cost of its winning bid on any of the licenses in this subpart.

[73 FR 26041, May 8, 2008]

## TECHNICAL STANDARDS

**§ 27.1220 Transmission standards.**

The width of a channel in the LBS and UBS is 5.5 MHz, with the exception of BRS channels 1 and 2 which are 6.0 MHz. The width of all channels in the MBS is 6 MHz. However, the licensee may subchannelize its authorized bandwidth, provided that digital modulation is employed and the aggregate power does not exceed the authorized power for the channel. The licensee may also, jointly with other licensees, transmit utilizing bandwidth in excess of its authorized bandwidth, provided that digital modulation is employed, all power spectral density requirements set forth in this part are met and the out-of-band emissions restrictions set forth in § 27.53 are met at the edges of the channels employed.

**§ 27.1221 Interference protection.**

(a) Interference protection will be afforded to BRS and EBS on a station-by-station basis based on the heights of the stations in the LBS and UBS and also on height benchmarking, although the heights of antennas utilized are not restricted.

(b) *Height benchmarking.* Height benchmarking is defined for pairs of base stations, one in each of two proximate geographic service areas (GSAs). The height benchmark, which is defined in meters ( $hb_m$ ) for a particular base station relative to a base station in another GSA, is equal to the distance, in kilometers, from the base station along a radial to the nearest point on the GSA boundary of the other base station squared ( $D_{km}^2$ ) and then divided by 17. That is,  $hb_m = D_{km}^2/17$ . A base station antenna will be considered to be within its applicable height benchmark relative to another base station if the height in meters of its centerline of radiation above average elevation (HAAE) calculated along the straight line between the two base stations in accordance with § 24.53(b) and (c) of this chapter does not exceed the height benchmark ( $hb_m$ ). A base station antenna will be considered to exceed its applicable height benchmark relative to another base station if the HAAE of its centerline of radiation calculated along the straight line between the two

base stations in accordance with § 24.53(b) and (c) of this chapter exceeds the height benchmark ( $hb_m$ ).

(c) *Protection for receiving antennas not exceeding the height benchmark.* Absent agreement between the two licensees to the contrary, if a transmitting antenna of one BRS/EBS licensee's base station exceeds its applicable height benchmark and such licensee is notified by another BRS/EBS licensee that it is generating an undesired signal level in excess of  $-107$  dBm/5.5 megahertz at the receiver of a co-channel base station that is within its applicable height benchmark, then the licensee of the base station that exceeds its applicable height benchmark shall either limit the undesired signal at the receiver of the protected base station to  $-107$  dBm/5.5 megahertz or less or reduce the height of its transmission antenna to no more than the height benchmark. If the interfering base station has been modified to increase the EIRP transmitted in the direction of the protected base station, it shall be deemed to have commenced operations on the date of such modification. Such corrective action shall be completed no later than:

(i) 24 hours after receiving such notification, if the base station that exceeds its height benchmark commenced operations after the station that is within its applicable height benchmark; or

(ii) 90 days after receiving such notification, if the base station that exceeds its height commenced operations prior to the station that is within its applicable height benchmark. For purposes of this section, if the interfering base station has been modified to increase the EIRP transmitted in the direction of the victim base station, it shall be deemed to have commenced operations on the date of such modification.

(d) *No Protection from a transmitting antenna not exceeding the height benchmark.* The licensee of a base station transmitting antenna less than or equal to its applicable height benchmark shall not be required pursuant to paragraph (c) of this section to limit that antenna's undesired signal level to  $-107$  dBm/5.5 megahertz or less at the receiver of any co-channel base station.