## §27.51

3. At 79 FR 48538, Aug. 15, 2014, \$27.50 was amended by revising paragraphs (c) introductory text, (c)(5) introductory text, (c)(9), (c)(10), and the headings to Tables 1 through 4, effective Oct. 14, 2014. For the convenience of the user, the revised text is set forth as follows:

#### §27.50 Power limits and duty cycle.

\* \* \* \* \*

(c) The following power and antenna height requirements apply to stations transmitting in the 600 MHz band and the 698-746 MHz band:

\* \* \* \* \*

(5) Licensees, except for licensees operating in the 600 MHz downlink band, seeking to operate a fixed or base station located in a county with population density of 100 or fewer persons per square mile, based upon the most recently available population statistics from the Bureau of the Census, and transmitting a signal at an ERP greater than 1000 watts must:

\* \* \* \* \*

(9) Control and mobile stations in the 698–746 MHz band are limited to 30 watts ERP.

(10) Portable stations (hand-held devices) in the 600 MHz uplink band and the 698-746 MHz band, and fixed and mobile stations in the 600 MHz uplink band are limited to 3 watts ERP.

\* \* \* \* \*

Table 1 to §27.50—Permissible Power and Antenna Heights for Base and Fixed Stations in the 757–758 and 775–776 MHz Bands and for Base and Fixed Stations in the 600 MHz, 698– 757 MHz, 758–763 MHz, 776–787 MHz and 788–793 MHz Bands Transmitting a Signal With an Emission Bandwidth of 1 MHz or Less.

\* \* \* \* \*

Table 2 to §27.50—Permissible Power and Antenna Heights for Base and Fixed Stations in the 600 MHz, 698-757 MHz, 758-763 MHz, 776-787 MHz and 788-793 MHz Bands Transmitting a Signal With an Emission Bandwidth of 1 MHz or Less.

\* \* \* \* \*

Table 3 to §27.50—Permissible Power and Antenna Heights for Base and Fixed Stations in the 600 MHz, 698-757 MHz, 758-763 MHz, 776-787 MHz and 788-793 MHz Bands Transmitting 47 CFR Ch. I (10–1–14 Edition)

a Signal With an Emission Bandwidth Greater than 1  $\rm MHz.$ 

\* \* \* \*

Table 4 to §27.50—Permissible Power and Antenna Heights for Base and Fixed Stations in the 600 MHz, 698–757 MHz, 758–763 MHz, 776– 787 MHz and 788–793 MHz Bands Transmitting a Signal With an Emission Bandwidth Greater than 1 MHz

\* \* \* \*

# §27.51 Equipment authorization.

(a) Each transmitter utilized for operation under this part must be of a type that has been authorized by the Commission under its certification procedure.

(b) Any manufacturer of radio transmitting equipment to be used in these services may request equipment authorization following the procedures set forth in subpart J of part 2 of this chapter. Equipment authorization for an individual transmitter may be requested by an applicant for a station authorization by following the procedures set forth in part 2 of this chapter.

[65 FR 3147, Jan. 20, 2000]

### §27.52 RF safety.

Licensees and manufacturers are subject to the radio frequency radiation exposure requirements specified in sections 1.1307(b), 2.1091, and 2.1093 of this chapter, as appropriate. Applications for equipment authorization of mobile or portable devices operating under this section must contain a statement confirming compliance with these requirements for both fundamental emissions and unwanted emissions. Technical information showing the basis for this statement must be submitted to the Commission upon request.

### §27.53 Emission limits.

(a) For operations in the 2305-2320 MHz band and the 2345-2360 MHz band, the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power P (with averaging performed only during periods of transmission) within the licensed band(s) of operation, in watts, by the following amounts: