

§ 4.7

47 CFR Ch. I (10–1–14 Edition)

(b) *Special offices and facilities* are defined as major military installations, key government facilities, nuclear power plants, and those airports that are listed as current primary (PR), commercial service (CM), and reliever (RL) airports in the FAA's National Plan of Integrated Airports Systems (NPIAS) (as issued at least one calendar year prior to the outage). The member agencies of the National Communications System (NCS) will determine which of their locations are "major military installations" and "key government facilities." 911 special facilities are addressed separately in paragraph (e) of this section.

(c) All outages that potentially affect communications for at least 30 minutes with any airport that qualifies as a "special office and facility" pursuant to the preceding paragraph shall be reported in accordance with the provisions of §§ 4.11 and 4.13.

(d) A mission-affecting outage is defined as an outage that is deemed critical to national security/emergency preparedness (NS/EP) operations of the affected facility by the National Communications System member agency operating the affected facility.

(e) An outage that potentially affects a 911 special facility occurs whenever:

(1) There is a loss of communications to PSAP(s) potentially affecting at least 900,000 user-minutes and: The failure is neither at the PSAP(s) nor on the premises of the PSAP(s); no re-route for all end users was available; and the outage lasts 30 minutes or more; or

(2) There is a loss of 911 call processing capabilities in one or more E-911 tandems/selective routers for at least 30 minutes duration; or

(3) One or more end-office or MSC switches or host/remote clusters is isolated from 911 service for at least 30 minutes and potentially affects at least 900,000 user-minutes; or

(4) There is a loss of ANI/ALI (associated name and location information) and/or a failure of location determination equipment, including Phase II equipment, for at least 30 minutes and potentially affecting at least 900,000 user-minutes (provided that the ANI/ALI or location determination equipment was then currently deployed and

in use, and the failure is neither at the PSAP(s) or on the premises of the PSAP(s)).

§ 4.7 Definitions of metrics used to determine the general outage-reporting threshold criteria.

(a) *Administrative numbers* are defined as the telephone numbers used by communications providers to perform internal administrative or operational functions necessary to maintain reasonable quality of service standards.

(b) *Assigned numbers* are defined as the telephone numbers working in the Public Switched Telephone Network under an agreement such as a contract or tariff at the request of specific end users or customers for their use. This excludes numbers that are not yet working but have a service order pending.

(c) *Assigned telephone number minutes* are defined as the mathematical result of multiplying the duration of an outage, expressed in minutes, by the sum of the number of assigned numbers (defined in paragraph (b) of this section) potentially affected by the outage and the number of administrative numbers (defined in paragraph (a) of this section) potentially affected by the outage. "Assigned telephone number minutes" can alternatively be calculated as the mathematical result of multiplying the duration of an outage, expressed in minutes, by the number of working telephone numbers potentially affected by the outage, where working telephone numbers are defined as the telephone numbers, including DID numbers, working immediately prior to the outage.

(d) *DS3 minutes* are defined as the mathematical result of multiplying the duration of an outage, expressed in minutes, by the number of previously operating DS3 circuits that were affected by the outage.

(e) *User minutes* are defined as:

(1) Assigned telephone number minutes (as defined in paragraph (c) of this section), for telephony, including non-mobile interconnected VoIP telephony, and for those paging networks in which each individual user is assigned a telephone number;

(2) The mathematical result of multiplying the duration of an outage, expressed in minutes, by the number of end users potentially affected by the outage, for all other forms of communications. For wireless service providers and interconnected VoIP service providers to mobile users, the number of potentially affected users should be determined by multiplying the simultaneous call capacity of the affected equipment by a concentration ratio of 8.

(f) *Working telephone numbers* are defined to be the sum of all telephone numbers that can originate, or terminate telecommunications. This includes, for example, all working telephone numbers on the customer's side of a PBX, or Centrex, or similar arrangement.

[69 FR 70338, Dec. 3, 2004, as amended at 77 FR 25097, Apr. 27, 2012]

§ 4.9 Outage reporting requirements—threshold criteria.

(a) *Cable*. All cable communications providers shall submit electronically a Notification to the Commission within 120 minutes of discovering that they have experienced on any facilities that they own, operate, lease, or otherwise utilize, an outage of at least 30 minutes duration that:

(1) Potentially affects at least 900,000 user minutes of telephony service;

(2) Affects at least 1,350 DS3 minutes;

(3) Potentially affects any special offices and facilities (in accordance with paragraphs (a) through (d) of § 4.5); or

(4) Potentially affects a 911 special facility (as defined in paragraph (e) of § 4.5), in which case they also shall notify, as soon as possible by telephone or other electronic means, any official who has been designated by the management of the affected 911 facility as the provider's contact person for communications outages at that facility, and they shall convey to that person all available information that may be useful to the management of the affected facility in mitigating the effects of the outage on callers to that facility. (DS3 minutes and user minutes are defined in paragraphs (d) and (e) of § 4.7.) Not later than 72 hours after discovering the outage, the provider shall submit electronically an Initial Com-

munications Outage Report to the Commission. Not later than thirty days after discovering the outage, the provider shall submit electronically a Final Communications Outage Report to the Commission. The Notification and the Initial and Final reports shall comply with all of the requirements of § 4.11.

(b) *IXC or LEC tandem facilities*. In the case of IXC or LEC tandem facilities, providers must, if technically possible, use real-time blocked calls to determine whether criteria for reporting an outage have been reached. Providers must report IXC and LEC tandem outages of at least 30 minutes duration in which at least 90,000 calls are blocked or at least 1,350 DS3-minutes are lost. For interoffice facilities which handle traffic in both directions and for which blocked call information is available in one direction only, the total number of blocked calls shall be estimated as twice the number of blocked calls determined for the available direction. Providers may use historic carried call load data for the same day(s) of the week and the same time(s) of day as the outage, and for a time interval not older than 90 days preceding the onset of the outage, to estimate blocked calls whenever it is not possible to obtain real-time blocked call counts. When using historic data, providers must report incidents where at least 30,000 calls would have been carried during a time interval with the same duration of the outage. (DS3 minutes are defined in paragraph (d) of § 4.7.) In situations where, for whatever reason, real-time and historic carried call load data are unavailable to the provider, even after a detailed investigation, the provider must determine the carried call load based on data obtained in the time interval between the onset of the outage and the due date for the final report; this data must cover the same day of the week, the same time of day, and the same duration as the outage. Justification that such data accurately estimates the traffic that would have been carried at the time of the outage had the outage not occurred must be available on request. If carried call load data cannot be obtained through