| Mexican station class | Co-channel (km) | First-adjacent channel (km) | Second- and third-adjacent channel (km) | Intermediate frequency (IF) channel (km) |
|-----------------------|--------------------|-----------------------------------|--------------------------------------------------|---------------------------------------------------|
| Low Power | 27 | 17 | 9 | 3 |
| A | 43 | 32 | 25 | 5 |
| AA | 47 | 36 | 29 | 6 |
| B1 | 67 | 54 | 45 | 8 |
| В | 91 | 76 | 66 | 11 |
| C1 | 91 | 80 | 73 | 19 |
| C | 110 | 100 | 92 | 27 |

- (3) The Commission will notify the International Telecommunications Union (ITU) of any LPFM authorizations in the US Virgin Islands. Any authorization issued for a US Virgin Islands LPFM station will include a condition that permits the Commission to modify, suspend or terminate without right to a hearing if found by the Commission to be necessary to conform to any international regulations or agreements.
- (4) The Commission will initiate international coordination of a LPFM proposal even where the above Canadian and Mexican spacing tables are met, if it appears that such coordination is necessary to maintain compliance with international agreements.

[78 FR 2102, Jan. 9, 2013]

§ 73.808 Distance computations.

For the purposes of determining compliance with any LPFM distance requirements, distances shall be calculated in accordance with §73.208(c) of this part.

§ 73.809 Interference protection to full service FM stations.

- (a) If a full service commercial or NCE FM facility application is filed subsequent to the filing of an LPFM station facility application, such full service station is protected against any condition of interference to the direct reception of its signal that is caused by such LPFM station operating on the same channel or first-adjacent channel provided that the interference is predicted to occur and actually occurs within:
- (1) The 3.16~mV/m (70 dBu) contour of such full service station;
- (2) The community of license of such full service station; or

- (3) Any area of the community of license of such full service station that is predicted to receive at least a 1 mV/ m (60 dBu) signal. Predicted interference shall be calculated in accordance with the ratios set forth in §73.215 paragraphs (a)(1) and (a)(2). Intermediate frequency (IF) channel interference overlap will be determined based upon overlap of the 91 dBu F(50,50) contours of the FM and LPFM stations. Actual interference will be considered to occur whenever reception of a regularly used signal is impaired by the signal radiated by the LPFM station.
- (b) An LPFM station will be provided an opportunity to demonstrate in connection with the processing of the commercial or NCE FM application that interference as described in paragraph (a) of this section is unlikely. If the LPFM station fails to so demonstrate, it will be required to cease operations upon the commencement of program tests by the commercial or NCE FM station.
- (c) Complaints of actual interference by an LPFM station subject to paragraphs (a) and (b) of this section must be served on the LPFM licensee and the Federal Communications Commission, attention Audio Services Division. The LPFM station must suspend operations within twenty-four hours of the receipt of such complaint unless the interference has been resolved to the satisfaction of the complainant on the basis of suitable techniques. An LPFM station may only resume operations at the direction of the Federal Communications Commission. If the Commission determines that the complainant has refused to permit the

§73.810

LPFM station to apply remedial techniques that demonstrably will eliminate the interference without impairment of the original reception, the licensee of the LPFM station is absolved of further responsibility for the complaint.

(d) It shall be the responsibility of the licensee of an LPFM station to correct any condition of interference that results from the radiation of radio frequency energy outside its assigned channel. Upon notice by the FCC to the station licensee or operator that such interference is caused by spurious emissions of the station, operation of the station shall be immediately suspended and not resumed until the interference has been eliminated. However, short test transmissions may be made during the period of suspended operation to check the efficacy of remedial measures.

(e) In each instance where suspension of operation is required, the licensee shall submit a full report to the FCC in Washington, DC, after operation is resumed, containing details of the nature of the interference, the source of the interfering signals, and the remedial steps taken to eliminate the interference.

[65 FR 7640, Feb. 15, 2000, as amended at 65 FR 67302, Nov. 9, 2000; 73 FR 3216, Jan. 17, 2008; 78 FR 2104, Jan. 9, 2013]

§ 73.810 Third adjacent channel interference.

- (a) LPFM Stations Licensed at Locations That Do Not Satisfy Third-Adjacent Channel Minimum Distance Separations. An LPFM station licensed at a location that does not satisfy the third-adjacent channel minimum distance separations set forth in §73.807 is subject to the following provisions:
- (1) Such an LPFM station will not be permitted to continue to operate if it causes any actual third-adjacent channel interference to:
- (i) The transmission of any authorized broadcast station; or
- (ii) The reception of the input signal of any TV translator, TV booster, FM translator or FM booster station; or
- (iii) The direct reception by the public of the off-the-air signals of any authorized broadcast station including TV Channel 6 stations, Class D (sec-

ondary) noncommercial educational FM stations, and previously authorized and operating LPFM stations, FM translators and FM booster stations. Interference will be considered to occur whenever reception of a regularly used signal on a third-adjacent channel is impaired by the signals radiated by the LPFM station, regardless of the quality of such reception, the strength of the signal so used, or the channel on which the protected signal is transmitted.

- (2) If third-adjacent channel interference cannot be properly eliminated by the application of suitable techniques, operation of the offending LPFM station shall be suspended and shall not be resumed until the interference has been eliminated. Short test transmissions may be made during the period of suspended operation to check the efficacy of remedial measures. If a complainant refuses to permit the licensee of the offending LPFM station to apply remedial techniques which demonstrably will eliminate the third-adjacent channel interference without impairment to the original reception, the licensee is absolved of further responsibility for that complaint.
- (3) Upon notice by the Commission to the licensee that such third-adjacent channel interference is being caused, the operation of the LPFM station shall be suspended within three minutes and shall not be resumed until the interference has been eliminated or it can be demonstrated that the interference is not due to spurious emissions by the LPFM station; provided, however, that short test transmissions may be made during the period of suspended operation to check the efficacy of remedial measures.
- (b) LPFM stations licensed at locations that satisfy third-adjacent channel minimum distance separations. An LPFM station licensed at a location that satisfies the third-adjacent channel minimum distance separations set forth in §73.807 is subject to the following provisions:
- (1) Interference complaints and remediation. (i) Such an LPFM station is required to provide copies of all complaints alleging that its signal is causing third-adjacent channel interference to or impairing the reception of the