

## § 74.34

## 47 CFR Ch. I (10–1–14 Edition)

will be accepted for filing if the proposed station is located within 20 km of the following coordinates:

Denver, CO area: 39°43'00" N. Lat./104°46'00" W. Long.

Washington, DC area: 38°48'00" N. Lat./76°52'00" W. Long.

NOTE TO §74.32: The coordinates cited in this section are specified in terms of the "North American Datum of 1983 (NAD 83)" with an accuracy of ±30 meters with respect to the "National Spatial Reference System"

[71 FR 69048, Nov. 29, 2006; 71 FR 75614, Dec. 15, 2006]

### § 74.34 Period of construction; certification of completion of construction.

(a) Each aural and television broadcast auxiliary station authorized under subparts E and F of this part must be in operation within 18 months from the initial date of grant.

(b) Each remote pickup broadcast auxiliary station authorized under subpart D of this part must be in operation within 12 months from the initial date of grant.

(c) Failure to timely begin operation means the authorization terminates automatically.

(d) Requests for extension of time may be granted upon a showing of good cause pursuant to §1.946(e) of this chapter.

(e) Construction of any authorized facility or frequency must be completed by the date specified in the license and the Commission must be notified pursuant to §1.946 of this chapter.

[68 FR 12763, Mar. 17, 2003]

### Subparts A–C [Reserved]

### Subpart D—Remote Pickup Broadcast Stations

#### § 74.401 Definitions.

*Associated broadcasting station(s).* The broadcasting station or stations with which a remote pickup broadcast station or system is licensed as an auxiliary and with which it is principally used.

*Authorized bandwidth.* The occupied or necessary bandwidth, whichever is greater, authorized to be used by a station.

*Automatic relay station.* A remote pickup broadcast base station which is actuated by automatic means and is used to relay transmissions between remote pickup broadcast base and mobile stations, between remote pickup broadcast mobile stations and from remote pickup broadcast mobile stations to broadcasting stations. (Automatic operation is not operation by remote control.)

*Carrier power.* The average power at the output terminals of a transmitter (other than a transmitter having a suppressed, reduced or controlled carrier) during one radio frequency cycle under conditions of no modulation.

*Mean power.* The power at the output terminals of a transmitter during normal operation, averaged over a time sufficiently long compared with the period of the lowest frequency encountered in the modulation. A time of  $\frac{1}{10}$  second during which the mean power is greatest will be selected normally.

*Necessary bandwidth.* For a given class of emission, the minimum value of the occupied bandwidth sufficient to ensure the transmission of information at the rate and with the quality required for the system employed, under specified conditions. Emissions useful for the good functioning of the receiving equipment, as for example, the emission corresponding to the carrier of reduced carrier systems, shall be included in the necessary bandwidth.

*Occupied bandwidth.* The frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission.

*Operational communications.* Communications concerning the technical and programming operation of a broadcast station and its auxiliaries.

*Remote control operation.* Operation of a base station by a properly designated person on duty at a control position from which the transmitter is not visible but that position is equipped with suitable controls so that essential functions can be performed therefrom.

*Remote pickup broadcast base station.* A remote pickup broadcast station authorized for operation at a specified location.