

§ 87.351

47 CFR Ch. I (10–1–14 Edition)

be assigned the tower or RCO frequency if the assignment is specifically approved by the FAA as provided for in § 87.347(c). The frequencies assigned are normally from the band 121.600–121.925 MHz.

(b) The frequency assigned to the unicom is available to aeronautical utility stations on a noninterference basis at airports which have a part-time control tower, part-time RCO or part-time FAA flight service station and a unicom.

(c) At airports which have a unicom but no control tower, RCO or FAA flight service station, the frequency assigned to the unicom is available to aeronautical utility stations on a noninterference basis. The frequencies available for assignment to unicom are described in subpart G of this part.

(d) At airports which have no control tower, RCO, flight service station or unicom, the frequency 122.900 MHz is available for assignment to aeronautical utility stations.

(e) The frequency 978.0 MHz is authorized for Universal Access Transceiver data transmission.

(f) The Commission will assign frequency 1090 MHz for use by aeronautical utility mobile stations for ground vehicle identification and collision avoidance after coordination with the FAA, subject to the following conditions:

(1) The applicant must notify the appropriate Regional Office of the FAA prior to submission to the Commission of an application for a new station or for modification of an existing station. Each application must include the FAA Regional Office notified and date of notification.

(2) Eligibility is restricted to airport operators holding an FAA Airport Operating Certificate, and other entities approved by the FAA on a case-by-case basis to use frequency 1090 MHz for use by aeronautical utility mobile stations for ground vehicle identification and collision avoidance;

(3) No more than two hundred 1090 MHz aeronautical utility mobile stations will be authorized at one airport;

(4) Licenses are limited to only those locations that are within the vicinity of an FAA ASDE-X multilateration system or ADS-B equipment, and/or where the primary purpose for seeking transmit authorization is to provide surface data to aircraft and air traffic control authorities.

(5) Message transmission rates are limited as indicated in the table below:

ADS-B Message	Rate when moving	Rate when stationary
Surface Position Message (Types 5, 6, 7, 8).	Every 0.4 to 0.6 seconds	Every 4.8 to 5.2 seconds.
Aircraft Operational Status (Type 31)	Every 4.8 to 5.2 seconds	Every 4.8 to 5.2 seconds.
Aircraft Identification and Type (Type 2)	Every 4.8 to 5.2 seconds	Every 9.8 to 10.2 seconds.

[55 FR 30464, July 26, 1990, as amended at 55 FR 30908, July 30, 1990; 71 FR 70680, Dec. 6, 2006; 78 FR 61207, Oct. 3, 2013]

Subpart M—Aeronautical Search and Rescue Stations

§ 87.351 Frequency changes.

When the aeronautical utility frequency is required to be changed because of an action by the FAA or the Commission (such as a change in the ground control of unicom frequency) the licensee must submit an application for modification to specify the new frequency within 10 days from the date the station begins operation on the new frequency. The licensee has temporary authority to use the new frequency from the date of the change pending receipt of the modified license.

§ 87.371 Scope of service.

Aeronautical search and rescue land and mobile stations must be used only for communications with aircraft and other aeronautical search and rescue stations engaged in search and rescue activities. Aeronautical land search and rescue stations can be moved for temporary periods from a specified location to an area where actual or practice search and rescue operations are being conducted.