

### § 1.30003

### 47 CFR Ch. I (10–1–15 Edition)

2013, that meets the criteria in paragraphs (a) and (b) of this section, unless the analysis and notice process described in this subpart, and any necessary measures to correct disturbances of the AM radiation pattern, have been completed by the tower owner, the party proposing to locate the antenna, or any other party, either prior to construction or at any other time prior to the proposal or antenna location.

[78 FR 66295, Nov. 5, 2013]

#### § 1.30003 Installations on an AM antenna.

(a) *Installations on a nondirectional AM tower.* When antennas are installed on a nondirectional AM tower the AM station shall determine the operating power by the indirect method (see § 73.51 of this chapter). Upon completion of the installation, antenna impedance measurements on the AM antenna shall be made. If the resistance of the AM antenna changes by more than 2 percent (see § 73.45(c)(1) of this chapter), an application on FCC Form 302-AM (including a tower sketch of the installation) shall be filed with the Commission for the AM station to return to direct power measurement.

(b) *Installations on a directional AM array.* Before antennas are installed on a tower in a directional AM array, the proponent shall notify the AM station so that, if necessary, the AM station may determine operating power by the indirect method (see § 73.51 of this chapter) and request special temporary authority pursuant to § 73.1635 of this chapter to operate with parameters at variance.

(1) For AM stations licensed via field strength measurements (see § 73.151(a)), a partial proof of performance as defined by § 73.154 of this chapter shall be conducted by the tower proponent both before and after construction to establish that the AM array will not be and has not been adversely affected. If the operating parameters of the AM array change following the installation, the results of the partial proof of performance shall be filed by the AM station with the Commission on Form 302-AM.

(2) For AM stations licensed via a moment method proof (see § 73.151(c) of this chapter), a base impedance meas-

urement on the tower being modified shall be made by the tower proponent as described in § 73.151(c)(1). The result of the new tower impedance measurement shall be retained in the station's records. If the new measured base resistance and reactance values of the affected tower differ by more than  $\pm 2$  ohms and  $\pm 4$  percent from the corresponding modeled resistance and reactance values contained in the last moment method proof, then the station shall file Form 302-AM. The Form 302-AM shall be accompanied by the new impedance measurements for the modified tower and a new moment method model for each pattern in which the tower is a radiating element. Base impedance measurements for other towers in the array, sampling system measurements, and reference field strength measurements need not be repeated. The procedures described in this paragraph may be used as long as the affected tower continues to meet the requirements for moment method proofing after the modification.

(c) *Form 302-AM Filing.* When the AM station is required to file Form 302-AM following an installation as set forth in paragraphs (a) and (b) of this section, the Form 302-AM shall be filed before or simultaneously with any license application associated with the installation. If no license application is filed as a result of the installation, the Form 302-AM shall be filed within 30 days after the completion of the installation.

[78 FR 66295, Nov. 5, 2013]

#### § 1.30004 Notice of tower construction or modification near AM stations.

(a) Proponents of proposed tower construction or significant modification to an existing tower near an AM station that are subject to the notification requirement in §§ 1.30002 and 1.30003 shall provide notice of the proposed tower construction or modification to the AM station at least 30 days prior to commencement of the planned tower construction or modification. Notice shall be provided to any AM station that is licensed or operating under Program Test Authority using the official licensee information and address listed

## Federal Communications Commission

## § 1.40001

in CDBS or any successor database. Notification to an AM station and any responses may be oral or written. If such notification and/or response is oral, the party providing such notification or response must supply written documentation of the communication and written documentation of the date of communication upon request of the other party to the communication or the Commission. Notification must include the relevant technical details of the proposed tower construction or modification. At a minimum, the notification should include the following:

(1) Proponent's name and address. Coordinates of the tower to be constructed or modified.

(2) Physical description of the planned structure.

(3) Results of the analysis showing the predicted effect on the AM pattern, if performed.

(b) Response to a notification should be made as quickly as possible, even if no technical problems are anticipated. Any response to a notification indicating a potential disturbance of the AM radiation pattern must specify the technical details and must be provided to the proponent within 30 days. If no response to notification is received within 30 days, the proponent may proceed with the proposed tower construction or modification.

(c) The 30-day response period is calculated from the date of receipt of the notification by the AM station. If notification is by mail, this date may be ascertained by:

(1) The return receipt on certified mail;

(2) The enclosure of a card to be dated and returned by the recipient; or

(3) A conservative estimate of the time required for the mail to reach its destination, in which case the estimated date when the 30-day period would expire shall be stated in the notification.

(d) An expedited notification period (less than 30 days) may be requested when deemed necessary by the proponent. The notification shall be identified as "expedited" and the requested response date shall be clearly indicated. The proponent may proceed with the proposed tower construction or modification prior to the expiration of

the 30-day notification period only upon receipt of written concurrence from the affected AM station (or oral concurrence, with written confirmation to follow).

(e) To address immediate and urgent communications needs in the event of an emergency situation involving essential public services, public health, or public welfare, a tower proponent may erect a temporary new tower or make a temporary significant modification to an existing tower without prior notice to potentially affected nearby AM stations, provided that the tower proponent shall provide written notice to such AM stations within five days of the construction or modification of the tower and shall cooperate with such AM stations to promptly remedy any pattern distortions that arise as a consequence of such construction.

[78 FR 66295, Nov. 5, 2013]

### Subpart CC—State and Local Review of Applications for Wireless Service Facility Modification

SOURCE: 80 FR 1269, Jan. 8, 2015, unless otherwise noted.

#### § 1.40001 Wireless Facility Modifications.

(a) *Purpose.* These rules implement section 6409 of the Spectrum Act (codified at 47 U.S.C. 1455), which requires a State or local government to approve any eligible facilities request for a modification of an existing tower or base station that does not substantially change the physical dimensions of such tower or base station.

(b) *Definitions.* Terms used in this section have the following meanings.

(1) *Base station.* A structure or equipment at a fixed location that enables Commission-licensed or authorized wireless communications between user equipment and a communications network. The term does not encompass a tower as defined in this subpart or any equipment associated with a tower.

(i) The term includes, but is not limited to, equipment associated with wireless communications services such as private, broadcast, and public safety