

on an individual basis in accordance with part 1, subpart G, of this chapter.

(f) Modifications to existing authorized EAS decoders, encoders or combined units necessary to implement the new EAS codes specified in § 11.31 and to implement the selective displaying and logging feature specified in § 11.33(a)(4) will be considered Class I permissive changes that do not require a new application for and grant of equipment certification under part 2, subpart J of this chapter.

(g) All existing and new models of EAS encoders, decoders and combined units manufactured after August 1, 2003 must be capable of generating and detecting the new EAS codes specified in § 11.31 in order to be certified under part 2, subpart J of this chapter. All existing and new models of EAS decoders and combined units manufactured after August 1, 2003 must have the selective displaying and logging capability specified in § 11.33(a)(4) in order to be certified under part 2, subpart J of this chapter.

[59 FR 67092, Dec. 28, 1994, as amended at 60 FR 56000, Nov. 6, 1995; 67 FR 18510, Apr. 16, 2002; 70 FR 71034, Nov. 25, 2005; 77 FR 16703, Mar. 22, 2012]

§ 11.35 Equipment operational readiness.

(a) EAS Participants are responsible for ensuring that EAS Encoders, EAS Decoders, Attention Signal generating and receiving equipment, and Intermediate Devices used as part of the EAS to decode and/or encode messages formatted in the EAS Protocol and/or the Common Alerting Protocol are installed so that the monitoring and transmitting functions are available during the times the stations and systems are in operation. Additionally, EAS Participants must determine the cause of any failure to receive the required tests or activations specified in § 11.61(a)(1) and (2). Appropriate entries indicating reasons why any tests were not received must be made in the broadcast station log as specified in §§ 73.1820 and 73.1840 of this chapter for all broadcast streams and cable system records as specified in §§ 76.1700, 76.1708, and 76.1711 of this chapter. All other EAS Participants must also keep records indicating reasons why any

tests were not received and these records must be retained for two years, maintained at the EAS Participant's headquarters, and made available for public inspection upon reasonable request.

(b) If an EAS Encoder, EAS Decoder or Intermediary Device used as part of the EAS to decode and/or encode messages formatted in the EAS Protocol and/or the Common Alerting Protocol becomes defective, the EAS Participant may operate without the defective equipment pending its repair or replacement for 60 days without further FCC authority. Entries shall be made in the broadcast station log, cable system records, and records of other EAS Participants, as specified in paragraph (a) of this section, showing the date and time the equipment was removed and restored to service. For personnel training purposes, the required monthly test script must still be transmitted even though the equipment for generating the EAS message codes, Attention Signal and EOM code is not functioning.

(c) If repair or replacement of defective equipment is not completed within 60 days, an informal request shall be submitted to the Regional Director of the FCC field office serving the area in which the EAS Participant is located, or in the case of DBS and SDARS providers to the Regional Director of the FCC field office serving the area where their headquarters is located, for additional time to repair the defective equipment. This request must explain what steps have been taken to repair or replace the defective equipment, the alternative procedures being used while the defective equipment is out of service, and when the defective equipment will be repaired or replaced.

[70 FR 71034, Nov. 25, 2005, as amended at 77 FR 16704, Mar. 22, 2012; 80 FR 53750, Sept. 8, 2015]

Subpart C—Organization

§ 11.41 Participation in EAS.

All EAS Participants specified in § 11.11 are categorized as Participating National (PN) sources, and must have