

automatically block programming with a more restrictive age rating but a similar content rating. For example, if all shows rated TV-PG-V have been selected for blocking, the user should be able to block automatically shows with the more restrictive ratings of TV-14-V and TV-MA-V.

(iii) The user should have the capability of overriding the automatic blocking described in paragraphs (e)(4)(i) and (4)(ii) of this section.

[63 FR 20133, Apr. 23, 1998, as amended at 68 FR 68546, Dec. 9, 2003; 69 FR 2849, Jan. 21, 2004; 69 FR 59534, Oct. 4, 2004; 73 FR 5682, Jan. 30, 2008; 74 FR 63079, Dec. 2, 2009; 77 FR 4913, Feb. 1, 2012]

§ 15.121 Scanning receivers and frequency converters used with scanning receivers.

(a) Except as provided in paragraph (c) of this section, scanning receivers and frequency converters designed or marketed for use with scanning receivers, shall:

(1) Be incapable of operating (tuning), or readily being altered by the user to operate, within the frequency bands allocated to the Cellular Radiotelephone Service in part 22 of this chapter (cellular telephone bands). Scanning receivers capable of “readily being altered by the user” include, but are not limited to, those for which the ability to receive transmissions in the cellular telephone bands can be added by clipping the leads of, or installing, a simple component such as a diode, resistor or jumper wire; replacing a plug-in semiconductor chip; or programming a semiconductor chip using special access codes or an external device, such as a personal computer. Scanning receivers, and frequency converters designed for use with scanning receivers, also shall be incapable of converting digital cellular communication transmissions to analog voice audio.

(2) Be designed so that the tuning, control and filtering circuitry is inaccessible. The design must be such that any attempts to modify the equipment to receive transmissions from the Cellular Radiotelephone Service likely will render the receiver inoperable.

(b) Except as provided in paragraph (c) of this section, scanning receivers shall reject any signals from the Cel-

lular Radiotelephone Service frequency bands that are 38 dB or lower based upon a 12 dB SINAD measurement, which is considered the threshold where a signal can be clearly discerned from any interference that may be present.

(c) Scanning receivers and frequency converters designed or marketed for use with scanning receivers, are not subject to the requirements of paragraphs (a) and (b) of this section provided that they are manufactured exclusively for, and marketed exclusively to, entities described in 18 U.S.C. 2512(2), or are marketed exclusively as test equipment pursuant to §15.3(dd).

(d) Modification of a scanning receiver to receive transmissions from Cellular Radiotelephone Service frequency bands will be considered to constitute manufacture of such equipment. This includes any individual, individuals, entity or organization that modifies one or more scanners. Any modification to a scanning receiver to receive transmissions from the Cellular Radiotelephone Service frequency bands voids the certification of the scanning receiver, regardless of the date of manufacture of the original unit. In addition, the provisions of §15.23 shall not be interpreted as permitting modification of a scanning receiver to receive Cellular Radiotelephone Service transmissions.

(e) Scanning receivers and frequency converters designed for use with scanning receivers shall not be assembled from kits or marketed in kit form unless they comply with the requirements in paragraph (a) through (c) of this section.

(f) Scanning receivers shall have a label permanently affixed to the product, and this label shall be readily visible to the purchaser at the time of purchase. The label shall read as follows: WARNING: MODIFICATION OF THIS DEVICE TO RECEIVE CELLULAR RADIOTELEPHONE SERVICE SIGNALS IS PROHIBITED UNDER FCC RULES AND FEDERAL LAW.

(1) “Permanently affixed” means that the label is etched, engraved, stamped, silkscreened, indelible printed or otherwise permanently marked on a permanently attached part of the equipment or on a nameplate of metal,

§ 15.122

plastic or other material fastened to the equipment by welding, riveting, or permanent adhesive. The label shall be designed to last the expected lifetime of the equipment in the environment in which the equipment may be operated and must not be readily detachable. The label shall not be a stick-on, paper label.

(2) When the device is so small that it is not practicable to place the warning label on it, the information required by this paragraph shall be placed in a prominent location in the instruction manual or pamphlet supplied to the user and shall also be placed on the container in which the device is marketed. However, the FCC identifier must be displayed on the device.

[64 FR 22561, Apr. 27, 1999, as amended at 66 FR 32582, June 15, 2001]

§ 15.122 [Reserved]

§ 15.123 Labeling of digital cable ready products.

(a) The requirements of this section shall apply to unidirectional digital cable products. Unidirectional digital cable products are one-way devices that accept a Point of Deployment module (POD) and which include, but are not limited to televisions, set-top-boxes and recording devices connected to digital cable systems. Unidirectional digital cable products do not include interactive two-way digital television products.

(b) A unidirectional digital cable product may not be labeled with or marketed using the term “digital cable ready,” or other terminology that describes the device as “cable ready” or “cable compatible,” or otherwise indicates that the device accepts a POD or conveys the impression that the device is compatible with digital cable service unless it implements at a minimum the following features:

(1) Tunes NTSC analog channels transmitted in-the-clear.

(2) Tunes digital channels that are transmitted in compliance with SCTE 40 2003 (formerly DVS 313): “Digital Cable Network Interface Standard” (incorporated by reference, *see* §15.38), provided, however, that with respect to Table B.11 of that standard, the phase noise requirement shall be -86 dB/Hz

47 CFR Ch. I (10–1–15 Edition)

including both in-the-clear channels and channels that are subject to conditional access.

(3) Allows navigation of channels based on channel information (virtual channel map and source names) provided through the cable system in compliance with ANSI/SCTE 65 2002 (formerly DVS 234): “Service Information Delivered Out-of-Band for Digital Cable Television” (incorporated by reference, *see* §15.38), and/or PSIP-enabled navigation (ANSI/SCTE 54 2003 (formerly DVS 241): “Digital Video Service Multiplex and Transport System Standard for Cable Television” (incorporated by reference, *see* §15.38)).

(4) Includes the POD-Host Interface specified in SCTE 28 2003 (formerly DVS 295): “Host-POD Interface Standard” (incorporated by reference, *see* §15.38), and SCTE 41 2003 (formerly DVS 301): “POD Copy Protection System” (incorporated by reference, *see* §15.38), or implementation of a more advanced POD-Host Interface based on successor standards. Support for Internet protocol flows is not required.

(5) Responds to emergency alerts that are transmitted in compliance with ANSI/SCTE 54 2003 (formerly DVS 241): “Digital Video Service Multiplex and Transport System Standard for Cable Television” (incorporated by reference, *see* §15.38).

(6) In addition to the requirements of paragraphs (b)(1) through (5) of this section, a unidirectional digital cable television may not be labeled or marketed as digital cable ready or with other terminology as described in paragraph (b) of this section, unless it includes a DTV broadcast tuner as set forth in §15.117(i) and employs at least one interface specified in paragraphs (b)(6)(i) and (ii) of this section:

(i) For 480p grade unidirectional digital cable televisions, either a DVI/HDCP, HDMI/HDCP, or 480p Y,Pb,Pr interface.

(ii) For 720p/1080i grade unidirectional digital cable televisions, either a DVI/HDCP or HDMI/HDCP interface.

(c) Before a manufacturer’s or importer’s first unidirectional digital cable product may be labeled or marketed as digital cable ready or with