

**§ 17.48 Notification of extinguishment or improper functioning of lights.**

The owner of any antenna structure which is registered with the Commission and has been assigned lighting specifications referenced in this part:

(a) Shall report immediately to the FAA, by means acceptable to the FAA, any observed or otherwise known extinguishment or improper functioning of any top steady burning light or any flashing obstruction light, regardless of its position on the antenna structure, not corrected within 30 minutes. If the lights cannot be repaired within the FAA's Notices to Airmen (NOTAM) period, the owner shall notify the FAA to extend the outage date and report a return-to-service date. The owner shall repeat this process until the lights are repaired. Such reports shall set forth the condition of the light or lights, the circumstances which caused the failure, the probable date for restoration of service, the FCC Antenna Structure Registration Number, the height of the structure (AGL and AMSL if known) and the name, title, address, and telephone number of the person making the report. Further notification to the FAA by means acceptable to the FAA shall be given immediately upon resumption of normal operation of the light or lights.

(b) An extinguishment or improper functioning of a steady burning side intermediate light or lights, shall be corrected as soon as practicable, but notification to the FAA of such extinguishment or improper functioning is not required.

[32 FR 11273, Aug. 3, 1967, as amended at 39 FR 26157, July 17, 1974; 40 FR 30267, July 18, 1975; 61 FR 4364, Feb. 6, 1996; 79 FR 56986, Sept. 24, 2014]

**§ 17.49 Recording of antenna structure light inspections in the owner record.**

The owner of each antenna structure which is registered with the Commission and has been assigned lighting specifications referenced in this part must maintain a record of any observed or otherwise known extinguishment or improper functioning of a structure light. This record shall be retained for a period of two years and provided to the FCC or its agents upon

request. The record shall include the following information for each such event:

(a) The nature of such extinguishment or improper functioning.

(b) The date and time the extinguishment or improper operation was observed or otherwise noted.

(c) Date and time of FAA notification, if applicable.

(d) The date, time and nature of adjustments, repairs, or replacements made.

[48 FR 38477, Aug. 24, 1983, as amended at 61 FR 4364, Feb. 6, 1996; 79 FR 56987, Sept. 24, 2014]

**§ 17.50 Cleaning and repainting.**

Antenna structures requiring painting under this part shall be cleaned or repainted as often as necessary to maintain good visibility. Evaluation of the current paint status shall be made by using the FAA's In-Service Aviation Orange Tolerance Chart. This chart is based upon the color requirements contained in the National Bureau of Standards Report NBSIR 75-663, Color Requirements for the Marking of Obstructions.

[79 FR 56987, Sept. 24, 2014]

**§ 17.51 [Reserved]**

**§ 17.53 Lighting equipment and paint.**

The lighting equipment, color or filters, and shade of paint referred to in the specifications are further defined in the following government and/or Army-Navy aeronautical specifications, bulletins, and drawings (lamps are referred to by standard numbers):

Outside white .....	TT-P-102 <sup>1</sup> (Color No. 17875, FS-595).
Aviation surface orange .....	TT-P-59 <sup>1</sup> (Color No. 12197, FS-595).
Aviation surface orange, enamel.	TT-E-489 <sup>1</sup> (Color No. 12197, FS-595).
Aviation red obstruction light—color.	MIL-C-25050 <sup>2</sup> .
Flashing beacons .....	CAA-446 <sup>3</sup> Code Beacons, 300 mm.
Do .....	MIL-6273 <sup>2</sup> .
Double and single obstruction light.	L-810 <sup>3</sup> (FAA AC No. 150/5345-2 <sup>4</sup> ).
Do .....	MIL-L-7830 <sup>2</sup> .
High intensity white obstruction light.	FAA/DOD L-856 (FAA AC No. 150/5345-43B <sup>4</sup> ).
116-Watt lamp .....	No. 116 A21/TS (6,000 h).
125-Watt lamp .....	No. 125 A21/TS (6,000 h).
620-Watt lamp .....	No. 620 PS-40 (3,000 h).