

§ 22.357

TABLE C-1—FREQUENCY TOLERANCE FOR TRANSMITTERS IN THE PUBLIC MOBILE SERVICES

Frequency range (MHz)	Base, fixed (ppm)	Mobile >3 watts (ppm)	Mobile ≤3 watts (ppm)
25 to 50	20.0	20.0	50.0
50 to 450	5.0	5.0	50.0
450 to 512	2.5	5.0	5.0
821 to 896	1.5	2.5	2.5
928 to 929	5.0	n/a	n/a
929 to 960	1.5	n/a	n/a
2110 to 2220	10.0	n/a	n/a

[61 FR 54099, Oct. 17, 1996]

§ 22.357 Emission types.

Any authorized station in the Public Mobile Services may transmit emissions of any type(s) that comply with the applicable emission rule, *i.e.* § 22.359, § 22.861 or § 22.917.

[70 FR 19308, Apr. 13, 2005]

§ 22.359 Emission limitations.

The rules in this section govern the spectral characteristics of emissions in the Public Mobile Services, except for the Air-Ground Radiotelephone Service (see § 22.861, instead) and the Cellular Radiotelephone Service (see § 22.917, instead).

(a) *Out of band emissions.* The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log (P)$ dB.

(b) *Measurement procedure.* Compliance with these rules is based on the use of measurement instrumentation employing a resolution bandwidth of 30 kHz or more. In the 60 kHz bands immediately outside and adjacent to the authorized frequency range or channel, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. A narrower resolution bandwidth is permitted in all cases to improve measurement accuracy provided the measured power is integrated over the full required measurement bandwidth (*i.e.*, 30 kHz or 1 percent of emission bandwidth, as specified). The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of

47 CFR Ch. I (10–1–15 Edition)

which all emissions are attenuated at least 26 dB below the transmitter power.

(c) *Alternative out of band emission limit.* Licensees in the Public Mobile Services may establish an alternative out of band emission limit to be used at specified frequencies (band edges) in specified geographical areas, in lieu of that set forth in this section, pursuant to a private contractual arrangement of all affected licensees and applicants. In this event, each party to such contract shall maintain a copy of the contract in their station files and disclose it to prospective assignees or transferees and, upon request, to the FCC.

(d) *Interference caused by out of band emissions.* If any emission from a transmitter operating in any of the Public Mobile Services results in interference to users of another radio service, the FCC may require a greater attenuation of that emission than specified in this section.

[70 FR 19308, Apr. 13, 2005]

§ 22.365 Antenna structures; air navigation safety.

Licensees that own their antenna structures must not allow these antenna structures to become a hazard to air navigation. In general, antenna structure owners are responsible for registering antenna structures with the FCC if required by part 17 of this chapter, and for installing and maintaining any required marking and lighting. However, in the event of default of this responsibility by an antenna structure owner, each FCC permittee or licensee authorized to use an affected antenna structure will be held responsible by the FCC for ensuring that the antenna structure continues to meet the requirements of part 17 of this chapter. See § 17.6 of this chapter.

(a) *Marking and lighting.* Antenna structures must be marked, lighted and maintained in accordance with part 17 of this chapter and all applicable rules and requirements of the Federal Aviation Administration.

(b) *Maintenance contracts.* Antenna structure owners (or licensees and permittees, in the event of default by an antenna structure owner) may enter into contracts with other entities to

Federal Communications Commission

§ 22.503

monitor and carry out necessary maintenance of antenna structures. Antenna structure owners (or licensees and permittees, in the event of default by an antenna structure owner) that make such contractual arrangements continue to be responsible for the maintenance of antenna structures in regard to air navigation safety.

[61 FR 4365, Feb. 6, 1996]

§ 22.377 Certification of transmitters.

Transmitters used in the Public Mobile Services, including those used with signal boosters, in-building radiation systems and cellular repeaters, must be certificated for use in the radio services regulated under this part. Transmitters must be certificated when the station is ready for service, not necessarily at the time of filing an application. The FCC may list as certificated only transmitters that are capable of meeting all technical requirements of the rules governing the service in which they will operate. The procedure for obtaining certification is set forth in part 2 of this chapter.

[78 FR 25174, Apr. 29, 2013]

§ 22.383 In-building radiation systems.

Licensees may install and operate in-building radiation systems without applying for authorization or notifying the FCC, provided that the locations of the in-building radiation systems are within the protected service area of the licensee's authorized transmitter(s) on the same channel or channel block.

Subpart D [Reserved]

Subpart E—Paging and Radiotelephone Service

§ 22.501 Scope.

The rules in this subpart govern the licensing and operation of public mobile paging and radiotelephone stations. The licensing and operation of these stations are also subject to rules elsewhere in this part that apply generally to the Public Mobile Services. However, in case of conflict, the rules in this subpart govern.

§ 22.503 Paging geographic area authorizations.

The FCC considers applications for and issues paging geographic area authorizations in the Paging and Radiotelephone Service in accordance with the rules in this section. Each paging geographic area authorization contains conditions requiring compliance with paragraphs (h) and (i) of this section.

(a) *Channels*. The FCC may issue a paging geographic area authorization for any channel listed in § 22.531 of this part or for any channel pair listed in § 22.561 of this part.

(b) *Paging geographic areas*. The paging geographic areas are as follows:

(1) The Nationwide paging geographic area comprises the District of Columbia and all States, Territories and possessions of the United States of America.

(2) Major Economic Areas (MEAs) and Economic Areas (EAs) are defined below. EAs are defined by the Department of Commerce, Bureau of Economic Analysis. *See* Final Redefinition of the MEA Economic Areas, 60 FR 13114 (March 10, 1995). MEAs are based on EAs. In addition to the Department of Commerce's 172 EAs, the FCC shall separately license Guam and the Northern Mariana Islands, Puerto Rico and the United States Virgin Islands, and American Samoa, which have been assigned FCC-created EA numbers 173–175, respectively, and MEA numbers 49–51, respectively.

(3) The 51 MEAs are composed of one or more EAs as defined in the following table:

MEAs	EAs
1 (Boston)	1–3.
2 (New York City)	4–7, 10.
3 (Buffalo)	8.
4 (Philadelphia)	11–12.
5 (Washington)	13–14.
6 (Richmond)	15–17, 20.
7 (Charlotte-Greensboro-Greenville-Raleigh).	18–19, 21–26, 41–42, 46.
8 (Atlanta)	27–28, 37–40, 43.
9 (Jacksonville)	29, 35.
10 (Tampa-St. Petersburg-Orlando).	30, 33–34.
11 (Miami)	31–32.
12 (Pittsburgh)	9, 52–53.
13 (Cincinnati-Dayton)	48–50.
14 (Columbus)	51.
15 (Cleveland)	54–55.
16 (Detroit)	56–58, 61–62.
17 (Milwaukee)	59–60, 63, 104–105, 108.
18 (Chicago)	64–66, 68, 97, 101.