§ 25.205

percent of the actual amount of monitored excess attenuation in dB, whichever is larger, with a confidence level of 90 percent except over transient periods accounting for no more than 0.5 percent of the time during which the excess is no more than 4.0 dB.

(f) An earth station in the Fixed-Satellite Service transmitting in the 13.75–14 GHz band must have a minimum antenna diameter of 4.5 m, and the EIRP of any emission in that band should be at least 68 dBW and should not exceed 85 dBW.

(g) [Reserved]

- (h) ESV transmissions in the 5925–6425 MHz (Earth-to-space) band shall not exceed an e.i.r.p. spectral density towards the radio-horizon of 17 dBW/MHz, and shall not exceed an e.i.r.p. towards the radio-horizon of 20.8 dBW. The ESV network shall shut-off the ESV transmitter if the e.i.r.p. spectral density towards the radio-horizon or e.i.r.p. towards the radio-horizon are exceeded.
- (i) Within 125 km of the TDRSS sites identified in §25.222(d), ESV transmissions in the 14.0–14.2 GHz (Earth-tospace) band shall not exceed an e.i.r.p. spectral density towards the horizon of 12.5 dBW/MHz, and shall not exceed an e.i.r.p. towards the horizon of 16.3 dBW.
- (j) Within 125 km of the Tracking and Data Relay System Satellite (TDRSS) sites identified in §25.226(c), VMES transmissions in the 14.0-14.2 GHz (Earth-to-space) band shall not exceed an EIRP spectral density towards the horizon of 12.5 dBW/MHz, and shall not exceed an EIRP towards the horizon of 16.3 dBW.
- (k) Within radio line-of-sight of the Tracking and Data Relay System Satellite (TDRSS) sites identified in §25.227(c), ESAA transmissions in the 14.0–14.2 GHz (Earth-to-space) band shall not exceed an EIRP spectral density towards or below the horizon of 12.5 dBW/MHz, and shall not exceed an EIRP towards or below the horizon of 16.3 dBW.

[48 FR 40255, Sept. 6, 1983, as amended at 58 FR 13420, Mar. 11, 1993; 61 FR 52307, Oct. 7, 1996; 62 FR 61457, Nov. 18, 1997; 66 FR 10623, Feb. 16, 2001; 70 FR 4784, Jan. 31, 2005; 70 FR 32255, June 2, 2005; 72 FR 50029, Aug. 29, 2007; 74 FR 57098, Nov. 4, 2009; 78 FR 8427, Feb. 6, 2013; 78 FR 14927, Mar. 8, 2013; 79 FR 8322, Feb. 12, 20041

§ 25,205 Minimum angle of antenna elevation.

- (a) Earth station antennas shall not normally be authorized for transmission at angles less than 5° measured from the horizontal plane to the direction of maximum radiation. However, upon a showing that the transmission path will be seaward and away from land masses or upon special showing of need for lower angles by the applicant, the Commission will consider authorizing transmissions at angles between 3° and 5° in the pertinent directions. In certain instances, it may be necessary to specify minimum angles greater than 5° because of interference considerations.
- (b) ESVs making a special showing requesting angles of elevation less than 5° measured from the horizontal plane to the direction of maximum radiation pursuant to (a) of this Section must still meet the effective isotropically radiated power (e.i.r.p.) and e.i.r.p. density towards the horizon limits contained in §25.204(h) and (i).
- (c) VMESs making a special showing requesting angles of elevation less than 5° measured from the horizontal plane to the direction of maximum radiation pursuant to (a) of this section must still meet the EIRP and EIRP density towards the horizon limits contained in §25.204(j).
- (d) While on the ground, ESAAs shall not be authorized for transmission at angles less than 5° measured from the plane of the horizon to the direction of maximum radiation. While in flight there is no minimum angle of antenna elevation.

[70 FR 4784, Jan. 31, 2005, as amended at 74 FR 57099, Nov. 4, 2009; 78 FR 14927, Mar. 8, 2013]

§25.206 Station identification.

The requirement to transmit station identification is waived for all radio stations licensed under this part with the exception of earth stations subject to the requirements of §25.281.

[79 FR 8322, Feb. 12, 2014]

§25.207 Cessation of emissions.

Space stations shall be made capable of ceasing radio emissions by the use of