

§ 25.214

47 CFR Ch. I (10–1–15 Edition)

MHz band so as not to exceed -241 dB (W/m²/Hz) at the surface of the Earth.

(4) The Radioastronomy Service shall avoid scheduling radio astronomy observations during peak MSS/RDSS traffic periods to the greatest extent practicable.

(b) If a Mobile-Satellite Service space station operator in the 2496–2500 MHz band intends to operate at powers levels that exceed the PFD limits in § 25.208(v), or if actual operations routinely exceed these PFD limits, we require the Mobile-Satellite Service operator to receive approval from each operational BRS system in the affected geographical region.

[59 FR 53329, Oct. 21, 1994, as amended at 61 FR 9945, Mar. 12, 1996; 67 FR 61816, Oct. 2, 2002; 71 FR 35188, June 19, 2006; 78 FR 8428, Feb. 6, 2013]

§ 25.214 Technical requirements for space stations in the Satellite Digital Audio Radio Service and associated terrestrial repeaters.

(a) [Reserved]

(b) Each system authorized under this section will be conditioned upon construction, launch and operation milestones as outlined in § 25.144(b). The failure to meet any of the milestones contained in an authorization will result in its cancellation, unless such failure is due to circumstances beyond the licensee's control or unless otherwise determined by the Commission upon proper showing by the licensee in any particular case.

(c) Frequency assignments will be made for each satellite DARS system as follows:

(1) Exclusive SDARS licenses are limited to the 2320–2345 MHz segment of the 2310–2360 MHz allocated bandwidth for SDARS;

(2) Two, 12.5 MHz frequency assignments are available for satellite DARS: 2320.0–2332.5 MHz and 2332.5–2345.0 MHz;

(3) Satellite DARS licensees may reduce their assigned bandwidth occupancy to provide telemetry beacons in their exclusive frequency assignments;

(4) Each licensee may employ cross polarization within its exclusive frequency assignment and/or may employ cross polarized transmissions in frequency assignments of other satellite DARS licensees under mutual agree-

ment with those licensees. Licensees who come to mutual agreement to use cross-polarized transmissions shall apply to the Commission for approval of the agreement before coordination is initiated with other administrations by the licensee of the exclusive frequency assignment; and

(5) Feeder uplink networks are permitted in the following Fixed-Satellite Service frequency bands: 7025–7075 MHz and 6725–7025 MHz (101° W.L. orbital location only).

(d) *Power limit for SDARS terrestrial repeaters.* (1) SDARS terrestrial repeaters must be operated at a power level less than or equal to 12-kW average EIRP, with a maximum peak-to-average power ratio of 13 dB.

(2) SDARS repeaters are permitted to operate at power levels above 12-kW average EIRP, unless a potentially affected WCS licensee provides written notice that it intends to commence commercial service within the following 365 days. Starting 180 days after receipt of such written notice, SDARS repeaters within the area notified by the potentially affected WCS licensee must be operated at a power level less than or equal to 12-kW average EIRP, with a maximum peak-to-average power ratio of 13 dB.

(3) For the purpose of this section, a WCS licensee is potentially affected if it is authorized to operate a base station in the 2305–2315 MHz or 2350–2360 MHz bands within 25 kilometers of a repeater seeking to operate with a power level greater than that prescribed in paragraph (d)(1) of this section.

[62 FR 11106, Mar. 11, 1997, as amended at 75 FR 45068, Aug. 2, 2010; 78 FR 8429, Feb. 6, 2013; 78 FR 9619, Feb. 11, 2013; 79 FR 8323, Feb. 12, 2014]

§ 25.215 [Reserved]

§ 25.216 Limits on emissions from mobile earth stations for protection of aeronautical radionavigation-satellite service.

(a) The e.i.r.p. density of emissions from mobile earth stations placed in service on or before July 21, 2002 with assigned uplink frequencies between 1610 MHz and 1660.5 MHz shall not exceed -70 dBW/MHz, averaged over any 2 millisecond active transmission interval, in the band 1559–1587.42 MHz.