

sight of the new TDRSS site until the licensees complete coordination with NTIA/IRAC for the new TDRSS facility. Licensees shall notify the International Bureau once they have completed coordination for the new TDRSS site. Upon receipt of such notification from a licensee, the International Bureau will issue a public notice stating that the licensee may commence operations within the coordination zone in 30 days if no party has opposed the operations. The ESAA licensee then will be permitted to commence operations in the 14.0–14.2 GHz band within radio line-of-sight of the new TDRSS site, subject to any operational constraints developed in the coordination process.

(d)(1) Operations of ESAA in the 14.47–14.5 GHz (Earth-to-space) frequency band in the radio line-of-sight of radio astronomy service (RAS) observatories observing in the 14.47–14.5 GHz band are subject to coordination with the National Science Foundation (NSF). The appropriate NSF contact point to initiate coordination is Electromagnetic Spectrum Manager, NSF, 4201 Wilson Blvd., Suite 1045, Arlington VA 22203, fax 703–292–9034, email *esm@nsf.gov*. Licensees shall notify the International Bureau once they have completed coordination. Upon receipt of the coordination agreement from a licensee, the International Bureau will issue a public notice stating that the licensee may commence operations within the coordination zone in 30 days if no party has opposed the operations.

(2) A list of applicable RAS sites and their locations can be found in §25.226(d)(2) Table 1.

(3) When NTIA seeks to provide similar protection to future RAS sites that have been coordinated through the IRAC Frequency Assignment Subcommittee process, NTIA will notify the Commission's International Bureau that the site is nearing operational status. Upon public notice from the International Bureau, all Ku-band ESAA licensees shall cease operations in the 14.47–14.5 GHz band within the relevant geographic zone of the new RAS site until the licensees complete coordination for the new RAS facility. Licensees shall notify the International Bureau once they have completed coordination for the new RAS site and shall

submit the coordination agreement to the Commission. Upon receipt of such notification from a licensee, the International Bureau will issue a public notice stating that the licensee may commence operations within the coordination zone in 30 days if no party has opposed the operations. The ESAA licensee then will be permitted to commence operations in the 14.47–14.5 GHz band within the relevant coordination distance around the new RAS site, subject to any operational constraints developed in the coordination process.

[78 FR 14927, Mar. 8, 2013, as amended at 79 FR 8324, Feb. 12, 2014; 79 FR 26868, May 12, 2014]

§§ 25.228–25.249 [Reserved]

§ 25.250 Sharing between NGSO MSS Feeder links Earth Stations in the 19.3–19.7 GHz and 29.1–29.5 GHz Bands.

(a) NGSO MSS applicants shall be licensed to operate in the 29.1–29.5 GHz band for Earth-to-space transmissions and 19.3–19.7 GHz for space-to-Earth transmissions from feeder link earth station complexes. A “feeder link earth station complex” may include up to three (3) earth station groups, with each earth station group having up to four (4) antennas, located within a radius of 75 km of a given set of geographic coordinates provided by NGSO-MSS licensees or applicants.

(b) Licensees of NGSO MSS feeder link earth stations separated by 800 km or less are required to coordinate their operations, see §25.203. The results of the coordination shall be reported to the Commission.

[61 FR 44181, Aug. 28, 1996]

§ 25.251 Special requirements for coordination.

(a) The administrative aspects of the coordination process are set forth in §101.103 of this chapter in the case of coordination of terrestrial stations with earth stations, and in §25.203 in the case of coordination of earth stations with terrestrial stations.

(b) The technical aspects of coordination are based on Appendix 7 of the International Telecommunication Union Radio Regulations and certain recommendations of the ITU