feeder uplinks will have to demonstrate that their systems can share with GSO FSS and NGSO MSS systems that have been authorized for operation in that band.

 $[67~{\rm FR}~37336,~{\rm May}~29,~2002,~{\rm as}~{\rm amended}~{\rm at}~68~{\rm FR}~16967,~{\rm Apr.}~8,~2003]$

§ 25.259 Time sharing between NOAA meteorological satellite systems and non-voice, non-geostationary satellite systems in the 137-138 MHz band.

- (a) The space stations of a non-voice, non-geostationary Mobile-Satellite Service (NVNG MSS) system time-sharing downlink spectrum in the 137–138 MHz band with National Oceanic and Atmospheric Administration (NOAA) satellites shall not transmit signals into the "protection areas" of the NOAA satellites.
- (1) With respect to transmission in the 137.333–137.367 MHz, 137.485–137.515 MHz, 137.605–137.635 MHz, and 137.753–137.787 MHz bands, the protection area for a NOAA satellite is the area on the Earth's surface in which the NOAA satellite is in line of sight from the ground at an elevation angle of five degrees or more above the horizon. No NVNG MSS satellite shall transmit in these bands when it is in line of sight at an elevation angle of zero degrees or more from any point on the ground within a NOAA satellite's protected area for that band.
- (2) With respect to transmission in the 137.025-137.175 MHz and 137.825-138 MHz bands, the protection area for a NOAA satellite is the area on the Earth's surface in which the NOAA satellite is in line of sight from the ground at any elevation angle above zero degrees. No NVNG MSS satellite shall transmit in these bands when at a line-of-sight elevation angle of zero degrees or more from any point on the ground within a NOAA satellite's protected area for that band. In addition, such an NVNG MSS satellite shall cease transmitting when it is at an elevation angle of less than zero degrees from any such point, if reasonably necessary to protect reception of the NOAA satellite's signal.
- (3) An NVNG MSS licensee is responsible for obtaining the ephemeris data necessary for compliance with these re-

strictions. The ephemeris information must be updated system-wide on at least a weekly basis. For calculation required for compliance with these restrictions an NVNG MSS licensee shall use an orbital propagator algorithm with an accuracy equal to or greater than the NORAD propagator used by NOAA

- (b) An NVNG licensee time sharing spectrum in the 137-138 MHz band must establish a 24-hour per day contact person and telephone number so that claims of harmful interference into NOAA earth stations and other operational issues can be reported and resolved expeditiously. This contact information must be made available to NOAA or its designee. If the NTIA notifies the Commission that NOAA is receiving unacceptable interference from a NVNG licensee, the Commission will require such NVNG licensee to terminate its interfering operations immediately unless it demonstrates to the Commission's reasonable satisfaction, and that of NTIA, that it is not responsible for causing harmful interference into the worldwide NOAA system. An NVNG licensee assumes the risk of any liability or damage that it and its directors, officers, employees, affiliates, agents and subcontractors may incur or suffer in connection with an interruption of its Mobile-Satellite Service, in whole or in part, arising from or relating to its compliance or noncompliance with the requirements of this paragraph.
- (c) Each satellite in a NVNG licensee's system time-sharing spectrum with NOAA in the 137–138 MHz band shall automatically turn off and cease satellite transmissions if, after 72 consecutive hours, no reset signal is received from the NVNG licensee's gateway earth station and verified by the satellite. All satellites in such NVNG licensee's system shall be capable of instantaneous shutdown on any sub-band upon command from such NVNG licensee's gateway earth station.

[62 FR 59296, Nov. 3, 1997, as amended at 78 FR 8430, Feb. 6, 2013; 79 FR 8324, Feb. 12, 2014]