interference arising from the reverseband operations of U.S. authorized 17/24 GHz BSS networks to the extent that the DBS space station operates within the bounds of inclination and eccentricity listed below. When the geostationary orbit of the DBS space station exceeds these bounds on inclination and eccentricity, it may not claim protection from any additional space path interference arising as a result of its inclined or eccentric operations and may only claim protection as if it were operating within the bounds listed below:

- (1) The DBS space station's orbit does not exceed  $0.075^{\circ}$  of inclination, and
- (2) The DBS space station's orbit maintains an apogee less than or equal to 35,806 km above the surface of the Earth, and a perigee greater than or equal to 35,766 km above the surface of the Earth (*i.e.*, an eccentricity of less than  $4.7 \times 10^{-4}$ ).

[76 FR 50431, Aug. 15, 2011]

## § 25.265 Acceptance of interference in 2000–2020 MHz.

- (a) MSS receivers operating in the 2000-2020 MHz band must accept interference from lawful operations in the 1995-2000 MHz band, where such interference is due to:
- (1) The in-band power of any operations in 1995–2000 MHz (*i.e.*, the portion of transmit power contained in the 1995–2000 MHz band); or
- (2) The portion of out-of-band emissions contained in 2000–2005 MHz.
- (b) [Reserved]

[78 FR 8267, Feb. 5, 2013]

### **Subpart D—Technical Operations**

Source:  $58 \ \mathrm{FR}$  13421, Mar. 11, 1993, unless otherwise noted.

# $\S 25.271$ Control of transmitting stations.

- (a) The licensee of a facility licensed under this part is responsible for the proper operation and maintenance of the station.
- (b) The licensee of a transmitting earth station licensed under this part shall ensure that a trained operator is present on the earth station site, or at

- a designated remote control point for the earth station, at all times that transmissions are being conducted. No operator's license is required for a person to operate or perform maintenance on facilities authorized under this part.
- (c) Authority will be granted to operate a transmitting earth station by remote control only on the conditions that:
- (1) The parameters of the transmissions of the remote station monitored at the control point, and the operational functions of the remote earth stations that can be controlled by the operator at the control point, are sufficient to ensure that the operations of the remote station(s) are at all times in full compliance with the remote station authorization(s):
- (2) The earth station facilities are protected by appropriate security measures to prevent unauthorized entry or operations;
- (3) Upon detection by the licensee, or upon notification from the Commission of a deviation or upon notification by another licensee of harmful interference, the operation of the remote station shall be immediately suspended by the operator at the control point until the deviation or interference is corrected, except that transmissions concerning the immediate safety of life or property may be conducted for the duration of the emergency; and
- (4) The licensee shall have available at all times the technical personnel necessary to perform expeditiously the technical servicing and maintenance of the remote stations.
- (5) International VSAT system operators are required to maintain a control point within the United States, or to maintain a point of contact within the United States available 24 hours a day, 7 days a week, with the ability to shut off any earth station within the VSAT network immediately upon notification of harmful interference.
- (d) The licensee shall insure that the licensed facilities are properly secured against unauthorized access or use whenever an operator is not present at the transmitter.
- (e) The licensee of an NGSO FSS system operating in the 10.7–14.5 GHz bands shall maintain an electronic web site bulletin board to list the satellite

#### § 25.272

ephemeris data, for each satellite in the constellation, using the North American Aerospace Defense Command (NORAD) two-line orbital element format. The orbital elements shall be updated at least once every three days.

(f) The licensee of any transmitting earth station licensed under this part must update the contact information provided in the most recent license application for the station within 10 days of any change therein. The updated information must be filed electronically in the "Other Filings" tab of the station's current authorization file in the International Bureau Filing System.

[58 FR 13421, Mar. 11, 1993, as amended at 66 FR 10631, Feb. 16, 2001; 70 FR 4787, Jan. 31, 2005; 70 FR 32257, June 2, 2005; 74 FR 47107, Sept. 15, 2009; 78 FR 8430, Feb. 6, 2013; 79 FR 8325, Feb. 12, 2014]

# § 25.272 General inter-system coordination procedures.

- (a) Each space station licensee in the Fixed-Satellite Service shall establish a satellite network control center which will have the responsibility to do the following:
- (1) Monitor space-to-Earth transmissions in its system (thus indirectly monitoring uplink earth station transmissions in its system) and
- (2) Coordinate transmissions in its satellite system with those of other systems to prevent harmful interference incidents or, in the event of a harmful interference incident, to identify the source of the interference and correct the problem promptly.
  - (b) [Reserved]
- (c) The transmitting earth station licensee shall provide the operator(s) of the satellites, on which the licensee is authorized to transmit, contact telephone numbers for the control center of the earth station and emergency telephone numbers for key personnel; a current file of these contacts shall be maintained at each satellite system control center.
- (d) An earth station licensee shall ensure that each of its authorized earth stations complies with the following:
- (1) The earth station licensee shall ensure that there is continuously available means of communications between the satellite network control center and the earth station operator

or its remote control point as designated by the licensee.

- (2) The earth station operator shall notify the satellite network control center and receive permission from the control center before transmitting to the satellite or changing the basic characteristics of a transmission.
- (3) The earth station operator shall keep the space station licensee informed of all actual and planned usage.
- (4) Upon approval of the satellite network control center, the earth station operator may radiate an RF carrier into the designated transponder. Should improper illumination of the transponder or undue adjacent transponder interference be observed by the satellite network control center, the earth station operator shall immediately take whatever measures are needed to eliminate the problem.
- (5) The space station licensee may delegate the responsibility and duties of the satellite network control center to a technically qualified user or group of users, but the space station licensee shall remain ultimately responsible for the performance of those duties.

[58 FR 13421, Mar. 11, 1993, as amended at 62 FR 5931, Feb. 10, 1997; 78 FR 8431, Feb. 6, 2013; 79 FR 8325, Feb. 12, 2014]

## § 25.273 Duties regarding space communications transmissions.

- (a) No person shall:
- (1) Transmit to a satellite unless the specific transmission is first authorized by the satellite network control center;
- (2) Conduct transmissions over a transponder unless the operator is authorized to transmit at that time by the satellite licensee or the satellite licensee's successor in interest; or
- (3) Transmit in any manner that causes unacceptable interference to the authorized transmission of another licensee.
- (b) Satellite operators shall provide upon request by the Commission and by earth station licensees authorized to transmit on their satellites relevant information needed to avoid unacceptable interference to other users, including the polarization angles for proper illumination of a given transponder.
- (c) Space station licensees are responsible for maintaining complete and