

they offer real-time, two way switched voice service that is interconnected with the public switched network and utilize an in-network switching facility which enables the provider to reuse frequencies and/or accomplish seamless hand-offs of subscriber calls. Emergency Call Center personnel must determine the emergency caller's phone number and location and then transfer or otherwise redirect the call to an appropriate public safety answering point. Providers of Mobile-Satellite Services that utilize earth terminals that are not capable of use while in motion are exempt from providing Emergency Call Center service for such terminals.

(b) Beginning February 11, 2005, each Mobile-Satellite Service carrier that is subject to the provisions of paragraph (a) of this section must maintain records of all 911 calls received at its emergency call center. Beginning October 15, 2005, and on each following October 15, Mobile-Satellite Service carriers providing service in the 1.6/2.4 GHz and 2 GHz bands must submit a report to the Commission regarding their call center data, current as of September 30 of that year. Beginning June 30, 2006, and on each following June 30, Mobile-Satellite Service carriers providing service in bands other than 1.6/2.4 GHz and 2 GHz must submit a report to the Commission regarding their call center data, current as of May 31 of that year. These reports must include, at a minimum, the following:

- (1) The name and address of the carrier, the address of the carrier's emergency call center, and emergency call center contact information;
- (2) The aggregate number of calls received by the call center each month during the relevant reporting period;
- (3) An indication of how many calls received by the call center each month during the relevant reporting period required forwarding to a public safety answering point and how many did not require forwarding to a public safety answering point.

[69 FR 6582, Feb. 11, 2004, as amended at 69 FR 54042, Sept. 7, 2004; 78 FR 8431, Feb. 6, 2013]

§ 25.285 Operation of MSS and ATC transmitters or transceivers on board civil aircraft.

(a) Operation of any of the following devices aboard civil aircraft is prohibited, unless the device is installed in a manner approved by the Federal Aviation Administration or is used by the pilot or with the pilot's consent:

- (1) Earth stations capable of transmitting in the 1.5/1.6 GHz, 1.6/2.4 GHz, or 2 GHz Mobile-Satellite Service frequency bands;
- (2) ATC terminals capable of transmitting in the 1.5/1.6 GHz or 1.6/2.4 GHz MSS bands;
- (3) Earth stations used for non-voice, non-geostationary Mobile-Satellite Service communication that can emit radiation in the 108–137 MHz band.

(b) No portable device of any type identified in paragraph (a) of this section (including transmitter or transceiver units installed in other devices that are themselves portable) may be sold or distributed to users unless it conspicuously bears the following warning: "This device must be turned off at all times while on board aircraft." For purposes of this section, a device is portable if it is a "portable device" as defined in § 2.1093(b) of this chapter or is designed to be carried by hand.

[79 FR 8325, Feb. 12, 2014]

EFFECTIVE DATE NOTE: At 79 FR 44140, July 30, 2014, in § 25.285, paragraph (a)(2) was corrected. This text contains information collection and recordkeeping requirements and will not become effective until approval has been given by the Office of Management and Budget.

§ 25.286 Antenna painting and lighting.

The owner of an earth station antenna structure must comply with all applicable painting, marking, and/or lighting requirements in part 17 of this chapter. In the event of default by the owner, the station licensee will be responsible for ensuring that such requirements are met.

[79 FR 8326, Feb. 12, 2014]