

## § 74.802

## 47 CFR Ch. I (10–1–15 Edition)

low power auxiliary station devices means that the venue owner or operator uses 50 or more such devices for most events or productions.

*Low power auxiliary station.* An auxiliary station authorized and operated pursuant to the provisions set forth in this subpart. Devices authorized as low power auxiliary stations are intended to transmit over distances of approximately 100 meters for uses such as wireless microphones, cue and control communications, and synchronization of TV camera signals.

*Motion picture producer.* Motion picture producer refers to a person or organization engaged in the production or filming of motion pictures.

*Professional sound company.* Professional sound company refers to a person or organization that provides audio services that routinely use 50 or more low power auxiliary station devices, where the use of such devices is an integral part of major events or productions. Routinely using 50 or more low power auxiliary station devices means that the professional sound company uses 50 or more such devices for most events or productions.

*Television program producer.* Television program producer refers to a person or organization engaged in the production of television programs.

*Wireless assist video device.* An auxiliary station authorized and operated by motion picture and television program producers pursuant to the provi-

sions of this subpart. These stations are intended to transmit over distances of approximately 300 meters for use as an aid in composing camera shots on motion picture and television sets.

(Sec. 5, 48 Stat. 1068; 47 U.S.C. 155)

[42 FR 14729, Mar. 16, 1977, as amended at 43 FR 14662, Apr. 7, 1978; 51 FR 4603, Feb. 6, 1986; 51 FR 9966, Mar. 24, 1986; 54 FR 41842, Oct. 12, 1989; 68 FR 12772, Mar. 17, 2003; 79 FR 40689, July 14, 2014]

### § 74.802 Frequency assignment.

(a) Frequencies within the following bands may be assigned for use by low power auxiliary stations:

26.100–26.480 MHz  
54.000–72.000 MHz  
76.000–88.000 MHz  
161.625–161.775 MHz (except in Puerto Rico or the Virgin Islands)  
174.000–216.000 MHz  
450.000–451.000 MHz  
455.000–456.000 MHz  
470.000–488.000 MHz  
488.000–494.000 MHz (except Hawaii)  
494.000–608.000 MHz  
614.000–698.000 MHz  
944.000–952.000 MHz

(b)(1) Operations in the bands allocated for TV broadcasting are limited to locations at least 4 kilometers outside the protected contours of co-channel TV stations shown in the following table. These contours are calculated using the methodology in §73.684 of this chapter and the R-6602 curves contained in §73.699 of this chapter.

Type of station	Protected contour		
	Channel	Contour (dBU)	Propagation curve
Analog: Class A TV, LPTV, translator and booster	Low VHF (2–6)	47	F(50,50)
	High VHF (7–13) UHF (14–51)	56 64	F(50,50) F(50,50)
Digital: Full service TV, Class A TV, LPTV, translator and booster.	Low VHF (2–6)	28	F(50,90)
	High VHF (7–13) UHF (14–51)	36 41	F(50,90) F(50,90)

(2) Low power auxiliary stations may operate closer to co-channel TV broadcast stations than the distances specified in paragraph (b)(1) of this section provided that their operations are coordinated with TV broadcast stations that could be affected by the low power auxiliary station operation. Coordina-

tion must be completed prior to operation of the low power auxiliary station.

(c) Specific frequency operation is required when operating within the bands allocated for TV broadcasting.

(1) The frequency selection shall be offset from the upper or lower band

limits by 25 kHz or an integral multiple thereof.

(2) One or more adjacent 25 kHz segments within the assignable frequencies may be combined to form a channel whose maximum bandwidth shall not exceed 200 kHz.

(d) Low power auxiliary licensees will not be granted exclusive frequency assignments.

(e) *Clearing mechanisms for the 700 MHz Band.* This section sets forth provisions relating to the transition of low power auxiliary stations operating at 698–806 MHz (700 MHz band).

(1) Any low power auxiliary station that operates at frequencies in the 700 MHz band while transitioning its operations out of that band must not cause harmful interference and must accept interference from any commercial or public safety wireless licensees in the 700 MHz band.

(2) Any low power auxiliary station that operates at frequencies in the 700 MHz band will have until no later than June 12, 2010 to transition its operations completely out of the 700 MHz band, subject to the following. During this transition period, any commercial or public safety licensee in the 700 MHz band may choose one or both of the following voluntary methods to notify low power auxiliary stations:

(i) Any commercial or public safety licensee in the 700 MHz band may notify the Commission that it has initiated or will be initiating operations on specified frequencies in a particular market(s) in the 700 MHz band. The wireless operations initiated by the commercial or public safety 700 MHz licensees may include system testing or trials. Following receipt of the notification, the Commission will issue a public notice providing that operators of low power auxiliary stations, including wireless microphones, in the 700 MHz band in those market(s) will be required to cease operations within 60 days after the Commission's notice is released.

(ii) Any commercial or public safety licensee in the 700 MHz band may notify any low power auxiliary station users operating in the 700 MHz band that it has initiated or will be initiating operations on specified frequencies in the market in which the

low power auxiliary station is operating. The wireless operations initiated by the commercial or public safety 700 MHz licensees may include system testing or trials. Upon receipt of such notice, the low power auxiliary station in the affected market area must cease operation within 60 days.

(iii) In the event that both of these notice provisions in paragraphs (e)(2)(i) and (ii) of this section are used with respect to a particular low power auxiliary station, the low power auxiliary station will have to cease operations in the market(s) in accordance with whichever notice provides for earlier termination of its operations.

(3) Notwithstanding this 60 day notice requirement, any low power auxiliary station that causes harmful interference to any commercial or public safety 700 MHz licensee must cease operations immediately, consistent with the rules for secondary use.

(f) *Operations in 600 MHz band assigned to wireless licensees under part 27 of this chapter.* A low power auxiliary station that operates on frequencies in the 600 MHz band assigned to wireless licensees under part 27 of this chapter must cease operations on those frequencies no later than the end of the post-auction transition period as defined in § 27.4 of this chapter. During the post-auction transition period, low power auxiliary stations will operate on a secondary basis to licensees of part 27 of this chapter, *i.e.*, they must not cause to and must accept harmful interference from these licensees.

[52 FR 2535, Jan. 23, 1987, as amended at 68 FR 12772, Mar. 17, 2003; 75 FR 3638, Jan. 22, 2010; 79 FR 48545, Aug. 15, 2014]

#### **§ 74.803 Frequency selection to avoid interference.**

(a) Where two or more low power auxiliary licensees need to operate in the same area, the licensees shall endeavor to select frequencies or schedule operation in such manner as to avoid mutual interference. If a mutually satisfactory arrangement cannot be reached, the Commission shall be notified and it will specify the frequency or frequencies to be employed by each licensee.

(b) The selection of frequencies in the bands allocated for TV broadcasting for