

§ 1.21004 Winning bidder's obligation to apply for support

(a) *Timely and Sufficient Application.* A winning bidder has a binding obligation to apply for support by the applicable deadline. A winning bidder that fails to file an application by the applicable deadline or that for any reason is not subsequently authorized to receive support has defaulted on its bid.

(b) *Liability for Default Payment.* A winning bidder that defaults is liable for a default payment, which will be calculated by a method that will be established as provided in a public notice prior to competitive bidding. If the default payment is determined as a percentage of the defaulted bid amount, the default payment will not exceed twenty percent of the amount of the defaulted bid amount.

(c) *Additional Liabilities.* A winning bidder that defaults, in addition to being liable for a default payment, shall be subject to such measures as the Commission may provide, including but not limited to disqualification from future competitive bidding pursuant to this subpart AA, competitive bidding for universal service support.

Subpart BB—Disturbance of AM Broadcast Station Antenna Patterns

SOURCE: 78 FR 66295, Nov. 5, 2013, as amended at 78 FR 70499, Nov. 26, 2013, unless otherwise noted.

§ 1.30000 Purpose.

This rule part protects the operations of AM broadcast stations from nearby tower construction that may distort the AM antenna patterns. All parties holding or applying for Commission authorizations that propose to construct or make a significant modification to an antenna tower or support structure in the immediate vicinity of an AM antenna, or propose to install an antenna on an AM tower, are responsible for completing the analysis and notice process described in this subpart, and for taking any measures necessary to correct disturbances of the AM radiation pattern, if such disturbances occur as a result of the tower construction or modification or

as a result of the installation of an antenna on an AM tower. In the event these processes are not completed before an antenna structure is constructed, any holder of or applicant for a Commission authorization is responsible for completing these processes before locating or proposing to locate an antenna on the structure, as described in this subpart.

§ 1.30001 Definitions.

For purposes of this subpart:

(a) *Wavelength at the AM frequency.* In this subpart, critical distances from an AM station are described in terms of the AM wavelength. The AM wavelength, expressed in meters, is computed as follows:

$(300 \text{ meters}) / (\text{AM frequency in megahertz}) = \text{AM wavelength in meters.}$

For example, at the AM frequency of 1000 kHz, or 1 MHz, the wavelength is $(300 / 1 \text{ MHz}) = 300 \text{ meters.}$

(b) *Electrical degrees at the AM frequency.* This term describes the height of a proposed tower as a function of the frequency of a nearby AM station. To compute tower height in electrical degrees, first determine the AM wavelength in meters as described in paragraph (a) of this section. Tower height in electrical degrees is computed as follows: $(\text{Tower height in meters}) / (\text{AM wavelength in meters}) \times 360 \text{ degrees} = \text{Tower height in electrical degrees.}$ For example, if the AM frequency is 1000 kHz, then the wavelength is 300 meters, per paragraph (a) of this section. A nearby tower 75 meters tall is therefore $[75 / 300] \times 360 = 90 \text{ electrical degrees}$ tall at the AM frequency.

(c) *Proponent.* The term proponent refers in this section to the party proposing tower construction or significant modification of an existing tower or proposing installation of an antenna on an AM tower.

(d) *Distance from the AM station.* The distance shall be calculated from the tower coordinates in the case of a non-directional AM station, or from the array center coordinates given in CDBS or any successor database for a directional AM station.