Federal Communications Commission

objectivity or impartiality of the testing laboratory's testing process and decisions.

(iii) Subsequent to the successful testing of its initial M-UDCP. a manufacturer or importer is not required to have other M-UDCP models tested at a qualified test facility for compliance with M-UDCP-PICS-I04-080225, "Uni-Directional Cable Product Supporting M-Card: Multiple Profiles; Conformance Checklist: PICS," February 25, 2008 (incorporated by reference, see §15.38) unless the first model tested was not a television, in which event the first television shall be tested as provided in §15.123(c)(5)(i). The manufacturer or importer shall ensure that all subsequent models of M-UDCPs comply with M-UDCP-PICS-I04-080225, "Uni-Directional Cable Product Supporting M-Card: Multiple Profiles; Conformance Checklist: PICS," February 25, 2008 (incorporated by reference, see §15.38) and all other applicable rules and standards. The manufacturer or importer shall maintain records indicating such compliance in accordance with the verification procedure requirements in part 2, subpart J of this chapter. For each M-UDCP model, the manufacturer or importer shall further submit documentation verifying compliance with M-UDCP-PICS-I04-080225, "Uni-Directional Cable Product Supporting M-Card: Multiple Profiles; Conformance Checklist: PICS," Februarv 25, 2008 (incorporated by reference, see §15.38) to the qualified test facility.

(iv) M-UDCPs must be in compliance with M-UDCP-PICS-I04-080225, "Uni-Directional Cable Product Supporting M-Card: Multiple Profiles; Conformance Checklist: PICS," February 25, 2008 (incorporated by reference, see §15.38) in accordance with the procedures set forth in TP-ATP-M-UDCP-I05-20080304, "Uni-Directional Digital Cable Products Supporting M-Card; M-UDCP Device Acceptance Test Plan," March 4, 2008 (incorporated by reference, see §15.38) or an equivalent test procedure that produces identical pass/ fail test results. In the event of any dispute over the applicable results under an equivalent test procedure, the results under TP-ATP-M-UDCP-I05-20080304, "Uni-Directional Digital Cable Products Supporting M-Card; M-UDCP

Device Acceptance Test Plan," March 4, 2008 (incorporated by reference, see §15.38) shall govern.

(d) Manufacturers and importers shall provide in appropriate post-sale material that describes the features and functionality of the product, such as the owner's guide, the following language: "This digital television is capable of receiving analog basic, digital basic and digital premium cable television programming by direct connection to a cable system providing such programming. A security card provided by your cable operator is required to view encrypted digital programming. Certain advanced and interactive digital cable services such as video-on-demand, a cable operator's enhanced program guide and data-enhanced television services may require the use of a set-top box. For more information call your local cable operator."

[68 FR 66733, Nov. 28, 2003, as amended at 76 FR 40277, July 8, 2011; 77 FR 4914, Feb. 1, 2012]

Subpart C—Intentional Radiators

§15.201 Equipment authorization requirement.

(a) Intentional radiators operated as carrier current systems, devices operated under the provisions of §§15.211, 15.213, and 15.221, and devices operating below 490 kHz in which all emissions are at least 40 dB below the limits in §15.209 shall be verified pursuant to the procedures in Subpart J of part 2 of this chapter prior to marketing.

(b) Except as otherwise exempted in paragraph (c) of this section and in §15.23 of this part, all intentional radiators operating under the provisions of this part shall be certificated by the Commission pursuant to the procedures in subpart J of part 2 of this chapter prior to marketing.

(c) For devices such as perimeter protection systems which, in accordance with §15.31(d), are required to be measured at the installation site, each application for certification must be accompanied by a statement indicating that the system has been tested at three installations and found to comply at each installation. Until such time as certification is granted, a given installation of a system that was measured for the submission for certification will be considered to be in compliance with the provisions of this chapter, including the marketing regulations in subpart I of part 2 of this chapter, if tests at that installation show the system to be in compliance with the relevant technical requirements. Similarly, where measurements must be performed on site for equipment subject to verification, a given installation that has been verified to demonstrate compliance with the applicable standards will be considered to be in compliance with the provisions of this chapter, including the marketing regulations in subpart I of part 2 of this chapter.

(d) For perimeter protection systems operating in the frequency bands allocated to television broadcast stations operating under part 73 of this chapter, the holder of the grant of certification must test each installation prior to initiation of normal operation to verify compliance with the technical standards and must maintain a list of all installations and records of measurements. For perimeter protection systems operating outside of the frequency bands allocated to television broadcast stations, upon receipt of a grant of certification, further testing of the same or similar type of system or installation is not required.

[54 FR 17714, Apr. 25, 1989, as amended at 68 FR 68546, Dec. 9, 2003]

§15.202 Certified operating frequency range.

Client devices that operate in a master/client network may be certified if they have the capability of operating outside permissible part 15 frequency bands, provided they operate on only permissible part 15 frequencies under the control of the master device with which they communicate. Master devices marketed within the United States must be limited to operation on permissible part 15 frequencies. Client devices that can also act as master devices must meet the requirements of a master device. For the purposes of this section, a master device is defined as a device operating in a mode in which it has the capability to transmit without receiving an enabling signal. In this mode it is able to select a channel and

47 CFR Ch. I (10–1–16 Edition)

initiate a network by sending enabling signals to other devices. A network always has at least one device operating in master mode. A client device is defined as a device operating in a mode in which the transmissions of the device are under control of the master. A device in client mode is not able to initiate a network.

[70 FR 23040, May 4, 2005]

§15.203 Antenna requirement.

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

[54 FR 17714, Apr. 25, 1989, as amended at 55 FR 28762, July 13, 1990]

§15.204 External radio frequency power amplifiers and antenna modifications.

(a) Except as otherwise described in paragraphs (b) and (d) of this section, no person shall use, manufacture, sell or lease, offer for sale or lease (including advertising for sale or lease), or import, ship, or distribute for the purpose of selling or leasing, any external radio frequency power amplifier or amplifier kit intended for use with a part 15 intentional radiator.