

§ 22.983

alerts them to possible interference; and

(3) Rapidly identify the source if interference is encountered when the cell is activated.

[69 FR 67834, Nov. 22, 2004]

§ 22.983 Field strength limit.

(a) Subject to paragraphs (b) and (c) of this section, a licensee's predicted or measured median field strength limit must not exceed 40 dBμV/m at any given point along the Cellular Geographic Service Area (CGSA) boundary of a neighboring licensee on the same channel block, unless the affected licensee of the neighboring CGSA on the same channel block agrees to a different field strength. This also applies to CGSAs partitioned pursuant to § 22.948.

(b) *Gulf of Mexico Service Area.* Notwithstanding the field strength limit provision set forth in paragraph (a) of this section, licensees in or adjacent to the Gulf of Mexico Exclusive Zone are subject to § 22.912(c) regarding service area boundary extensions. See § 22.912(c).

(c) Cellular licensees shall be subject to all applicable provisions and requirements of treaties and other international agreements between the United States government and the governments of Canada and Mexico, notwithstanding paragraphs (a) and (b) of this section.

[79 FR 72153, Dec. 5, 2014]

Subpart I—Offshore Radiotelephone Service

§ 22.1001 Scope.

The rules in this subpart govern the licensing and operation of offshore radiotelephone stations. The licensing and operation of these stations and systems is also subject to rules elsewhere in this part that apply generally to the public mobile services. However, in case of conflict, the rules in this subpart govern.

§ 22.1003 Eligibility.

Any eligible entity (see § 22.7) may apply for central station license(s) and/

47 CFR Ch. I (10–1–16 Edition)

or offshore subscriber licenses under this subpart.

[70 FR 19312, Apr. 13, 2005]

§ 22.1005 Priority of service.

Facilities in the Offshore Radiotelephone Service are intended primarily for rendition of public message service between offshore subscriber and central stations. However, they may also be used to render private leased line communication service, provided that such usage does not reduce or impair the extent or quality of communication service which would be available, in the absence of private leased line service, to the general public receiving or subsequently requesting public message service from an offshore central station.

§ 22.1007 Channels for offshore radiotelephone systems.

The channels listed in this section are allocated for paired assignment to transmitters located in the specified geographical zones that provide offshore radiotelephone service. All channels have a bandwidth of 20 kHz and are designated by their center frequencies in MegaHertz.

(a) *Zone A—Southern Louisiana.* The geographical area in Zone A is bounded as follows:

From longitude W.87°45' on the East to longitude W.94°00' on the West and from the 4.8 kilometer (3 mile) limit along the Gulf of Mexico shoreline on the North to the limit of the Outer Continental Shelf on the South.

(1) These channels may be assigned for use by offshore central (base/fixed) or subscriber stations (fixed, temporary fixed, surface and/or airborne mobile) as indicated, for voice-grade general communications:

Central	Subscriber	Central	Subscriber
488.025	491.025	488.225	491.225
488.050	491.050	488.250	491.250
488.075	491.075	488.275	491.275
488.100	491.100	488.300	491.300
488.125	491.125	488.325	491.325
488.150	491.150	488.350	491.350
488.175	491.175	488.375	491.375
488.200	491.200	488.400	491.400

(2) These channels may be assigned for use by offshore central (base/fixed) or subscriber stations (fixed, temporary fixed, surface and/or airborne

Federal Communications Commission

§ 22.1007

mobile) as indicated, for voice-grade general communications and private line service:

Central	Subscriber	Central	Subscriber
488.425	491.425	488.575	491.575
488.450	491.450	488.600	491.600
488.475	491.475	488.625	491.625
488.500	491.500	488.650	491.650
488.525	491.525	488.675	491.675
488.550	491.550	488.700	491.700

(3) These channels may be assigned for use by relay stations in systems where it would be impractical to provide offshore radiotelephone service without the use of relay stations.

Central	Subscriber	Central	Subscriber
488.725	491.725	488.775	491.775
488.750	491.750	488.800	491.800

(4) These channels may be assigned for use by offshore central (base/fixed) or subscriber stations (fixed, temporary fixed, surface and/or airborne mobile) as indicated, for emergency communications involving protection of life and property.

Central	Subscriber	Central	Subscriber
488.825	491.825	488.875	491.875
488.850	491.850	488.900	491.900

(5) These channels may be assigned for use by offshore central (base/fixed) or subscriber stations (fixed, temporary fixed, surface and/or airborne mobile) as indicated, for emergency auto alarm and voice transmission pertaining to emergency conditions only.

Central	Subscriber
488.950	491.950

(6) These channels may be assigned for use by offshore central (base/fixed) or subscriber stations (fixed, temporary fixed, surface and/or airborne mobile) as indicated, for emergency shut-off remote control telemetry, environmental data acquisition and disseminations, or facsimile transmissions.

Central	Subscriber	Central	Subscriber
489.000	492.000	489.200	492.200
489.025	492.025	489.225	492.225
489.050	492.050	489.250	492.250
489.075	492.075	489.275	492.275
489.100	492.100	489.300	492.300
489.125	492.125	489.325	492.325

Central	Subscriber	Central	Subscriber
489.150	492.150	489.350	492.350
489.175	492.175	489.375	492.375

(7) These channels may be assigned for use by offshore central (base/fixed) or subscriber stations (fixed, temporary fixed, surface and/or airborne mobile) as indicated, for private line service:

Central	Subscriber	Central	Subscriber
489.400	492.400	489.725	492.725
489.425	492.425	489.750	492.750
489.450	492.450	489.775	492.775
489.475	492.475	489.800	492.800
489.500	492.500	489.825	492.825
489.525	492.525	489.850	492.850
489.550	492.550	489.875	492.875
489.575	492.575	489.900	492.900
489.600	492.600	489.925	492.925
489.625	492.625	489.950	492.950
489.650	492.650	489.975	492.975
489.675	492.675	490.000	493.000
489.700	492.700		

(8) *Interstitial channels.* Interstitial channels are those with center frequencies offset by ± 12.5 kHz from the listed center frequencies. The FCC may assign interstitial channels to offshore stations in Zone A subject to the following conditions:

- Offshore stations transmitting on interstitial channels must be located east of W.92° longitude.
- Operations on interstitial channels are considered to be secondary to operations on channels with the listed center frequencies.
- Offshore stations operating on interstitial channels must be used only for voice grade general communications or to provide for private line service.

NOTE TO PARAGRAPH (a) OF § 22.1007: These channels are contained in UHF TV Channel 17.

(b) *Zone B—Southern Louisiana—Texas.* (1) The geographical area in Zone B is bounded as follows:

From longitude W.87°45' on the East to longitude W.95°00' on the West and from the 4.8 kilometer (3 mile) limit along the Gulf of Mexico shoreline on the North to the limit of the Outer Continental Shelf on the South.

(2) These channels may be assigned for use by offshore central (base/fixed) or subscriber stations (fixed, temporary fixed, surface and/or airborne mobile) as indicated, for voice-grade

§ 22.1007

47 CFR Ch. I (10–1–16 Edition)

general communications and private line service:

Central	Subscriber	Central	Subscriber
485.025	482.025	486.025	483.025
485.050	482.050	486.050	483.050
485.075	482.075	486.075	483.075
485.100	482.100	486.100	483.100
485.125	482.125	486.125	483.125
485.150	482.150	486.150	483.150
485.175	482.175	486.175	483.175
485.200	482.200	486.200	483.200
485.225	482.225	486.225	483.225
485.250	482.250	486.250	483.250
485.275	482.275	486.275	483.275
485.300	482.300	486.300	483.300
485.325	482.325	486.325	483.325
485.350	482.350	486.350	483.350
485.375	482.375	486.375	483.375
485.400	482.400	486.400	483.400
485.425	482.425	486.425	483.425
485.450	482.450	486.450	483.450
485.475	482.475	486.475	483.475
485.500	482.500	486.500	483.500
485.525	482.525	486.525	483.525
485.550	482.550	486.550	483.550
485.575	482.575	486.575	483.575
485.600	482.600	486.600	483.600
485.625	482.625	486.625	483.625
485.650	482.650	486.650	483.650
485.675	482.675	486.675	483.675
485.700	482.700	486.700	483.700
485.725	482.725	486.725	483.725
485.750	482.750	486.750	483.750
485.775	482.775	486.775	483.775
485.800	482.800	486.800	483.800
485.825	482.825	486.825	483.825
485.850	482.850	486.850	483.850
485.875	482.875	486.875	483.875
485.900	482.900	486.900	483.900
485.925	482.925	486.925	483.925
485.950	482.950	486.950	483.950
485.975	482.975	486.975	483.975
486.000	483.000	487.050	480.050

NOTE TO PARAGRAPH (b) OF § 22.1007: These channels are contained in UHF TV Channel 16.

(c) *Zone C—Southern Texas.* The geographical area in Zone C is bounded as follows:

Longitude W.94°00' on the East, the 4.8 kilometer (3 mile) limit on the North and West, a 282 kilometer (175 mile) radius from the reference point at Linares, N.L., Mexico on the Southwest, latitude N.26°00' on the South, and the limits of the outer continental shelf on the Southeast.

(1) These channels may be assigned for use by offshore central (base/fixed) or subscriber stations (fixed, temporary fixed, surface and/or airborne mobile) as indicated, for emergency auto alarm and voice transmission pertaining to emergency conditions only.

Central	Subscriber
476.950	479.950

(2) These channels may be assigned for use by offshore central (base/fixed) or subscriber stations (fixed, temporary fixed, surface and/or airborne mobile) as indicated, for voice-grade general communications and private line service:

476.025	479.025
476.050	479.050
476.075	479.075
476.100	479.100
476.125	479.125
476.150	479.150
476.175	479.175
476.200	479.200
476.225	479.225
476.250	479.250
476.275	479.275
476.300	479.300
476.325	479.325
476.350	479.350
476.375	479.375
476.400	479.400
476.425	479.425
476.450	479.450
476.475	479.475
476.500	479.500
476.525	479.525
476.550	479.550
476.575	479.575
476.600	479.600
476.625	479.625
476.650	479.650
476.675	479.675
476.700	479.700
476.725	479.725
476.750	479.750
476.775	479.775
476.800	479.800
476.825	479.825
476.850	479.850
476.875	479.875
476.900	479.900
477.000	480.000
477.025	480.025
477.075	480.075
477.100	480.100
477.125	480.125
477.150	480.150
477.175	480.175
477.200	480.200
477.225	480.225
477.250	480.250
477.275	480.275
477.300	480.300
477.325	480.325
477.350	480.350
477.375	480.375
477.400	480.400
477.425	480.425
477.450	480.450
477.475	480.475
477.500	480.500
477.525	480.525
477.550	480.550
477.575	480.575

Federal Communications Commission

§ 22.1013

477.600	480.600
477.625	480.625
477.650	480.650
477.675	480.675
477.700	480.700
477.725	480.725
477.750	480.750
477.775	480.775
477.800	480.800
477.825	480.825
477.850	480.850
477.875	480.875
477.900	480.900
477.925	480.925
477.950	480.950
477.975	480.975

[59 FR 59507, Nov. 17, 1994; 60 FR 9891, Feb. 22, 1995]

§ 22.1009 Transmitter locations.

The rules in this section establish limitations on the locations from which stations in the Offshore Radiotelephone Service may transmit.

(a) *All stations.* Offshore stations must not transmit from locations outside the boundaries of the appropriate zones specified in § 22.1007. Offshore stations must not transmit from locations within 241 kilometers (150 miles) of any full-service television station that transmits on the TV channel containing the channel on which the offshore station transmits.

(b) *Airborne subscriber stations.* Airborne subscriber stations must not transmit from altitudes exceeding 305 meters (1000 feet) above mean sea level. Airborne mobile stations in Zone A must not transmit from locations within 129 kilometers (80 miles) of Lake Charles, Louisiana. Airborne mobile stations in Zone B must not transmit from locations within 129 kilometers (80 miles) of Lafayette, Louisiana. Airborne mobile stations in Zone C must not transmit from locations within 129 kilometers (80 miles) of Corpus Christi or locations within 129 kilometers (80 miles) of Houston, Texas.

§ 22.1011 Antenna height limitations.

The antenna height of offshore stations must not exceed 61 meters (200 feet) above mean sea level. The antenna height of offshore surface mobile stations must not exceed 10 meters (30 feet) above the waterline.

§ 22.1013 Effective radiated power limitations.

The effective radiated power (ERP) of transmitters in the Offshore Radiotelephone Service must not exceed the limits in this section.

(a) *Maximum power.* The ERP of transmitters in this service must not exceed 1000 Watts under any circumstances.

(b) *Mobile transmitters.* The ERP of mobile transmitters must not exceed 100 Watts. The ERP of mobile transmitters, when located within 32 kilometers (20 miles) of the 4.8 kilometer (3 mile) limit, must not exceed 25 Watts. The ERP of airborne mobile stations must not exceed 1 Watt.

(c) *Protection for TV Reception.* The ERP limitations in this paragraph are intended to reduce the likelihood that interference to television reception from offshore radiotelephone operations will occur.

(1) *Co-channel protection.* The ERP of offshore stations must not exceed the limits in Table I-1 of this section. The limits depend upon the height above mean sea level of the offshore transmitting antenna and the distance between the antenna location of the offshore transmitter and the antenna location of the main transmitter of the nearest full-service television station that transmits on the TV channel containing the channel on which the offshore station transmits.

(2) *Adjacent channel protection.* The ERP of offshore stations located within 128.8 kilometers (80 miles) of the main transmitter antenna of a full service TV station that transmits on a TV channel adjacent to the TV channel which contains the channel on which the offshore station transmits must not exceed the limits in the Table I-2 of § 22.1015. The limits depend upon the height above mean sea level of the offshore transmitting antenna and the distance between the location of the offshore transmitter and the 4.8 kilometer (3 mile) limit.

TABLE I-1—MAXIMUM ERP (WATTS)

Distance	30 meters (100 feet)	45 meters (150 feet)	61 meters (200 feet)
338 km (210 mi)	1000	1000	1000