

license modification to deploy and operate technically identical replacement satellites in an authorized orbit within the term of the system authorization. However, the licensee must notify the Commission of the intended launch at least 30 days in advance and certify that its operation of the additional space station(s) will not increase the number of space stations providing service above the maximum number specified in the license.

[56 FR 24016, May 28, 1991, as amended at 61 FR 4366, Feb. 6, 1996; 61 FR 9951, Mar. 12, 1996; 61 FR 55582, Oct. 28, 1996; 62 FR 5927, Feb. 10, 1997; 62 FR 64172, Dec. 4, 1997; 68 FR 51502, Aug. 27, 2003; 69 FR 47794, Aug. 6, 2004; 70 FR 32253, June 2, 2005; 77 FR 3954, Jan. 26, 2012; 78 FR 8421, Feb. 6, 2013; 79 FR 8314, Feb. 12, 2014; 79 FR 27503, May 14, 2014; 81 FR 55326, Aug. 18, 2016]

EFFECTIVE DATE NOTE: At 79 FR 27503, May 14, 2014, in § 25.113, in the second sentence in paragraph (b), “1.5/1.6 GHz, 1.6/2.4 GHz, or 2 GHz Mobile-Satellite Service” was corrected to read “1.5/1.6 GHz or 1.6/2.4 GHz Mobile-Satellite Service”. This amendment contains information collection and record-keeping requirements and will not become effective until approval has been given by the Office of Management and Budget.

**§ 25.114 Applications for space station authorizations.**

(a)(1) A license application filed pursuant to § 25.110(b)(2) for a GSO space station or NGSO space station or space-station constellation must comprise a comprehensive proposal and must be submitted on FCC Form 312, Main Form and Schedule S, with attached exhibits required by paragraph (d) of this section.

(2) An application for blanket authority for an NGSO constellation of space stations that are not all technically identical must provide the information required by paragraphs (c) and (d) of this section for each type of station in the constellation.

(3) For an application filed pursuant to the two-step procedure in § 25.110(b)(3), the filing pursuant to § 25.110(b)(3)(iii) must be submitted on FCC Form 312, Main Form and Schedule S, with attached exhibits as required by paragraph (d) of this section, and must constitute a comprehensive proposal.

(b) Each application for a new or modified space station authorization must contain the formal waiver required by 47 U.S.C. 304.

(c) The following information shall be filed on FCC Form 312, Main Form and Schedule S:

(1) Name, address, and telephone number of the applicant;

(2) Name, address, and telephone number of the person(s), including counsel, to whom inquiries or correspondence should be directed;

(3) Type of authorization requested (*e.g.*, launch authority, station license, modification of authorization);

(4)(i) For each space station transmitting and receiving antenna beam (including telemetry and tracking beams but not command beams), specify channel center frequencies and bandwidths and polarization plan. For command beams, specify each of the center frequencies within a 5 MHz range or a range of 2 percent of the assigned bandwidth, whichever is smaller, and the polarization plan. If the space station can vary channel bandwidth in a particular frequency band with on-board processing, specify only the range of frequencies in that band over which the beam can operate and the polarization plan.

(ii) Specify maximum EIRP and maximum EIRP density for each space station transmitting antenna beam. If the satellite uses shapeable antenna beams, as defined in § 25.103, specify instead maximum possible EIRP and maximum possible EIRP density within each shapeable beam’s proposed coverage area. Provide this information for each frequency band in which the transmitting antenna would operate. For bands below 15 GHz, specify EIRP density in dBW/4 kHz; for bands at and above 15 GHz, specify EIRP density in dBW/MHz. If the EIRP density varies over time, specify the maximum possible EIRP density.

(iii)–(iv) [Reserved]

(v) For each space station receiving beam other than command beams, specify the gain-to-temperature ratio at beam peak. For receiving beams fed into transponders, also specify the minimum and maximum saturation flux density at beam peak. If the satellite uses shapeable beams, specify the

minimum and maximum gain-to-temperature ratio within each shapeable beam's proposed coverage area, and for shapeable receiving beams fed into transponders, specify the minimum and maximum saturation power flux density within the 0 dB relative antenna gain isoline. Provide this information for each frequency band in which the receiving beam can operate. For command beams, specify the beam peak flux density at the command threshold;

(vi)(A) For space stations in geostationary orbit, specify predicted space station antenna gain contour(s) for each transmit and receive antenna beam, except for beams where the contour at 8 dB below peak falls entirely beyond the edge of the visible Earth. These contour(s) should be plotted on an area map at 2 dB intervals down to 10 dB below the peak gain and at 5 dB intervals between 10 dB and 20 dB below the peak gain. Applicants must present this information in a GIMS-readable format.

(B) For space stations in non-geostationary orbits, specify for each unique orbital plane the predicted antenna gain contour(s) for each transmit and receive antenna beam for one space station if all space stations are identical in the constellation. If individual space stations in the constellation have different antenna beam configurations, specify the predicted antenna gain contours for each transmit and receive beam for each space station type and orbit or orbital plane requested. The contours should be plotted on an area map with the beam depicted on the surface of the earth with the space stations' peak antenna gain pointed at nadir to a latitude and longitude within the proposed service area. The contour(s) should be plotted at 2 dB intervals down to 10 dB below the peak gain and at 5 dB intervals between 10 dB and 20 dB below the peak gain. For inter-satellite links, specify the peak antenna gain and 3 dB beamwidth.

(C) For space stations with shapeable antenna beams, specify the contours, as defined in paragraph (c)(4)(vi)(A) or (B) of this section, for the transmitting beam configuration that results in the highest EIRP density for the beams listed in paragraph (c)(4)(ii) of this section and for the receiving beam con-

figuration with the smallest gain-to-temperature ratio and the highest required saturation power flux density for the beams listed in paragraph (c)(4)(v) of this section. If the shapeable beams are also steerable, include the contours that would result from moving the beam peak around the limit of the effective beam peak area and the 0 dB relative antenna gain isoline. The proposed maximum coverage area must be clearly specified.

(D) For a space station with steerable beams that are not shapeable, specify the applicable contours, as defined in paragraph (c)(4)(vi)(A) or (c)(4)(vi)(B) of this section, with a description of a proposed coverage area for each steerable beam or provide the contour information described in paragraph (c)(4)(vi)(C) of this section for each steerable beam.

(vii) For geostationary satellites with large numbers of identical fixed spot beams, other than DBS satellites, applicants may, as an alternative to submitting the information described in paragraph (c)(4)(vi) of this section with respect to these beams, provide the predicted antenna gain contours for one transmit and receive antenna beam, together with one of the following:

(A) An area map showing all of the spot beams depicted on the surface of the Earth;

(B) A table identifying the maximum antenna gain point(s) in latitude and longitude to the nearest 0.1 degree; or

(C) A map of the isolines formed by combining all of the spot beams into one or more composite beams. For non-geostationary satellites with large numbers of identical fixed beams on each satellite, applicants may, as an alternative to submitting the information described in paragraph (c)(4)(vi) of this section with respect to those beams, specify the predicted antenna gain contours for one transmit and receive beam pointed to nadir, together with an area map showing all of the spot beams depicted on the surface of the earth with the satellites' peak antenna gain pointed to a selected latitude and longitude within the service area.

(5) For space stations in geostationary orbit:

**§ 25.114**

**47 CFR Ch. I (10–1–16 Edition)**

- (i) Orbital location requested,
- (ii) [Reserved]
- (iii) East-west station-keeping range,
- (iv) North-south station-keeping range, and
- (v) Accuracy to which antenna axis attitude will be maintained;
- (6) For space stations in non-geostationary orbits:
  - (i) The number of orbital planes and the number of space stations in each plane,
  - (ii) The inclination of the orbital plane(s),
  - (iii) The orbital period,
  - (iv) The apogee,
  - (v) The perigee,
  - (vi) The argument(s) of perigee,
  - (vii) Active service arc(s),
  - (viii) Right ascension of the ascending node(s), and
  - (ix) For each satellite in each orbital plane, the initial phase angle at the reference time;
- (7) The frequency bands, types of service, and coverage areas;
- (8) Calculated maximum power flux density levels within each coverage area and energy dispersal bandwidths, if any, needed for compliance with § 25.208, for the angles of arrival specified in the applicable paragraph(s) of § 25.208;
- (9) [Reserved]
- (10) Estimated operational lifetime;
- (11) Whether the space station is to be operated on a common carrier basis;
- (12) [Reserved]
- (13) And the polarization information necessary to determine compliance with § 25.210(i).
- (d) The following information in narrative form shall be contained in each application:
  - (1) Overall description of system facilities, operations and services and explanation of how uplink frequency bands would be connected to downlink frequency bands;
  - (2)–(5) [Reserved]
  - (6) Public interest considerations in support of grant;
  - (7) Applicants for authorizations for space stations in the Fixed-Satellite Service must also include the information specified in § 25.140(a). Applicants for authorizations for space stations in the 17/24 GHz Broadcasting-Satellite Service must also include the informa-

- tion specified in § 25.140(b)(3), (b)(4), (b)(5), or (b)(6);
- (8) Applications for authorizations in the Mobile-Satellite Service in the 1545–1559/1646.5–1660.5 MHz frequency bands shall also provide all information necessary to comply with the policies and procedures set forth in Rules and Policies Pertaining to the Use of Radio Frequencies in a Land Mobile Satellite Service, 2 FCC Rcd 485 (1987) (Available at address in § 0.445 of this chapter.);
- (9) Applications to license multiple space station systems in the non-voice, non-geostationary mobile-satellite service under blanket operating authority shall also provide all information specified in § 25.142; and
- (10) An application for space station authorization in the 1.6/2.4 GHz or 2 GHz Mobile-Satellite Service must include information required by § 25.143(b);
- (11) Applications for space stations in the Direct Broadcast Satellite Service must include a clear and detailed statement of whether the space station is to be operated on a broadcast or non-broadcast basis;
- (12) Applications for authorizations in the non-geostationary orbit Fixed-Satellite Service in the 10.7–14.5 GHz bands must also provide all information specified in § 25.146.
- (13) For satellite applications in the Direct Broadcast Satellite Service, if the proposed system’s technical characteristics differ from those specified in the Appendix 30 BSS Plans, the Appendix 30A feeder link Plans, Annex 5 to Appendix 30 or Annex 3 to Appendix 30A of the ITU Radio Regulations, each applicant must provide:
  - (i) The information requested in Appendix 4 of the ITU Radio Regulations. Further, applicants must provide sufficient technical showing that the proposed system could operate satisfactorily if all assignments in the BSS and feeder link Plans were implemented.
  - (ii) Analyses of the proposed system with respect to the limits in Annex 1 to Appendices 30 and 30A of the ITU Radio Regulations.
- (14) A description of the design and operational strategies that will be used

to mitigate orbital debris, including the following information:

(i) A statement that the space station operator has assessed and limited the amount of debris released in a planned manner during normal operations, and has assessed and limited the probability of the space station becoming a source of debris by collisions with small debris or meteoroids that could cause loss of control and prevent post-mission disposal;

(ii) A statement that the space station operator has assessed and limited the probability of accidental explosions during and after completion of mission operations. This statement must include a demonstration that debris generation will not result from the conversion of energy sources on board the spacecraft into energy that fragments the spacecraft. Energy sources include chemical, pressure, and kinetic energy. This demonstration should address whether stored energy will be removed at the spacecraft's end of life, by depleting residual fuel and leaving all fuel line valves open, venting any pressurized system, leaving all batteries in a permanent discharge state, and removing any remaining source of stored energy, or through other equivalent procedures specifically disclosed in the application;

(iii) A statement that the space station operator has assessed and limited the probability of the space station becoming a source of debris by collisions with large debris or other operational space stations. Where a space station will be launched into a low-Earth orbit that is identical, or very similar, to an orbit used by other space stations, the statement must include an analysis of the potential risk of collision and a description of what measures the space station operator plans to take to avoid in-orbit collisions. If the space station operator is relying on coordination with another system, the statement must indicate what steps have been taken to contact, and ascertain the likelihood of successful coordination of physical operations with, the other system. The statement must disclose the accuracy—if any—with which orbital parameters of non-geostationary satellite orbit space stations will be maintained, including apogee, perigee,

inclination, and the right ascension of the ascending node(s). In the event that a system is not able to maintain orbital tolerances, *i.e.*, it lacks a propulsion system for orbital maintenance, that fact should be included in the debris mitigation disclosure. Such systems must also indicate the anticipated evolution over time of the orbit of the proposed satellite or satellites. Where a space station requests the assignment of a geostationary-Earth orbit location, it must assess whether there are any known satellites located at, or reasonably expected to be located at, the requested orbital location, or assigned in the vicinity of that location, such that the station keeping volumes of the respective satellites might overlap. If so, the statement must include a statement as to the identities of those parties and the measures that will be taken to prevent collisions;

(iv) A statement detailing the post-mission disposal plans for the space station at end of life, including the quantity of fuel—if any—that will be reserved for post-mission disposal maneuvers. For geostationary-Earth orbit space stations, the statement must disclose the altitude selected for a post-mission disposal orbit and the calculations that are used in deriving the disposal altitude. The statement must also include a casualty risk assessment if planned post-mission disposal involves atmospheric re-entry of the space station. In general, an assessment should include an estimate as to whether portions of the spacecraft will survive re-entry and reach the surface of the Earth, as well as an estimate of the resulting probability of human casualty. Applicants for space stations to be used only for commercial remote sensing may, in lieu of submitting detailed post-mission disposal plans to the Commission, certify that they have submitted such plans to the National Oceanic and Atmospheric Administration for review.

(v) For non-U.S.-licensed space stations, the requirement to describe the design and operational strategies to minimize orbital debris risk can be satisfied by demonstrating that debris mitigation plans for the space station(s) for which U.S. market access is

## § 25.115

## 47 CFR Ch. I (10–1–16 Edition)

requested are subject to direct and effective regulatory oversight by the national licensing authority.

(15) Each applicant for a space station license in the 17/24 GHz broadcasting-satellite service shall include the following information as an attachment to its application:

(i) If the applicant proposes to operate in the 17.3–17.7 GHz frequency band, a demonstration that the proposed space station will comply with the power flux density limits in § 25.208(w) unless the applicant provides a certification under paragraph (d)(15)(ii) of this section.

(ii) In cases where the proposed space station will not comply with the power flux density limits set forth in § 25.208(w) of this part, the applicant will be required to provide a certification that all potentially affected parties acknowledge and do not object to the use of the applicant's higher power flux densities. The affected parties with whom the applicant must coordinate are those GSO 17/24 GHz BSS satellite networks located up to  $\pm 6^\circ$  away for excesses of up to 3 dB above the power flux-density levels specified in § 25.208(w) of this part, and up to  $\pm 10^\circ$  away greater for excesses greater than 3 dB above those levels.

(iii) If the applicant proposes to provide international service in the 17.7–17.8 GHz frequency band, a certification that the proposed space station will comply with the power flux density limits in § 25.208(c).

(iv) Any information required by § 25.264(a)(6), 25.264(b)(4), or 25.264(d).

(16) In addition to the requirements of paragraph (d)(15) of this section, each applicant for a license to operate a 17/24 GHz BSS space station that will be used to provide video programming directly to consumers in the United States, that will not meet the requirements of § 25.225 of this part, must include as an attachment to its application a technical analysis demonstrating that providing video programming service to consumers in Alaska and Hawaii that is comparable to the video programming service provided to consumers in the 48 contiguous United States (CONUS) is not feasible as a technical matter or that, while technically feasible, such service

would require so many compromises in satellite design and operation as to make it economically unreasonable.

(17) An applicant seeking to operate a space station in the 17/24 GHz broadcasting-satellite service pursuant to the provisions of § 25.262(b) of this part, at an offset location no greater than one degree offset from an orbital location specified in Appendix F of the Report and Order adopted May 2, 2007, IB Docket No. 06–123, FCC 07–76, must submit a written request to that effect as part of the narrative portion of its application.

(18) For space stations in the Direct Broadcast Satellite service or the 17/24 GHz broadcasting-satellite service, maximum orbital eccentricity.

[68 FR 63997, Nov. 12, 2003, as amended at 69 FR 29901, May 26, 2004; 69 FR 47794, Aug. 6, 2004; 69 FR 54587, Sept. 9, 2004; 72 FR 50027, Aug. 29, 2007; 72 FR 60278, Oct. 24, 2007; 76 FR 50431, Aug. 15, 2011; 78 FR 8421, Feb. 6, 2013; 79 FR 8314, Feb. 12, 2014; 81 FR 55326, Aug. 18, 2016]

### § 25.115 Applications for earth station authorizations.

(a)(1) *Transmitting earth stations.* Commission authorization must be obtained for authority to operate a transmitting earth station. Applications shall be filed electronically on FCC Form 312, Main Form and Schedule B, and include the information specified in § 25.130, except as set forth in paragraph (a)(2) of this section.

(2) Applicants for licenses for transmitting earth stations in the FSS may file on FCC Form 312EZ if all of the following criteria are met:

(i) The application is for a single station that will transmit to an FSS GSO space station, or stations, in the 5925–6425 MHz band, or for single or multiple stations that will transmit to an FSS GSO space station, or stations, in the 14.0–14.5 GHz, 28.35–28.6 GHz, and/or 29.5–30.0 GHz band;

(ii) The earth station(s) will not be installed or operated on ships, aircraft, or other moving vehicles;

(iii) The application meets all relevant criteria in § 25.211 or § 25.212 or includes information filed pursuant to paragraph (g)(1) of this section indicating that off-axis EIRP density from