

ground elevation at the antenna, antenna directivity and gain, proposed frequency, relevant FCC rule part, type of emission, effective radiated power, and whether the proposed use is itinerant. Generally, submission of the information in the technical portion of the FCC license application is adequate notification. In addition, the applicant shall indicate in its application to the Commission the date notification was made to the Arecibo Observatory.

(2) After receipt of such applications, the Commission will allow the Arecibo Observatory a period of 20 days for comments or objections in response to the notification indicated. The applicant will be required to make reasonable efforts in order to resolve or mitigate any potential interference problem with the Arecibo Observatory and to file either an amendment to the application or a modification application, as appropriate. If the Commission determines that an applicant has satisfied its responsibility to make reasonable efforts to protect the Observatory from interference, its application may be granted.

(3) The provisions of this paragraph do not apply to operations that transmit on frequencies above 15 GHz.

(j) Applicants for NGSO 1.6/2.4 GHz Mobile-Satellite Service/Radiodetermination-Satellite Service feeder links in the 17.7–20.2 GHz and 27.5–30.0 GHz bands must coordinate with licensees of FSS and terrestrial-service systems sharing the band to determine geographic protection areas around each NGSO MSS/Radiodetermination-Satellite Service feeder-link earth station.

(k) An applicant for operation of an earth station, other than an ESV, VMES or an ESAA, that will operate with a geostationary satellite or non-geostationary satellite in a shared frequency band in which the non-geostationary system is (or is proposed to be) licensed for feeder links, shall demonstrate in its applications that its proposed earth station will not cause unacceptable interference to any other satellite network that is authorized to operate in the same frequency band, or certify that the operations of its earth station shall conform to established coordination agreements between the op-

erator(s) of the space station(s) with which the earth station is to communicate and the operator(s) of any other space station licensed to use the band.

(1) Applicants for feeder link earth station facilities operating in the 25.05–25.25 GHz band may be licensed only in Economic Areas where no existing FS licensee has been authorized, and shall coordinate their operations with 24 GHz fixed service operations if the power flux density of their transmitted signal at the boundary of the fixed service license area is equal to or greater than  $-114$  dBW/m<sup>2</sup> in any 1 MHz.

(1) When uplink adaptive power control is used, the EIRP used for calculation of the power flux density level should be the maximum possible, taking into account the adaptive power increase.

(2) The power flux density levels should be calculated based on the actual off-axis gain characteristics of the earth station antenna, and should assume free space propagation conditions.

(3) When determining whether the power flux density threshold limit is exceeded at the 24 GHz FS licensing boundary, a feeder link earth station applicant must take into account not only the transmissions from its own antenna(s), but also those from any previously authorized feeder link earth stations. Thus, if the cumulative power flux density level at the FS license boundary is in excess of  $-114$  dBW/m<sup>2</sup>/MHz, the earth station applicant must either modify its proposed operations such that this value is not exceeded, or enter into coordination with the affected FS licensee.

[30 FR 7176, May 28, 1965]

EDITORIAL NOTE: For FEDERAL REGISTER citations affecting § 25.203, see the List of CFR Sections Affected, which appears in the Finding Aids section of the printed volume and at [www.fdsys.gov](http://www.fdsys.gov).

#### § 25.204 Power limits for earth stations.

(a) In bands shared coequally with terrestrial radio communication services, the equivalent isotropically radiated power transmitted in any direction towards the horizon by an earth station, other than an ESV, operating

in frequency bands between 1 and 15 GHz, shall not exceed the following limits except as provided for in paragraph (c) of this section:

- + 40 dBW in any 4 kHz band for  $\theta \leq 0^\circ$
- + 40 + 3 $\theta$  dBW in any 4 kHz band for  $0^\circ < \theta \leq 5^\circ$

where  $\theta$  is the angle of elevation of the horizon viewed from the center of radiation of the antenna of the earth station and measured in degrees as positive above the horizontal plane and negative below it.

(b) In bands shared coequally with terrestrial radiocommunication services, the equivalent isotropically radiated power transmitted in any direction towards the horizon by an earth station operating in frequency bands above 15 GHz shall not exceed the following limits except as provided for in paragraph (c) of this section:

- + 64 dBW in any 1 MHz band for  $\theta \leq 0^\circ$
- + 64 + 3 $\theta$  dBW in any 1 MHz band for  $0^\circ < \theta \leq 5^\circ$

where  $\theta$  is as defined in paragraph (a) of this section.

(c) For angles of elevation of the horizon greater than  $5^\circ$  there shall be no restriction as to the equivalent isotropically radiated power transmitted by an earth station towards the horizon.

(d) Notwithstanding the e.i.r.p. and e.i.r.p. density limits specified in the station authorization, each earth station transmission shall be conducted at the lowest power level that will provide the required signal quality as indicated in the application and further amended by coordination agreements.

(e) To the extent specified in paragraphs (e)(1) through (e)(4) of this section, earth stations in the Fixed-Satellite Service may employ uplink adaptive power control or other methods of fade compensation to facilitate transmission of uplinks at power levels required for desired link performance while minimizing interference between networks.

(1) Except when paragraphs (e)(2) through (e)(4) of this section apply, transmissions from FSS earth stations in frequencies above 10 GHz may exceed the uplink EIRP and EIRP density limits specified in the station authoriza-

tion under conditions of uplink fading due to precipitation by an amount not to exceed 1 dB above the actual amount of monitored excess attenuation over clear sky propagation conditions. EIRP levels must be returned to normal as soon as the attenuating weather pattern subsides.

(2) An FSS earth station transmitting to a geostationary space station in the 13.77–13.78 GHz band must not generate more than 71 dBW EIRP in any 6 MHz band. An FSS earth station transmitting to a non-geostationary space station in the 13.77–13.78 GHz band must not generate more than 51 dBW EIRP in any 6 MHz band. Automatic power control may be used to increase the EIRP density in a 6 MHz uplink band in this frequency range to compensate for rain fade, provided that the power flux-density at the space station does not exceed the value that would result when transmitting with an EIRP of 71 dBW or 51 dBW, as appropriate, in that 6 MHz band in clear-sky conditions.

(3) FSS earth stations transmitting to geostationary space stations in the 28.35–28.6 GHz and/or 29.25–30.0 GHz bands may employ uplink adaptive power control or other methods of fade compensation. For stations employing uplink power control, the values in paragraphs (a)(1), (a)(2), and (a)(4) of §25.138 may be exceeded by up to 20 dB under conditions of uplink fading due to precipitation. The amount of such increase in excess of the actual amount of monitored excess attenuation over clear sky propagation conditions must not exceed 1.5 dB or 15 percent of the actual amount of monitored excess attenuation in dB, whichever is larger, with a confidence level of 90 percent except over transient periods accounting for no more than 0.5 percent of the time during which the excess is no more than 4.0 dB.

(4) Transmissions in the 24.75–25.25 GHz band from 17/24 GHz BSS feeder-link earth stations employing power control may exceed the values in paragraphs (b)(1), (b)(2), and (b)(4) of §25.223 by up to 20 dB under conditions of uplink fading due to precipitation. The amount of such increase in excess of the actual amount of monitored excess attenuation over clear sky propagation

## § 25.205

conditions must not exceed 1.5 dB or 15 percent of the actual amount of monitored excess attenuation in dB, whichever is larger, with a confidence level of 90 percent except over transient periods accounting for no more than 0.5 percent of the time during which the excess is no more than 4.0 dB.

(f) An earth station in the Fixed-Satellite Service transmitting in the 13.75–14 GHz band must have a minimum antenna diameter of 4.5 m, and the EIRP of any emission in that band should be at least 68 dBW and should not exceed 85 dBW.

(g) [Reserved]

(h) ESV transmissions in the 5925–6425 MHz (Earth-to-space) band shall not exceed an e.i.r.p. spectral density towards the radio-horizon of 17 dBW/MHz, and shall not exceed an e.i.r.p. towards the radio-horizon of 20.8 dBW. The ESV network shall shut-off the ESV transmitter if the e.i.r.p. spectral density towards the radio-horizon or e.i.r.p. towards the radio-horizon are exceeded.

(i) Within 125 km of the TDRSS sites identified in §25.222(d), ESV transmissions in the 14.0–14.2 GHz (Earth-to-space) band shall not exceed an e.i.r.p. spectral density towards the horizon of 12.5 dBW/MHz, and shall not exceed an e.i.r.p. towards the horizon of 16.3 dBW.

(j) Within 125 km of the Tracking and Data Relay System Satellite (TDRSS) sites identified in §25.226(c), VMES transmissions in the 14.0–14.2 GHz (Earth-to-space) band shall not exceed an EIRP spectral density towards the horizon of 12.5 dBW/MHz, and shall not exceed an EIRP towards the horizon of 16.3 dBW.

(k) Within radio line-of-sight of the Tracking and Data Relay System Satellite (TDRSS) sites identified in §25.227(c), ESAA transmissions in the 14.0–14.2 GHz (Earth-to-space) band shall not exceed an EIRP spectral density towards or below the horizon of 12.5 dBW/MHz, and shall not exceed an

## 47 CFR Ch. I (10–1–16 Edition)

EIRP towards or below the horizon of 16.3 dBW.

[48 FR 40255, Sept. 6, 1983, as amended at 58 FR 13420, Mar. 11, 1993; 61 FR 52307, Oct. 7, 1996; 62 FR 61457, Nov. 18, 1997; 66 FR 10623, Feb. 16, 2001; 70 FR 4784, Jan. 31, 2005; 70 FR 32255, June 2, 2005; 72 FR 50029, Aug. 29, 2007; 74 FR 57098, Nov. 4, 2009; 78 FR 8427, Feb. 6, 2013; 78 FR 14927, Mar. 8, 2013; 79 FR 8322, Feb. 12, 2004; 81 FR 55336, Aug. 18, 2016]

### § 25.205 Minimum antenna elevation angle.

(a) Earth station antennas must not transmit at elevation angles less than five degrees, measured from the horizontal plane to the direction of maximum radiation, in a frequency band shared with terrestrial radio services or in a frequency band with an allocation to space services operating in both the Earth-to-space and space-to-Earth directions. In other bands, earth station antennas must not transmit at elevation angles less than three degrees. In some instances, it may be necessary to specify greater minimum elevation angles because of interference considerations.

(b) ESAAs in aircraft on the ground must not transmit at elevation angles less than three degrees. There is no minimum angle of antenna elevation for ESAAs while airborne.

[81 FR 55336, Aug. 18, 2016]

### § 25.206 Station identification.

The requirement to transmit station identification is waived for all radio stations licensed under this part with the exception of earth stations subject to the requirements of §25.281.

[79 FR 8322, Feb. 12, 2014]

### § 25.207 Cessation of emissions.

Space stations shall be made capable of ceasing radio emissions by the use of appropriate devices (battery life, timing devices, ground command, etc.) that will ensure definite cessation of emissions.

### § 25.208 Power flux density limits.

(a) In the band 3650–4200 MHz, the power flux density at the Earth's surface produced by emissions from a space station for all conditions and for