

§ 25.210

47 CFR Ch. I (10–1–16 Edition)

Where θ and dBi are as defined in paragraph (a)(1) of this section.

(3) In the plane tangent to the GSO arc or in the plane perpendicular to the

GSO arc, for earth stations operating in the 24.75–25.25 GHz or 28.35–30 GHz bands:

19–25log ₁₀ θ	dBi	for 2° < θ ≤ 7°.
--------------------------------	-----	------------------

Where θ and dBi are as defined in paragraph (a)(1) of this section.

(c)(1) An earth station licensed for operation with an FSS space station or registered for reception of transmissions from such a space station pursuant to § 25.131(b) and (d) is not entitled to protection from interference from authorized operation of other stations that would not cause harmful interference to that earth station if it were using an antenna with receive-band gain patterns conforming to the levels specified in paragraphs (a) and (b) of this section.

(2) A 17/24 GHz BSS telemetry earth station is not entitled to protection from harmful interference from authorized space station operation that would not cause harmful interference to that earth station if it were using an antenna with receive-band gain patterns conforming to the levels specified in paragraphs (a) and (b) of this section. Receive-only earth stations in the 17/24 GHz BSS are entitled to protection from harmful interference caused by other space stations to the extent indicated in § 25.224.

(d) [Reserved]

(e) An earth station using asymmetrical antennas without skew angle adjustment capability must comply with the gain values specified in paragraph (a)(1) of this section, in the plane orthogonal to the to the main plane of the antenna, or, alternatively, in the plane corresponding to the maximum skew angle experienced at any location at which the earth station may be located.

(f) A GSO FSS earth station with an antenna that does not conform to the applicable standards in paragraphs (a) and (b) of this section will be authorized only if the applicant demonstrates that the antenna will not cause unacceptable interference. This demonstration must comply with the requirements in § 25.138, § 25.218, § 25.220, § 25.221, § 25.222, § 25.223, § 25.226, or § 25.227, as appropriate.

(g) [Reserved]

(h) The gain of any transmitting antenna in a gateway earth station communicating with NGSO FSS satellites in the 10.7–11.7 GHz, 12.75–13.15 GHz, 13.2125–13.25 GHz, 13.8–14.0 GHz, and/or 14.4–14.5 GHz bands must lie below the envelope defined as follows:

29–25log ₁₀ (θ)	dBi	for 1° ≤ θ ≤ 36°.
– 10	dBi	for 36° ≤ θ ≤ 180°.

Where θ and dBi are as defined in paragraph (a)(1) of this section. This envelope may be exceeded by up to 3 dB in 10% of the range of θ angles from ±7–180°.

[48 FR 40255, Sept. 6, 1983, as amended at 50 FR 2675, Jan. 18, 1985; 50 FR 39004, Sept. 26, 1985; 58 FR 13420, Mar. 11, 1993; 66 FR 10630, Feb. 16, 2001; 70 FR 32255, June 2, 2005; 72 FR 50029, Aug. 29, 2007; 73 FR 70901, Nov. 24, 2008; 74 FR 57099, Nov. 4, 2009; 78 FR 8427, Feb. 6, 2013; 78 FR 14927, Mar. 8, 2013; 79 FR 8322, Feb. 12, 2014; 81 FR 55336, Aug. 18, 2016]

§ 25.210 Technical requirements for space stations.

(a)–(b) [Reserved]

(c) Space station antennas operating in the Direct Broadcast Satellite Service or operating in the Fixed-Satellite Service for reception of feeder links for Direct Broadcast Satellite Service must be designed to provide a cross-polarization isolation such that the ratio of the on-axis co-polar gain to the cross-polar gain of the antenna in the assigned frequency band is at least 27 dB within the primary coverage area.

(d)–(e) [Reserved]

(f) All space stations in the Fixed-Satellite Service operating in any portion of the 3600–4200 MHz, 5091–5250 MHz, 5850–7025 MHz, 10.7–12.7 GHz, 12.75–13.25 GHz, 13.75–14.5 GHz, 15.43–15.63 GHz, 18.3–20.2 GHz, 24.75–25.25 GHz, or 27.5–30.0 GHz bands, including feeder links for other space services, and in the Broadcasting-Satellite Service in the 17.3–17.8 GHz band (space-to-Earth), shall employ state-of-the-art full frequency reuse, either through the use of orthogonal polarizations within the same beam and/or the use of spatially independent beams. This requirement does not apply to telemetry, tracking, and command operation.

(g)–(h) [Reserved]

(i) Space station antennas in the 17/24 GHz BSS must be designed to provide a cross-polarization isolation such that the ratio of the on axis co-polar gain to the cross-polar gain of the antenna in the assigned frequency band shall be at least 25 dB within its primary coverage area.

(j) Space stations operated in the geostationary satellite orbit must be maintained within 0.05° of their assigned orbital longitude in the east/west direction, unless specifically authorized by the Commission to operate with a different longitudinal tolerance, and except as provided in Section 25.283(b) (End-of-life Disposal).

[58 FR 13420, Mar. 11, 1993, as amended at 61 FR 9952, Mar. 12, 1996; 62 FR 5931, Feb. 10, 1997; 62 FR 61457, Nov. 18, 1997; 68 FR 51508, Aug. 27, 2003; 69 FR 54587, Sept. 9, 2004; 70 FR 32256, June 2, 2005; 72 FR 50029, Aug. 29, 2007; 78 FR 8428, Feb. 6, 2013; 79 FR 8323, Feb. 12, 2014; 81 FR 55338, Aug. 18, 2016]

§ 25.211 Analog video transmissions in the FSS.

(a) [Reserved]

(b) All conventional C-band analog video transmissions must contain an energy dispersal signal at all times with a minimum peak-to-peak bandwidth set at whatever value is necessary to meet the power flux density limits specified in § 25.208(a) and successfully coordinated internationally and accepted by adjacent U.S. satellite operators based on the use of state of the art space and earth station facilities. All transmissions in frequency

bands described in § 25.208(b) and (c) must also contain an energy dispersal signal at all times with a minimum peak-to-peak bandwidth set at whatever value is necessary to meet the power flux density limits specified in § 25.208(b) and (c) and successfully coordinated internationally and accepted by adjacent U.S. satellite operators based on the use of state of the art space and earth station facilities.

(c) All initial analog video transmissions shall be preceded by a video test transmission at an uplink e.i.r.p. at least 10 dB below the normal operating level. The earth station operator shall not increase power until receiving notification from the satellite network control center that the frequency and polarization alignment are satisfactory pursuant to the procedures specified in § 25.272. The stationary earth station operator that has successfully transmitted an initial video test signal to a satellite pursuant to this paragraph is not required to make subsequent video test transmissions if subsequent transmissions are conducted using exactly the same parameters as the initial transmission.

(d) An earth station may be routinely licensed for transmission of full-transponder analog video services in the 5925–6425 MHz band or 14.0–14.5 GHz band provided:

(1) The application includes certification, pursuant to § 25.132(a)(1), of conformance with the antenna performance standards in § 25.209(a) and (b);

(2) For transmission in the 5925–6425 MHz band, the input power into the antenna will not exceed 26.5 dBW; or

(3) For transmission in the 14.0–14.5 GHz band, the input power into the antenna will not exceed 27 dBW.

(e) Applications for authority for analog video uplink transmission in the 5925–6425 MHz or 14.0–14.5 GHz bands that are not eligible for routine processing under paragraph (d) of this section are subject to the requirements of § 25.220.

[58 FR 13421, Mar. 11, 1993, as amended at 61 FR 9952, Mar. 12, 1996; 62 FR 5931, Feb. 10, 1997; 70 FR 32256, June 2, 2005; 78 FR 8428, Feb. 6, 2013; 79 FR 8323, Feb. 12, 2014; 81 FR 55338, Aug. 18, 2016]