

distance around the new RAS site, subject to any operational constraints developed in the coordination process.

[78 FR 14927, Mar. 8, 2013, as amended at 79 FR 8324, Feb. 12, 2014; 79 FR 26868, May 12, 2014; 81 FR 55347, Aug. 18, 2016]

§§ 25.228–25.249 [Reserved]

§ 25.250 Sharing between NGSO MSS Feeder links Earth Stations in the 19.3–19.7 GHz and 29.1–29.5 GHz Bands.

(a) NGSO MSS applicants shall be licensed to operate in the 29.1–29.5 GHz band for Earth-to-space transmissions and 19.3–19.7 GHz for space-to-Earth transmissions from feeder link earth station complexes. A “feeder link earth station complex” may include up to three (3) earth station groups, with each earth station group having up to four (4) antennas, located within a radius of 75 km of a given set of geographic coordinates provided by NGSO-MSS licensees or applicants.

(b) Licensees of NGSO MSS feeder link earth stations separated by 800 km or less are required to coordinate their operations, see §25.203. The results of the coordination shall be reported to the Commission.

[61 FR 44181, Aug. 28, 1996]

§ 25.251 Special requirements for coordination.

(a) The administrative aspects of the coordination process are set forth in §101.103 of this chapter in the case of coordination of terrestrial stations with earth stations, and in §25.203 in the case of coordination of earth stations with terrestrial stations.

(b) The technical aspects of coordination are based on Appendix 7 of the International Telecommunication Union Radio Regulations and certain recommendations of the ITU Radiocommunication Sector (available at the address in §0.445 of this chapter).

[66 FR 10630, Feb. 16, 2001, as amended at 78 FR 8430, Feb. 6, 2013]

§ 25.252 [Reserved]

§ 25.253 Special requirements for ancillary terrestrial components operating in the 1626.5–1660.5 MHz/1525–1559 MHz bands.

(a) An ancillary terrestrial component in these bands shall:

(1) In any band segment coordinated for the exclusive use of an MSS applicant within the land area of the U.S., where there is no other L-Band MSS satellite making use of that band segment within the visible portion of the geostationary arc as seen from the ATC coverage area, the ATC system will be limited by the in-band and out-of-band emission limitations contained in this section and the requirement to maintain a substantial MSS service.

(2) In any band segment that is coordinated for the shared use of the applicant’s MSS system and another MSS operator, where the coordination agreement existed prior to February 10, 2005 and permits a level of interference to the other MSS system of less than 6% $\Delta T/T$, the applicant’s combined ATC and MSS operations shall increase the system noise level of the other MSS to no more than 6% $\Delta T/T$. Any future coordination agreement between the parties governing ATC operation will supersede this paragraph.

(3) In any band segment that is coordinated for the shared use of the applicant’s MSS system and another MSS operator, where a coordination agreement existed prior to February 10, 2005 and permits a level of interference to the other MSS system of 6% $\Delta T/T$ or greater, the applicant’s ATC operations may increase the system noise level of the other MSS system by no more than an additional 1% $\Delta T/T$. Any future coordination agreement between the parties governing ATC operations will supersede this paragraph.

(4) In a band segment in which the applicant has no rights under a coordination agreement, the applicant may not implement ATC in that band.

(b) ATC base stations shall not exceed an out-of-channel emissions measurement of -57.9 dBW/MHz at the edge of a MSS licensee’s authorized and internationally coordinated MSS frequency assignment.