Federal Communications Commission

liability or damage that it and its directors, officers, employees, affiliates, agents and subcontractors may incur or suffer in connection with an interruption of its Mobile-Satellite Service, in whole or in part, arising from or relating to its compliance or noncompliance with the requirements of this paragraph.

(c) Each satellite in a NVNG licensee's system time-sharing spectrum with DoD in the 400.15–401 MHz band shall automatically turn off and cease satellite transmissions if, after 72 consecutive hours, no reset signal is received from the NVNG licensee's gateway earth station and verified by the satellite. All satellites in such NVNG licensee's system shall be capable of instantaneous shutdown on any sub-band upon command from such NVNG licensee's gateway earth station.

(d) Initially, a NVNG licensee timesharing spectrum with DoD in the 400.15-401 MHz band shall be able to change the frequency on which its system satellites are operating within 125 minutes of receiving notification from a DoD required frequency change in the 400.15-401 MHz band. Thereafter, when a NVNG licensee constructs additional gateway earth stations located outside of North and South America, it shall use its best efforts to decrease to 90 minutes the time required to implement a DoD required frequency change. A NVNG licensee promptly shall notify the Commission and NTIA of any decrease in the time it requires to implement a DoD required frequency change.

(e) Once a NVNG licensee time-sharing spectrum with DoD in the 400.15-401 MHz band demonstrates to DoD that it is capable of implementing a DoD required frequency change within the time required under paragraph (d) of this section, thereafter, such NVNG licensee shall demonstrate its capability to implement a DoD required frequency change only once per year at the instruction of DoD. Such demonstrations shall occur during off-peak hours, as determined by the NVNG licensee, unless otherwise agreed by the NVNG licensee and DoD. Such NVNG licensee will coordinate with DoD in establishing a plan for such a demonstration. In the event that a NVNG licensee fails to demonstrate to DoD

that it is capable of implementing a DoD required frequency change in accordance with a demonstration plan established by DoD and the NVNG licensee, upon the Commission's receipt of a written notification from NTIA describing such failure, the Commission shall impose additional conditions or requirements on the NVNG licensee's authorization as may be necessary to protect DoD operations in the 400.15-401 MHz downlink band until the Commission is notified by NTIA that the NVNG licensee has successfully demonstrated its ability to implement a DoD required frequency change. Such additional conditions or requirements may include, but are not limited to, requiring such NVNG licensee immediately to terminate its operations interfering with the DoD system.

[62 FR 59296, Nov. 3, 1997, as amended at 78 FR 8430, Feb. 6, 2013; 79 FR 8325, Feb. 12, 2014]

§ 25.261 Procedures for avoidance of in-line interference events for Non Geostationary Satellite Orbit (NGSO) Satellite Network Operations in the Fixed-Satellite Service (FSS) Bands.

(a) Applicable NGSO FSS Bands. The coordination procedures in this section apply to non-Federal-Government NGSO FSS satellite networks operating in the following assigned frequency bands: The 28.6–29.1 GHz or 18.8–19.3 GHz frequency bands.

(b) Definition of "In-line interference events." For purposes of this section, an "in-line interference event" is defined as the interference associated with an occurrence of any physical alignment of space stations of two or more satellite networks with an operating Earth station of one of these networks in such a way that the angular separation between operational links of the two networks is less than 10° as measured at the Earth station.

(c) *Default procedure*. If no agreed coordination exists between two or more satellite networks, then the bands will be divided among the affected satellite networks involved in an in-line interference event in accordance with the following procedure:

(1) Each of n (number of) satellite networks involved in a particular inline interference event shall select 1/n of the assigned spectrum available in each frequency band for its home base spectrum. The selection order for each satellite network shall be determined by and be in accordance with the date that the first space station in each satellite network is launched and operating;

(2) The affected space station(s) of the respective satellite networks shall only operate in the selected (1/n) spectrum associated with its satellite network, its home base spectrum, for the duration of the in-line interference event;

(3) All affected space station(s) may resume operations throughout the assigned frequency bands once the angular separation between the affected space stations in the in-line interference event is again greater than 10° .

(d) Coordination procedure. Any coordination procedure agreed among the affected operating satellite networks, which allows operations of the satellite networks when each network's respective space stations are within the 10 degree avoidance angle associated with an in-line interference event, shall supersede the default procedure of paragraph (c) of this section. Coordination may be effected using information relating to the space stations and the parameters of one or more typical earth stations. All parties are required to coordinate in good faith.

 $[68\ {\rm FR}\ 59129,\ {\rm Oct.}\ 14,\ 2003,\ {\rm as}\ {\rm amended}\ {\rm at}\ 78$ FR 8430, Feb. 6, 2013]

§25.262 Licensing and domestic coordination requirements for 17/24 GHz BSS space stations.

(a) Except as described in paragraphs (b), (c) or (e) of this section, applicants seeking to operate a space station in the 17/24 GHz BSS must locate that space station at one of the orbital positions described in Appendix F of the Report and Order adopted May 2, 2007, IB Docket No. 06-123, FCC 07-76.

(b) An applicant may be authorized to operate a 17/24 GHz BSS space station at an orbital location described in Appendix F as set forth in paragraph (a) of this section, or at a location with a geocentric angular separation of one degree or less from an Appendix F location, and may operate at the maximum power flux density limits defined in 47 CFR Ch. I (10–1–16 Edition)

§25.208(c) and (w) of this part, without coordinating its power flux density levels with adjacent licensed or permitted operators, only if there is no licensed 17/24 GHz BSS space station or priorfiled application at a location less than four degrees from the offset orbital location at which the applicant proposes to operate.

(c)(1) Notwithstanding the provisions of this section, licensees and permittees will be allowed to apply for a license or authorization for a replacement satellite that will be operated at the same power level and interference protection as the satellite to be replaced.

(2) In addition, applicants for licenses or authority for a satellite to be operated at an orbit location that was made available after a previous 17/24 GHz BSS license was cancelled or surrendered will be permitted to apply for authority to operate a satellite at the same power level and interference protection as the previous licensee at that orbit location, to the extent that their proposed operations are consistent with the provisions of this part. Such applications will be considered pursuant to the first-come, first-served procedures set forth in §25.158 of this part.

(d) Any U.S. licensee or permittee using a 17/24 GHz BSS space station that is located less than four degrees away from a prior-authorized 17/24 GHz BSS space station that is authorized to operate in accordance with paragraph (b) of this section:

(1) may not cause any more interference to the adjacent satellite network than would be caused if the adjacent 17/24 GHz BSS space station were located four degrees away from the proposed space station; and

(2) must accept any increased interference that results from the adjacent space station network operating at the offset orbital location less than four degrees away.

(e) Any 17/24 GHz BSS U.S. licensee or permittee that is required to provide information in its application pursuant to §25.140(b)(4)(ii) or (b)(4)(iii) of this part must accept any increased interference that may result from adjacent 17/24 GHz BSS space stations that are operating in compliance with the rules for this service.