§ 74.1201

being used. A period of operation may consist of a continuous transmission or intermittent transmissions pertaining to a single event.

- (b) Each wireless video assist device, when transmitting, must transmit station identification at the beginning and end of each period of operation. Identification may be made by transmitting the station call sign by visual or aural means or by automatic transmission in international Morse telegraphy.
- (1) A period of operation is defined as a single uninterrupted transmission or a series of intermittent transmissions from a single location.
- (2) Station identification shall be performed in a manner conducive to prompt association of the signal source with the responsible licensee. In exercising the discretion provide by this rule, licensees are expected too act in a responsible manner to assure that result.

[68 FR 12774, Mar. 17, 2003]

Subparts I-K [Reserved]

Subpart L—FM Broadcast Translator Stations and FM Broadcast Booster Stations

SOURCE: 35 FR 15388, Oct. 2, 1970, unless otherwise noted.

§74.1201 Definitions.

- (a) FM translator. A station in the broadcasting service operated for the purpose of retransmitting the signals of an AM or FM radio broadcast station or another FM broadcast translator station without significantly altering any characteristics of the incoming signal other than its frequency and amplitude, in order to provide radio broadcast service to the general public.
- (b) Commercial FM translator. An FM broadcast translator station which rebroadcasts the signals of a commercial AM or FM radio broadcast station.
- (c) Noncommercial FM translator. An FM broadcast translator station which rebroadcasts the signals of a noncommercial educational AM or FM radio broadcast station.

- (d) Primary station. The AM or FM radio broadcast station radiating the signals which are retransmitted by an FM broadcast translator station or an FM broadcast booster station.
- (e) AM or FM radio broadcast station. When used in this Subpart L, the term AM broadcast station or AM radio broadcast station or FM broadcast station or FM radio broadcast station refers to commercial and noncommercial educational AM or FM radio broadcast stations as defined in §2.1 of this chapter, unless the context indicates otherwise.
- (f) FM broadcast booster station. A station in the broadcasting service operated for the sole purpose of retransmitting the signals of an FM radio broadcast station, by amplifying and reradiating such signals, without significantly altering any characteristic of the incoming signal other than its amplitude.
- (g) Translator coverage contour. For a fill-in FM translator rebroadcasting an FM radio broadcast station as its primary station, the FM translator's coverage contour must be contained within the primary station's coverage contour. For purposes of this rule section, the coverage contour of the FM translator has the same field strength value as the protected contour of the primary FM station (i.e., for a commercial Class B FM station it is the predicted 0.5 mV/m field strength contour, for a commercial Class B1 FM station it is the predicted 0.7 mV/m field strength contour, and for all other classes of FM stations it is the predicted 1 mV/m field strength contour). The coverage contour of an FM translator rebroadcasting an AM radio broadcast station as its primary station must be contained within the lesser of the 2 mV/m daytime contour of the AM station and a 25-mile (40 km) radius centered at the AM transmitter site. The protected contour for an FM translator station is its predicted 1 mV/m contour.
- (h) Fill-in area. The area where the coverage contour of an FM translator or booster station is within the protected contour of the associated primary station (i.e., predicted 0.5 mV/m contour for commercial Class B stations, predicted 0.7 mV/m contour for

commercial Class B1 stations, and predicted 1 mV/m contour for all other classes of stations).

- (i) Other area. The area where the coverage contour of an FM translator station extends beyond the protected contour of the primary station (i.e., predicted 0.5 mV/m contour for commercial Class B stations, predicted 0.7 mV/m contour for commercial Class B1 stations, and predicted 1 mV/m contour for all other classes of stations).
- (j) AM Fill-in area. The area within the lesser of the 2 mV/m daytime contour of the AM radio broadcast station being rebroadcast and a 25-mile (40 km) radius centered at the AM transmitter site.

[35 FR 15388, Oct. 2, 1970, as amended at 45 FR 37842, June 5, 1980; 52 FR 31405, Aug. 20, 1987; 55 FR 50693, Dec. 10, 1990; 74 FR 45129, Sept. 1, 20091

§74.1202 Frequency assignment.

- (a) An applicant for a new FM broadcast translator station or for changes in the facilities of an authorized translator station shall endeavor to select a channel on which its operation is not likely to cause interference to the reception of other stations. The application must be specific with regard to the frequency requested. Only one output channel will be assigned to each translator station.
- (b) Subject to compliance with all the requirements of this subpart, FM broadcast translators may be authorized to operate on the following FM channels, regardless of whether they are assigned for local use in the FM Table of Allotments (§73.202(b) of this chapter):
- (1) Commercial FM translators: Channels 221–300 as identified in $\S73.201$ of this chapter.
- (2) Noncommercial FM translators: Channels 201–300 as identified in §73.201 of this chapter. Use of reserved channels 201–220 is subject to the restrictions specified in §73.501 of this chapter.
- (3) In Alaska, FM translators operating on Channels 201–260 (88.1–99.9 MHz) shall not cause harmful interference to and must accept interference from non-Government fixed operations authorized prior to January 1, 1002

(c) An FM broadcast booster station will be assigned the channel assigned to its primary station.

[35 FR 15388, Oct. 2, 1970, as amended at 39 FR 12990, Apr. 10, 1974; 47 FR 30068, July 12, 1982; 52 FR 8260, Mar. 17, 1987; 55 FR 50693, Dec. 10, 19901

§ 74.1203 Interference.

- (a) An authorized FM translator or booster station will not be permitted to continue to operate if it causes any actual interference to:
- (1) The transmission of any authorized broadcast station; or
- (2) The reception of the input signal of any TV translator, TV booster, FM translator or FM booster station; or
- (3) The direct reception by the public of the off-the-air signals of any authorized broadcast station including TV Channel 6 stations, Class D (secondary) noncommercial educational FM stations, and previously authorized and operating FM translators and FM booster stations. Interference will be considered to occur whenever reception of a regularly used signal is impaired by the signals radiated by the FM translator or booster station, regardless of the quality of such reception, the strength of the signal so used, or the channel on which the protected signal is transmitted.
- (b) If interference cannot be properly eliminated by the application of suitable techniques, operation of the offending FM translator or booster station shall be suspended and shall not be resumed until the interference has been eliminated. Short test transmissions may be made during the period of suspended operation to check the efficacy of remedial measures. If a complainant refuses to permit the FM translator or booster licensee to apply remedial techniques which demonstrably will eliminate the interference without impairment to the original reception, the licensee of the FM translator or booster station is absolved of further responsibility for that com-
- (c) An FM booster station will be exempted from the provisions of paragraphs (a) and (b) of this section to the extent that it may cause limited interference to its primary station's signal, provided it does not disrupt the existing