

Pt. 15

- 15.103 Exempted devices.
- 15.105 Information to the user.
- 15.107 Conducted limits.
- 15.109 Radiated emission limits.
- 15.111 Antenna power conduction limits for receivers.
- 15.113 Power line carrier systems.
- 15.115 TV interface devices, including cable system terminal devices.
- 15.117 TV broadcast receivers.
- 15.118 Cable ready consumer electronics equipment.
- 15.119 [Reserved]
- 15.120 Program blocking technology requirements for television receivers.
- 15.121 Scanning receivers and frequency converters used with scanning receivers.
- 15.122 [Reserved]
- 15.123 Labeling of digital cable ready products.

Subpart C—Intentional Radiators

- 15.201 Equipment authorization requirement.
- 15.202 Certified operating frequency range.
- 15.203 Antenna requirement.
- 15.204 External radio frequency power amplifiers and antenna modifications.
- 15.205 Restricted bands of operation.
- 15.207 Conducted limits.
- 15.209 Radiated emission limits; general requirements.
- 15.211 Tunnel radio systems.
- 15.212 Modular transmitters.
- 15.213 Cable locating equipment.
- 15.214 Cordless telephones.

RADIATED EMISSION LIMITS, ADDITIONAL PROVISIONS

- 15.215 Additional provisions to the general radiated emission limitations.
- 15.216 [Reserved]
- 15.217 Operation in the band 160–190 kHz.
- 15.219 Operation in the band 510–1705 kHz.
- 15.221 Operation in the band 525–1705 kHz.
- 15.223 Operation in the band 1.705–10 MHz.
- 15.225 Operation within the band 13.110–14.010 MHz.
- 15.227 Operation within the band 26.96–27.28 MHz.
- 15.229 Operation within the band 40.66–40.70 MHz.
- 15.231 Periodic operation in the band 40.66–40.70 MHz and above 70 MHz.
- 15.233 Operation within the bands 43.71–44.49 MHz, 46.60–46.98 MHz, 48.75–49.51 MHz and 49.66–50.0 MHz.
- 15.235 Operation within the band 49.82–49.90 MHz.
- 15.236 Operation of wireless microphones in the bands 54–72 MHz, 76–88 MHz, 174–216 MHz, 470–608 MHz and 614–698 MHz.
- 15.237 Operation in the bands 72.0–73.0 MHz, 74.6–74.8 MHz and 75.2–76.0 MHz.
- 15.239 Operation in the band 88–108 MHz.
- 15.240 Operation in the band 433.5–434.5 MHz.

47 CFR Ch. I (10–1–20 Edition)

- 15.241 Operation in the band 174–216 MHz.
- 15.242 Operation in the bands 174–216 MHz and 470–668 MHz.
- 15.243 Operation in the band 890–940 MHz.
- 15.245 Operation within the bands 902–928 MHz, 2435–2465 MHz, 5785–5815 MHz, 10500–10550 MHz, and 24075–24175 MHz.
- 15.247 Operation within the bands 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz.
- 15.249 Operation within the bands 902–928 MHz, 2400–2483.5 MHz, 5725–5875 MHz, and 24.0–24.25 GHz.
- 15.250 Operation of wideband systems within the band 5925–7250 MHz.
- 15.251 Operation within the bands 2.9–3.26 GHz, 3.267–3.332 GHz, 3.339–3.3458 GHz, and 3.358–3.6 GHz.
- 15.252 Operation of wideband vehicular radar systems within the band 23.12–29.0 GHz.
- 15.253 [Reserved]
- 15.255 Operation within the band 57–71 GHz.
- 15.256 Operation of level probing radars within the bands 5.925–7.250 GHz, 24.05–29.00 GHz, and 75–85 GHz.
- 15.257 Operation within the band 92–95 GHz.
- 15.258 Operation in the bands 116–123 GHz, 174.8–182 GHz, 185–190 GHz and 244–246 GHz.

Subpart D—Unlicensed Personal Communications Service Devices

- 15.301 Scope.
- 15.303 Definitions.
- 15.305 Equipment authorization requirement.
- 15.307 [Reserved]
- 15.309 Cross reference.
- 15.313 Measurement procedures.
- 15.315 Conducted limits.
- 15.317 Antenna requirement.
- 15.319 General technical requirements.
- 15.321 [Reserved]
- 15.323 Specific requirements for devices operating in the 1920–1930 MHz band.

Subpart E—Unlicensed National Information Infrastructure Devices

- 15.401 Scope.
- 15.403 Definitions.
- 15.405 Cross reference.
- 15.407 General technical requirements.

Subpart F—Ultra-Wideband Operation

- 15.501 Scope.
- 15.503 Definitions.
- 15.505 Cross reference.
- 15.507 Marketing of UWB equipment.
- 15.509 Technical requirements for ground penetrating radars and wall imaging systems.
- 15.510 Technical requirements for through-wall imaging systems.
- 15.511 Technical requirements for surveillance systems.

Federal Communications Commission

§ 15.3

- 15.513 Technical requirements for medical imaging systems.
- 15.515 Technical requirements for vehicular radar systems.
- 15.517 Technical requirements for indoor UWB systems.
- 15.519 Technical requirements for hand held UWB systems.
- 15.521 Technical requirements applicable to all UWB devices.
- 15.523 Measurement procedures.
- 15.525 Coordination requirements.

Subpart G—Access Broadband Over Power Line (Access BPL)

- 15.601 Scope.
- 15.603 Definitions.
- 15.605 Cross reference.
- 15.607 Equipment authorization of Access BPL equipment.
- 15.609 Marketing of Access BPL equipment.
- 15.611 General technical requirements.
- 15.613 Measurement procedures.
- 15.615 General administrative requirements.

Subpart H—White Space Devices

- 15.701 Scope.
- 15.703 Definitions.
- 15.705 Cross reference.
- 15.706 Information to the user.
- 15.707 Permissible channels of operation.
- 15.709 General technical requirements.
- 15.711 Interference avoidance methods.
- 15.712 Interference protection requirements.
- 15.713 White space database.
- 15.714 White space database administration fees.
- 15.715 White space database administrator.
- 15.717 White space devices that rely on spectrum sensing.

AUTHORITY: 47 U.S.C. 154, 302a, 303, 304, 307, 336, 544a, and 549.

SOURCE: 54 FR 17714, Apr. 25, 1989, unless otherwise noted.

Subpart A—General

§ 15.1 Scope of this part.

(a) This part sets out the regulations under which an intentional, unintentional, or incidental radiator may be operated without an individual license. It also contains the technical specifications, administrative requirements and other conditions relating to the marketing of part 15 devices.

(b) The operation of an intentional or unintentional radiator that is not in accordance with the regulations in this part must be licensed pursuant to the provisions of section 301 of the Communications Act of 1934, as amended, un-

less otherwise exempted from the licensing requirements elsewhere in this chapter.

(c) Unless specifically exempted, the operation or marketing of an intentional or unintentional radiator that is not in compliance with the administrative and technical provisions in this part, including prior equipment authorization, as appropriate, is prohibited under section 302 of the Communications Act of 1934, as amended, and subpart I of part 2 of this chapter. The equipment authorization procedures are detailed in subpart J of part 2 of this chapter.

[54 FR 17714, Apr. 25, 1989, as amended at 82 FR 50830, Nov. 2, 2017]

§ 15.3 Definitions.

(a) *Auditory assistance device.* An intentional radiator used to provide auditory assistance communications (including but not limited to applications such as assistive listening, auricular training, audio description for the blind, and simultaneous language translation) for:

(1) Persons with disabilities: In the context of part 15 rules (47 CFR part 15), the term “disability,” with respect to the individual, has the meaning given to it by section 3(2)(A) of the Americans with Disabilities Act of 1990 (42 U.S.C. 12102(2)(A)), *i.e.*, a physical or mental impairment that substantially limits one or more of the major life activities of such individuals;

(2) Persons who require language translation; or

(3) Persons who may otherwise benefit from auditory assistance communications in places of public gatherings, such as a church, theater, auditorium, or educational institution.

(b) *Biomedical telemetry device.* An intentional radiator used to transmit measurements of either human or animal biomedical phenomena to a receiver.

(c) *Cable input selector switch.* A transfer switch that is intended as a means to alternate between the reception of broadcast signals via connection to an antenna and the reception of cable television service.

(d) *Cable locating equipment.* An intentional radiator used intermittently by

trained operators to locate buried cables, lines, pipes, and similar structures or elements. Operation entails coupling a radio frequency signal onto the cable, pipes, etc. and using a receiver to detect the location of that structure or element.

(e) *Cable system terminal device (CSTD)*. A TV interface device that serves, as its primary function, to connect a cable system operated under part 76 of this chapter to a TV broadcast receiver or other subscriber premise equipment. Any device which functions as a CSTD in one of its operating modes must comply with the technical requirements for such devices when operating in that mode.

(f) *Carrier current system*. A system, or part of a system, that transmits radio frequency energy by conduction over the electric power lines. A carrier current system can be designed such that the signals are received by conduction directly from connection to the electric power lines (unintentional radiator) or the signals are received over-the-air due to radiation of the radio frequency signals from the electric power lines (intentional radiator).

(g) *CB receiver*. Any receiver that operates in the Personal Radio Services on frequencies designated for CB Radio Service stations, as well as any receiver provided with a separate band specifically designed to receive the transmissions of CB stations in the Personal Radio Services. This includes the following:

- (1) A CB receiver sold as a separate unit of equipment;
- (2) The receiver section of a CB transceiver;
- (3) A converter to be used with any receiver for the purpose of receiving CB transmissions; and
- (4) A multiband receiver that includes a band labelled “CB” or “11-meter” in which such band can be separately selected, except that an Amateur Radio Service receiver that was manufactured prior to January 1, 1960, and which includes an 11-meter band shall not be considered to be a CB receiver.

(h) *Class A digital device*. A digital device that is marketed for use in a commercial, industrial or business environment, exclusive of a device which is

marketed for use by the general public or is intended to be used in the home.

(i) *Class B digital device*. A digital device that is marketed for use in a residential environment notwithstanding use in commercial, business and industrial environments. Examples of such devices include, but are not limited to, personal computers, calculators, and similar electronic devices that are marketed for use by the general public.

NOTE: The responsible party may also qualify a device intended to be marketed in a commercial, business or industrial environment as a Class B device, and in fact is encouraged to do so, provided the device complies with the technical specifications for a Class B digital device. In the event that a particular type of device has been found to repeatedly cause harmful interference to radio communications, the Commission may classify such a digital device as a Class B digital device, regardless of its intended use.

(j) *Cordless telephone system*. A system consisting of two transceivers, one a base station that connects to the public switched telephone network and the other a mobile handset unit that communicates directly with the base station. Transmissions from the mobile unit are received by the base station and then placed on the public switched telephone network. Information received from the switched telephone network is transmitted by the base station to the mobile unit.

NOTE: The Domestic Public Cellular Radio Telecommunications Service is considered to be part of the switched telephone network. In addition, intercom and paging operations are permitted provided these are not intended to be the primary modes of operation.

(k) *Digital device*. (Previously defined as a computing device). An unintentional radiator (device or system) that generates and uses timing signals or pulses at a rate in excess of 9,000 pulses (cycles) per second and uses digital techniques; inclusive of telephone equipment that uses digital techniques or any device or system that generates and uses radio frequency energy for the purpose of performing data processing functions, such as electronic computations, operations, transformations, recording, filing, sorting, storage, retrieval, or transfer. A radio frequency device that is specifically subject to an emanation requirement in any other

FCC Rule part or an intentional radiator subject to subpart C of this part that contains a digital device is not subject to the standards for digital devices, provided the digital device is used only to enable operation of the radio frequency device and the digital device does not control additional functions or capabilities.

NOTE: Computer terminals and peripherals that are intended to be connected to a computer are digital devices.

(l) *Field disturbance sensor.* A device that establishes a radio frequency field in its vicinity and detects changes in that field resulting from the movement of persons or objects within its range.

(m) *Harmful interference.* Any emission, radiation or induction that endangers the functioning of a radio navigation service or of other safety services or seriously degrades, obstructs or repeatedly interrupts a radiocommunications service operating in accordance with this chapter.

(n) *Incidental radiator.* A device that generates radio frequency energy during the course of its operation although the device is not intentionally designed to generate or emit radio frequency energy. Examples of incidental radiators are dc motors, mechanical light switches, etc.

(o) *Intentional radiator.* A device that intentionally generates and emits radio frequency energy by radiation or induction.

(p) *Kit.* Any number of electronic parts, usually provided with a schematic diagram or printed circuit board, which, when assembled in accordance with instructions, results in a device subject to the regulations in this part, even if additional parts of any type are required to complete assembly.

(q) *Perimeter protection system.* A field disturbance sensor that employs RF transmission lines as the radiating source. These RF transmission lines are installed in such a manner that allows the system to detect movement within the protected area.

(r) *Peripheral device.* An input/output unit of a system that feeds data into and/or receives data from the central processing unit of a digital device. Peripherals to a digital device include any device that is connected external to the digital device, any device inter-

nal to the digital device that connects the digital device to an external device by wire or cable, and any circuit board designed for interchangeable mounting, internally or externally, that increases the operating or processing speed of a digital device, e.g., "turbo" cards and "enhancement" boards. Examples of peripheral devices include terminals, printers, external floppy disk drives and other data storage devices, video monitors, keyboards, interface boards, external memory expansion cards, and other input/output devices that may or may not contain digital circuitry. This definition does not include CPU boards, as defined in paragraph (bb) of this section, even though a CPU board may connect to an external keyboard or other components.

(s) *Personal computer.* An electronic computer that is marketed for use in the home, notwithstanding business applications. Such computers are considered Class B digital devices. Computers which use a standard TV receiver as a display device or meet all of the following conditions are considered examples of personal computers:

(1) Marketed through a retail outlet or direct mail order catalog.

(2) Notices of sale or advertisements are distributed or directed to the general public or hobbyist users rather than restricted to commercial users.

(3) Operates on a battery or 120 volt electrical supply.

If the responsible party can demonstrate that because of price or performance the computer is not suitable for residential or hobbyist use, it may request that the computer be considered to fall outside of the scope of this definition for personal computers.

(t) *Power line carrier systems.* An unintentional radiator employed as a carrier current system used by an electric power utility entity on transmission lines for protective relaying, telemetry, etc. for general supervision of the power system. The system operates by the transmission of radio frequency energy by conduction over the electric power transmission lines of the system. The system does not include those electric lines which connect the distribution substation to the customer or house wiring.

§ 15.3

47 CFR Ch. I (10–1–20 Edition)

(u) *Radio frequency (RF) energy.* Electromagnetic energy at any frequency in the radio spectrum between 9 kHz and 3,000,000 MHz.

(v) *Scanning receiver.* For the purpose of this part, this is a receiver that automatically switches among two or more frequencies in the range of 30 to 960 MHz and that is capable of stopping at and receiving a radio signal detected on a frequency. Receivers designed solely for the reception of the broadcast signals under part 73 of this chapter, for the reception of NOAA broadcast weather band signals, or for operation as part of a licensed service are not included in this definition.

(w) *Television (TV) broadcast receiver.* A device designed to receive television pictures that are broadcast simultaneously with sound on the television channels authorized under part 73 of this chapter.

(x) *Transfer switch.* A device used to alternate between the reception of over-the-air radio frequency signals via connection to an antenna and the reception of radio frequency signals received by any other method, such as from a TV interface device.

(y) *TV interface device.* An unintentional radiator that produces or translates in frequency a radio frequency carrier modulated by a video signal derived from an external or internal signal source, and which feeds the modulated radio frequency energy by conduction to the antenna terminals or other non-baseband input connections of a television broadcast receiver. A TV interface device may include a stand-alone RF modulator, or a composite device consisting of an RF modulator, video source and other components devices. Examples of TV interface devices are video cassette recorders and terminal devices attached to a cable system or used with a Master Antenna (including those used for central distribution video devices in apartment or office buildings).

(z) *Unintentional radiator.* A device that intentionally generates radio frequency energy for use within the device, or that sends radio frequency signals by conduction to associated equipment via connecting wiring, but which is not intended to emit RF energy by radiation or induction.

(aa) *Cable ready consumer electronics equipment.* Consumer electronics TV receiving devices, including TV receivers, videocassette recorders and similar devices, that incorporate a tuner capable of receiving television signals and an input terminal intended for receiving cable television service, and are marketed as “cable ready” or “cable compatible.” Such equipment shall comply with the technical standards specified in §15.118 and the provisions of §15.19(d).

(bb) *CPU board.* A circuit board that contains a microprocessor, or frequency determining circuitry for the microprocessor, the primary function of which is to execute user-provided programming, but not including:

(1) A circuit board that contains only a microprocessor intended to operate under the primary control or instruction of a microprocessor external to such a circuit board; or

(2) A circuit board that is a dedicated controller for a storage or input/output device.

(cc) *External radio frequency power amplifier.* A device which is not an integral part of an intentional radiator as manufactured and which, when used in conjunction with an intentional radiator as a signal source, is capable of amplifying that signal.

(dd) *Test equipment* is defined as equipment that is intended primarily for purposes of performing measurements or scientific investigations. Such equipment includes, but is not limited to, field strength meters, spectrum analyzers, and modulation monitors.

(ee) *Radar detector.* A receiver designed to signal the presence of radio signals used for determining the speed of motor vehicles. This definition does not encompass the receiver incorporated within a radar transceiver certified under the Commission’s rules.

(ff) *Access Broadband over Power Line (Access BPL).* A carrier current system installed and operated on an electric utility service as an unintentional radiator that sends radio frequency energy on frequencies between 1.705 MHz and 80 MHz over medium voltage lines or over low voltage lines to provide broadband communications and is located on the supply side of the utility

Federal Communications Commission

§ 15.3

service's points of interconnection with customer premises. Access BPL does not include power line carrier systems as defined in §15.3(t) or In-House BPL as defined in §15.3(gg).

(gg) *In-House Broadband over Power Line (In-House BPL)*. A carrier current system, operating as an unintentional radiator, that sends radio frequency energy by conduction over electric power lines that are not owned, operated or controlled by an electric service provider. The electric power lines may be aerial (overhead), underground, or inside the walls, floors or ceilings of

user premises. In-House BPL devices may establish closed networks within a user's premises or provide connections to Access BPL networks, or both.

(hh) *Slant-Range distance*. Diagonal distance measured from the center of the measurement antenna to the nearest point of the overhead power line carrying the Access BPL signal being measured. This distance is equal to the hypotenuse of the right triangle as calculated in the formula below. The slant-range distance shall be calculated as follows:

$$d_{slant} = \sqrt{(h_{pwr_line} - h_{ant})^2 + (d_h)^2}$$

Where:

d_{slant} is the slant-range distance, in meters (see Figure 1, below);

d_h is the horizontal (lateral) distance between the center of the measurement antenna and the vertical projection of the

overhead power line carrying the BPL signals down to the height of the measurement antenna, in meters;

h_{pwr_line} is the height of the power line, in meters; and

h_{ant} is the measurement antenna height, in meters.

Figure 1 – Illustration of Slant-Range Distance

