§24.9

Fixed Station. A station in the fixed service.

Land Mobile Service. A mobile service between base stations and land mobile stations, or between land mobile stations.

Land Mobile Station. A mobile station in the land mobile service capable of surface movement within the geographic limits of a country or continent.

Land Station. A station in the mobile service not intended to be used while in motion.

Mobile Service. A radiocommunication service between mobile and land stations, or between mobile stations.

Mobile Station. A station in the mobile service intended to be used while in motion or during halts at unspecified points.

Narrowband PCS. PCS services operating in the 901-902 MHz, 930-931 MHz, and 940-941 MHz bands.

National Geodetic Reference System (NGRS): The name given to all geodetic control data contained in the National Geodetic Survey (NGS) data base. (Source: National Geodetic Survey, U.S. Department of Commerce)

PCS Relocator. A PCS entity that pays to relocate a fixed microwave link from its existing 2 GHz facility to other media or other fixed channels.

Personal Communications Services (PCS). Radio communications that encompass mobile and ancillary fixed communication that provide services to individuals and businesses and can be integrated with a variety of competing networks.

Universal Licensing System. The Universal Licensing System (ULS) is the consolidated database, application filing system, and processing system for all Wireless Radio Services. ULS supports electronic filing of all applications and related documents by applicants and licensees in the Wireless Radio Services, and provides public access to licensing information.

UTAM. The Unlicensed PCS Ad Hoc Committee for 2 GHz Microwave Transition and Management, which coordinates relocation in the 1910–1930 MHz band.

Voluntarily Relocating Microwave Incumbent A microwave incumbent that voluntarily relocates its licensed facilities to other media or fixed channels.

[58 FR 59183, Nov. 8, 1993. Redesignated at 59 FR 18499, Apr. 19, 1994, and amended at 61 FR 29691, June 12, 1996; 62 FR 12757, Mar. 18, 1997; 63 FR 68952, Dec. 14, 1998]

§24.9 Operation of certificated signal boosters.

Individuals and non-individuals may operate certificated Consumer Signal Boosters on frequencies regulated under this part provided that such operation complies with all applicable rules under this part and §20.21 of this chapter. Failure to comply with all applicable rules voids the authority to operate a signal booster.

[78 FR 21564, Apr. 11, 2013]

Subpart B—Applications and Licenses

GENERAL FILING REQUIREMENTS

§24.10 Scope.

This subpart contains some of the procedures and requirements for filing applications for licenses in the personal communications services. One also should consult subparts F and G of this part. Other Commission rule parts of importance that may be referred to with respect to licensing and operation of radio services governed under this part include 47 CFR parts 0, 1, 2, 5, 15, 17 and 20.

[59 FR 32854, June 24, 1994]

§24.11 Initial authorization.

(a) An applicant must file a single application for an initial authorization for all markets won and frequency blocks desired.

(b) Blanket licenses are granted for each market and frequency block. Applications for individual sites are not required and will not be accepted.

[59 FR 32854, June 24, 1994, as amended at 63 FR 68952, Dec. 14, 1998]

§24.12 Eligibility.

Any entity, other than those precluded by section 310 of the Communications Act of 1934, as amended, 47

Federal Communications Commission

U.S.C. 310, is eligible to hold a license under this part.

[70 FR 61059, Oct. 20, 2005]

§24.15 License period.

Licenses for service areas will be granted for ten year terms from the date of original issuance or renewal.

Subpart C—Technical Standards

§24.50 Scope.

This subpart sets forth the technical requirements for use of the spectrum and equipment in the personal communications services.

§24.51 Equipment authorization.

(a) Each transmitter utilized for operation under this part and each transmitter marketed, as set forth in §2.803 of this chapter, must be of a type that has been authorized by the Commission under its certification procedure for use under this part.

(b) Any manufacturer of radio transmitting equipment to be used in these services may request equipment authorization following the procedures set forth in subpart J of part 2 of this chapter. Equipment authorization for an individual transmitter may be requested by an applicant for a station authorization by following the procedures set forth in part 2 of this chapter.

[58 FR 59183, Nov. 8, 1993. Redesignated at 59
FR 18499, Apr. 19, 1994, as amended at 63
FR 36604, July 7, 1998; 85
FR 18150, Apr. 1, 2020]

§24.52 RF exposure.

Licensees and manufacturers shall ensure compliance with the Commission's radio frequency exposure requirements in §§1.1307(b), 2.1091, and 2.1093 of this chapter, as appropriate. Applications for equipment authorization of mobile or portable devices operating under this section must contain a statement confirming compliance with these requirements. Technical information showing the basis for this statement must be submitted to the Commission upon request.

[85 FR 18150, Apr. 1, 2020]

§24.53 Calculation of height above average terrain (HAAT).

(a) HAAT is determined by subtracting average terrain elevation from antenna height above mean sea level.

(b) Average terrain elevation shall be calculated using elevation data from a 30 arc second or better Digital Elevation Models (DEMs). DEM data is available from United States Geological Survey (USGS). The data file shall be identified. If 30 arc second data is used, the elevation data must be processed for intermediate points using interpolation techniques; otherwise, the nearest point may be used. If DEM data is not available, elevation data from the Defense Mapping Agency's Digital Chart of the World (DCW) may be used.

(c) Radial average terrain elevation is calculated as the average of the elevation along a straight line path from 3 to 16 kilometers extending radially from the antenna site. At least 50 evenly spaced data points for each radial shall be used in the computation.

(d) Average terrain elevation is the average of the eight radial average terrain elevations (for the eight cardinal radials).

(e) The position location of the antenna site shall be determined to an accuracy of no less than ± 5 meters in both the horizontal (latitude and longitude) and vertical (ground elevation) dimensions with respect to the National Geodetic Reference System.

 $[58\ {\rm FR}\ 59183,\ {\rm Nov.}\ 8,\ 1993;\ 59\ {\rm FR}\ 15269,\ {\rm Mar.}\ 31,\ 1994]$

§24.55 Antenna structures; air navigation safety.

Licensees that own their antenna structures must not allow these antenna structures to become a hazard to air navigation. In general, antenna structure owners are responsible for registering antenna structures with the FCC if required by part 17 of this chapter, and for installing and maintaining any required marking and lighting. However, in the event of default of this responsibility by an antenna structure owner, each FCC permittee or licensee authorized to use an affected antenna structure will be held responsible by the FCC for ensuring that the antenna structure continues