§§ 25.229-25.249

47 CFR Ch. I (10-1-20 Edition)

TABLE 1 TO § 25.228(j)(3)—APPLICABLE RADIO ASTRONOMY SERVICE (RAS) FACILITIES AND ASSOCIATED COORDINATION DISTANCES—Continued

Observatory	Latitude	Longitude	Radius (km) of
	(north)	(west)	coordination zone
St. Croix, VI	17°45′24″	64°35′01″	50.

*Owens Valley, CA operates both a VLBA station and single-dish telescopes.

(4) When NTIA seeks to provide similar protection to future RAS sites that have been coordinated through the IRAC Frequency Assignment Subcommittee process, NTIA will notify the Commission's International Bureau that the site is nearing operational status. Upon public notice from the International Bureau, all Ku-band ESIMs licensees must cease operations in the 14.47–14.5 GHz band within the relevant geographic zone (160 kms for singledish radio observatories and Verv Large Array antenna systems and 50 kms for Very Long Baseline Array antenna systems for ESVs and VMESs, radio line of sight for ESAAs) of the new RAS site until the licensees complete coordination for the new RAS facility. Licensees must notify the International Bureau once they have completed coordination for the new RAS site and must submit the coordination agreement to the Commission. Upon receipt of such notification from a licensee, the International Bureau will issue a public notice stating that the licensee may commence operations within the coordination zone in 30 days if no party opposed the operations. The ESIMs licensee then will be permitted to commence operations in the 14.47-14.5 GHz band within the relevant coordination distance around the new RAS site, subject to any operational constraints developed in the coordination process.

(5) ESIMs licensees must use Global Positioning Satellite-related or other similar position location technology to ensure compliance with the provisions of subparagraphs 1–3 of this paragraph.

[84 FR 53656, Oct. 8, 2019, as amended at 85 FR 44787, July 24, 2020]

§§ 25.229-25.249 [Reserved]

§25.250 Sharing between NGSO MSS Feeder links Earth Stations in the 19.3–19.7 GHz and 29.1–29.5 GHz Bands.

(a) NGSO MSS applicants shall be licensed to operate in the 29.1–29.5 GHz band for Earth-to-space transmissions and 19.3–19.7 GHz for space-to-Earth transmissions from feeder link earth station complexes. A "feeder link earth station complex" may include up to three (3) earth station groups, with each earth station group having up to four (4) antennas, located within a radius of 75 km of a given set of geographic coordinates provided by NGSO-MSS licensees or applicants.

(b) Licensees of NGSO MSS feeder link earth stations separated by 800 km or less are required to coordinate their operations, see §25.203. The results of the coordination shall be reported to the Commission.

[61 FR 44181, Aug. 28, 1996]

§25.251 Special requirements for coordination.

(a) The administrative aspects of the coordination process are set forth in \$101.103 of this chapter in the case of coordination of terrestrial stations with earth stations, and in \$25.203 in the case of coordination of earth stations with terrestrial stations.

(b) The technical aspects of coordination are based on Appendix 7 of the International Telecommunication Union Radio Regulations and certain recommendations of the ITU Radiocommunication Sector (available at the address in §0.445 of this chapter).

[66 FR 10630, Feb. 16, 2001, as amended at 78 FR 8430, Feb. 6, 2013]