

(2) If a pre-existing BRS base station suffers harmful interference from emissions caused by a new or modified ATC base station located 1.5 km or more away, within 24 hours of the receipt of a documented interference complaint the ATC licensee must attenuate its emissions by at least $67 + 10 \log(P)$ dB measured at 3 megahertz above the edge of the authorized ATC band, and shall immediately notify the complaining licensee upon implementation of the additional attenuation.

(3) If a pre-existing BRS base station suffers harmful interference from emissions caused by a new or modified ATC base station located less than 1.5 km away, within 24 hours of the receipt of a documented interference complaint the ATC licensee must attenuate its emissions by at least $67 + 10 \log(P) - 20 \log(D_{km}/1.5)$ dB measured at 3 megahertz above the edge of the authorized ATC band, or if both base stations are co-located, limit its undesired signal level at the pre-existing BRS base station receiver(s) to no more than -107 dBm measured in a 5.5 megahertz bandwidth and shall immediately notify the complaining licensee upon such reduction in the undesired signal level.

(4) If a new or modified BRS base station suffers harmful interference from emissions caused by a pre-existing ATC base station located 1.5 km or more away, within 60 days of receipt of a documented interference complaint the licensee of the ATC base station must attenuate its base station emissions by at least $67 + 10 \log(P)$ dB measured at 3 megahertz above the edge of the authorized ATC band.

(5) If a new or modified BRS base station suffers harmful interference from emissions caused by a pre-existing ATC base station located less than 1.5 km away, within 60 days of receipt of a documented interference complaint:

(i) the ATC licensee must attenuate its base station emissions by at least $67 + 10 \log(P) - 20 \log(D_{km}/1.5)$ dB measured 3 megahertz above the edge of the authorized ATC band, or

(ii) if both base stations are co-located, the ATC licensee must limit its undesired signal level at the new or modified BRS base station receiver(s) to no more than -107 dBm measured in a 5.5 megahertz bandwidth.

(6) Compliance with these rules is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately above and adjacent to the 2495 MHz a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. A narrower resolution bandwidth is permitted in all cases to improve measurement accuracy, provided the measured power is integrated over the full required measurement bandwidth (i.e., 1 MHz or 1 percent of emission bandwidth, as specified). The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power. When an emission outside of the authorized bandwidth causes harmful interference, the Commission may, at its discretion, require greater attenuation than specified in this section.

(e) Licensees of terrestrial low-power systems operating in the 2483.5–2495 MHz band shall operate consistent with the technical limits and other requirements specified in § 25.149(c)(4) and (g)(2)–(3).

NOTE TO § 25.254: The preceding rules of § 25.254 are based on cdma2000 and IS-95 system architecture. To the extent that a 1.6/2.4 GHz Mobile-Satellite Service licensee is able to demonstrate that the use of different system architectures would produce no greater potential interference than would be produced as a result of implementing the rules of this section, the licensee may apply for ATC authorization based on another system architecture.

[68 FR 33653, June 5, 2003, as amended at 69 FR 18803, Apr. 9, 2004; 70 FR 19320, Apr. 13, 2005; 73 FR 25592, May 5, 2008; 78 FR 8430, Feb. 6, 2013; 82 FR 8819, Jan. 31, 2017]

§ 25.255 Procedures for resolving harmful interference related to operation of ancillary terrestrial components operating in the 1.5/1.6 GHz and 1.6/2.4 GHz bands.

If harmful interference is caused to other services by ancillary MSS ATC operations, either from ATC base stations or mobile terminals, the MSS ATC operator must resolve any such

§ 25.256

interference. If the MSS ATC operator claims to have resolved the interference and other operators claim that interference has not been resolved, then the parties to the dispute may petition the Commission for a resolution of their claims.

[68 FR 33653, June 5, 2003, as amended at 78 FR 8267, Feb. 5, 2013]

§ 25.256 Special Requirements for operations in the 3.65–3.7 GHz band.

Upon request from a terrestrial licensee authorized under subpart Z, part 90 that seeks to place base and fixed stations in operation within 150 km of a primary earth station, licensees of earth stations operating on a primary basis in the Fixed-Satellite Service in the 3.65–3.7 GHz band must negotiate in good faith with that terrestrial licensee to arrive at mutually agreeable operating parameters to prevent unacceptable interference.

[70 FR 24725, May 11, 2005, as amended at 78 FR 8430, Feb. 6, 2013]

§ 25.257 Special requirements for NGSO MSS operations in the 29.1–29.25 GHz band regarding LMDS.

(a) Non-geostationary Mobile-Satellite Service (NGSO MSS) operators shall be licensed to use the 29.1–29.25 GHz band for Earth-to-space transmissions from feeder link earth station complexes. A “feeder link earth station complex” may include up to three (3) earth station groups, with each earth station group having up to four (4) antennas, located within a radius of 75 km of a given set of geographic coordinates provided by a NGSO MSS licensee or applicants pursuant to §101.147.

(b) A maximum of seven (7) feeder link earth station complexes in the contiguous United States, Alaska and Hawaii may be placed into operation, in the largest 100 MSAs, in the band 29.1–29.25 GHz in accordance with §25.203 and §101.147 of this chapter.

(c) One of the NGSO MSS operators licensed to use the 29.1–29.25 GHz band may specify geographic coordinates for a maximum of eight feeder link earth station complexes that transmit in the 29.1–29.25 GHz band. The other NGSO MSS operator licensed to use the 29.1–29.25 GHz band may specify geographic coordinates for a maximum of two

47 CFR Ch. I (10–1–20 Edition)

feeder link earth station complexes that transmit in the 29.1–29.25 GHz band.

(d) Additional NGSO MSS operators may be licensed in this band if the additional NGSO MSS operator shows that its system can share with the existing NGSO MSS systems.

(e) All NGSO MSS operators shall cooperate fully and make reasonable efforts to identify mutually acceptable locations for feeder link earth station complexes. In this regard, any single NGSO MSS operator may identify only one feeder-link earth station complex protection zone in each category identified in §101.147(y)(2) of this chapter until the other NGSO MSS operator has been given an opportunity to select a location from the same category.

[61 FR 44181, Aug. 28, 1996, as amended at 78 FR 8430, Feb. 6, 2013; 81 FR 55348, Aug. 18, 2016]

§ 25.258 Sharing between NGSO MSS feeder-link stations and GSO FSS services in the 29.25–29.5 GHz band.

(a) Operators of NGSO MSS feeder link earth stations and GSO FSS earth stations in the band 29.25 to 29.5 GHz where both services have a co-primary allocation shall cooperate fully in order to coordinate their systems. During the coordination process both service operators shall exchange the necessary technical parameters required for coordination.

(b) Licensed GSO FSS earth stations in the vicinity of operational NGSO MSS feeder-link earth station complexes must, to the maximum extent possible, operate with frequency/polarization selections that will minimize unacceptable interference with reception of GSO FSS and NGSO MSS uplink transmissions in the 29.25–29.5 GHz band. Earth station licensees operating with GSO FSS systems shall be capable of providing earth station locations to support coordination of NGSO MSS feeder link stations under paragraphs (a) and (c) of this section. Operation of ubiquitously deployed GSO FSS earth stations in the 29.25–29.5 GHz frequency band must conform to the rules contained in §25.218(i).

(c) Applicants for authority to use the 29.25–29.5 GHz band for NGSO MSS