

§ 74.882

- (iii) Antenna height.
- (iv) Emission type(s).
- (v) Effective radiated power.
- (vi) Intended dates of operation.
- (vii) Licensee contact information.

(3)(i) Failure of a local coordinator to respond to a notification request prior to the intended dates of operation indicated on the request will be considered as having the approval of the coordinator. In this case, licensees must in addition notify all co-channel and adjacent channel TV stations within 161 km (100 mi) of the proposed operating area. This notification is for information purposes only and will not enable TV stations to prevent a WAVD from operating, but is intended to help identify the source of interference if any is experienced after a WAVD begins operation.

(ii) If there is no local coordinator in the intended area of operation, failure of any adjacent channel TV station to respond to a notification request prior to the intended dates of operation indicated on the request will be considered as having the approval of the TV station.

(4) Licensees must operate in a manner consistent with the response of the local coordinator, or, if there is no local coordinator in the intended area of operation, the responses of the adjacent channel TV stations. Disagreements may be appealed to the Commission. However, in those instances, the licensee will bear the burden of proof and proceeding to overturn the recommendation of the local coordinator or the co-channel or adjacent channel TV station.

(h) Licenses for wireless video assist devices may not be transferred or assigned.

(i) *Operations in 600 MHz band assigned to wireless licensees under part 27 of this chapter.* A wireless video assist device that operates on frequencies in the 600 MHz band assigned to wireless licensees under part 27 of this chapter must cease operations on those frequencies no later than the end of the post-auction transition period as defined in §27.4 of this chapter. During the post-auction transition period, wireless video assist devices will operate on a secondary basis to licensees of part 27 of this chapter, *i.e.*, they must

47 CFR Ch. I (10–1–20 Edition)

not cause to and must accept harmful interference from these licensees.

[68 FR 12772, Mar. 17, 2003, as amended at 68 FR 69331, Dec. 12, 2003; 79 FR 48545, Aug. 15, 2014]

§ 74.882 Station identification.

(a) For transmitters used for voice transmissions and having a transmitter output power exceeding 50 mW, an announcement shall be made at the beginning and end of each period of operation at a single location, over the transmitting unit being operated, identifying the transmitting unit's call sign or designator, its location, and the call sign of the broadcasting station or name of the licensee with which it is being used. A period of operation may consist of a continuous transmission or intermittent transmissions pertaining to a single event.

(b) Each wireless video assist device, when transmitting, must transmit station identification at the beginning and end of each period of operation. Identification may be made by transmitting the station call sign by visual or aural means or by automatic transmission in international Morse telegraphy.

(1) A period of operation is defined as a single uninterrupted transmission or a series of intermittent transmissions from a single location.

(2) Station identification shall be performed in a manner conducive to prompt association of the signal source with the responsible licensee. In exercising the discretion provided by this rule, licensees are expected to act in a responsible manner to assure that result.

[68 FR 12774, Mar. 17, 2003]

Subparts I–K [Reserved]

Subpart L—FM Broadcast Translator Stations and FM Broadcast Booster Stations

SOURCE: 35 FR 15388, Oct. 2, 1970, unless otherwise noted.

§ 74.1201 Definitions.

(a) *FM translator.* A station in the broadcasting service operated for the purpose of retransmitting the signals

of an AM or FM radio broadcast station or another FM broadcast translator station without significantly altering any characteristics of the incoming signal other than its frequency and amplitude, in order to provide radio broadcast service to the general public.

(b) *Commercial FM translator.* An FM broadcast translator station which rebroadcasts the signals of a commercial AM or FM radio broadcast station.

(c) *Noncommercial FM translator.* An FM broadcast translator station which rebroadcasts the signals of a noncommercial educational AM or FM radio broadcast station.

(d) *Primary station.* The AM or FM radio broadcast station radiating the signals which are retransmitted by an FM broadcast translator station or an FM broadcast booster station.

(e) *AM or FM radio broadcast station.* When used in this Subpart L, the term AM broadcast station or AM radio broadcast station or FM broadcast station or FM radio broadcast station refers to commercial and noncommercial educational AM or FM radio broadcast stations as defined in § 2.1 of this chapter, unless the context indicates otherwise.

(f) *FM broadcast booster station.* A station in the broadcasting service operated for the sole purpose of retransmitting the signals of an FM radio broadcast station, by amplifying and reradiating such signals, without significantly altering any characteristic of the incoming signal other than its amplitude. Unless specified otherwise, this term includes LPFM boosters as defined in paragraph (1) of this section.

(g) *Translator coverage contour.* For a fill-in FM translator rebroadcasting an FM radio broadcast station as its primary station, the FM translator's coverage contour must be contained within the primary station's coverage contour. For purposes of this rule section, the coverage contour of the FM translator has the same field strength value as the protected contour of the primary FM station (*i.e.*, for a commercial Class B FM station it is the predicted 0.5 mV/m field strength contour, for a commercial Class B1 FM station it is the predicted 0.7 mV/m field strength contour, and for all other classes of FM

stations it is the predicted 1 mV/m field strength contour). The coverage contour of an FM translator rebroadcasting an AM radio broadcast station as its primary station must be contained within the greater of either the 2 mV/m daytime contour of the AM station or a 25-mile (40 km) radius centered at the AM transmitter site. The protected contour for an FM translator station is its predicted 1 mV/m contour.

(h) *Fill-in area.* The area where the coverage contour of an FM translator or booster station is within the protected contour of the associated primary station (*i.e.*, predicted 0.5 mV/m contour for commercial Class B stations, predicted 0.7 mV/m contour for commercial Class B1 stations, and predicted 1 mV/m contour for all other classes of stations).

(i) *Other area.* The area where the coverage contour of an FM translator station extends beyond the protected contour of the primary station (*i.e.*, predicted 0.5 mV/m contour for commercial Class B stations, predicted 0.7 mV/m contour for commercial Class B1 stations, and predicted 1 mV/m contour for all other classes of stations).

(j) *AM Fill-in area.* The area within the lesser of the 2 mV/m daytime contour of the AM radio broadcast station being rebroadcast and a 25-mile (40 km) radius centered at the AM transmitter site.

(k) *Listener complaint.* A statement that is signed and dated by the listener and contains the following information:

(1) The complainant's full name, address, and phone number;

(2) A clear, concise, and accurate description of the location where interference is alleged or predicted to occur;

(3) A statement that the complainant listens over-the-air to the desired station at least twice a month; and

(4) A statement that the complainant has no legal, financial, employment, or familial affiliation or relationship with the desired station.

(1) *LPFM booster.* An FM broadcast booster station as defined in paragraph (f) of this section that is commonly-

§ 74.1202

owned by an LPFM station for the purpose of retransmitting the signals of the commonly-owned LPFM station.

[35 FR 15388, Oct. 2, 1970, as amended at 45 FR 37842, June 5, 1980; 52 FR 31405, Aug. 20, 1987; 55 FR 50693, Dec. 10, 1990; 74 FR 45129, Sept. 1, 2009; 82 FR 13072, Mar. 9, 2017; 84 FR 27740, June 14, 2019; 85 FR 35574, June 11, 2020]

EFFECTIVE DATE NOTE: At 82 FR 13072, Mar. 9, 2017, § 74.1201 was amended by revising the last two sentences of paragraph (g), effective Apr. 10, 2017. At 82 FR 13069, Mar. 9, 2017, the effective date was delayed indefinitely pending Office of Management and Budget approval of a nonsubstantive change in the rule as originally proposed.

§ 74.1202 Frequency assignment.

(a) An applicant for a new FM broadcast translator station or for changes in the facilities of an authorized translator station shall endeavor to select a channel on which its operation is not likely to cause interference to the reception of other stations. The application must be specific with regard to the frequency requested. Only one output channel will be assigned to each translator station.

(b) Subject to compliance with all the requirements of this subpart, FM broadcast translators may be authorized to operate on the following FM channels, regardless of whether they are assigned for local use in the FM Table of Allotments (§ 73.202(b) of this chapter):

(1) *Commercial FM translators*: Channels 221–300 as identified in § 73.201 of this chapter.

(2) *Noncommercial FM translators*: Channels 201–300 as identified in § 73.201 of this chapter. Use of reserved channels 201–220 is subject to the restrictions specified in § 73.501 of this chapter.

(3) In Alaska, FM translators operating on Channels 201–260 (88.1–99.9 MHz) shall not cause harmful interference to and must accept interference from non-Government fixed operations authorized prior to January 1, 1982.

47 CFR Ch. I (10–1–20 Edition)

(c) An FM broadcast booster station will be assigned the channel assigned to its primary station.

[35 FR 15388, Oct. 2, 1970, as amended at 39 FR 12990, Apr. 10, 1974; 47 FR 30068, July 12, 1982; 52 FR 8260, Mar. 17, 1987; 55 FR 50693, Dec. 10, 1990]

§ 74.1203 Interference.

(a) An authorized FM translator or booster station will not be permitted to continue to operate if it causes any actual interference to:

(1) The transmission of any authorized broadcast station; or

(2) The reception of the input signal of any TV translator, TV booster, FM translator or FM booster station; or

(3) The direct reception by the public of the off-the-air signals of any full-service station or previously authorized secondary station. Interference will be considered to occur whenever reception of a regularly used signal is impaired by the signals radiated by the FM translator or booster station, regardless of the channel on which the protected signal is transmitted; except that no listener complaint will be considered actionable if the alleged interference occurs outside the desired station's 45 dBu contour. Interference is demonstrated by:

(i) The required minimum number of valid listener complaints as determined using Table 1 of this section and defined in § 74.1201(k) of the part;

(ii) A map plotting the specific location of the alleged interference in relation to the complaining station's 45 dBu contour;

(iii) A statement that the complaining station is operating within its licensed parameters;

(iv) A statement that the complaining station licensee has used commercially reasonable efforts to inform the relevant translator licensee of the claimed interference and attempted private resolution; and

(v) U/D data demonstrating that at each listener location the undesired to desired signal strength exceeds –20 dB for co-channel situations, –6 dB for first-adjacent channel situations or 40 dB for second- or third-adjacent channel situations, calculated using the Commission's standard contour prediction methodology set out in § 73.313.