

Federal Communications Commission

§ 74.682

in paragraph (f) of this section, by following the procedures set forth in subpart J of part 2 of this chapter.

(f) Transmitters designed to be used exclusively for a TV STL station, a TV intercity relay station, a TV translator relay station, or a TV microwave booster station, shall be authorized under Supplier's Declaration of Conformity. All other transmitters will be authorized under the certification procedure.

[63 FR 36605, July 7, 1998, as amended at 68 FR 12772, Mar. 17, 2003; 82 FR 50836, Nov. 2, 2017]

§ 74.661 Frequency tolerance.

Stations in this service shall maintain the carrier frequency of each authorized transmitter to within the following percentage of the assigned frequency.

TABLE 1 TO § 74.661

Frequency band (MHz)	Frequency tolerance (%)
2,025 to 2,110	¹ 0.005
2,450 to 2,483.5	² 0.001
6,425 to 6,525	0.005
6,875 to 7,125	¹ 0.005
12,700 to 13,250	¹ 0.005
17,700 to 18,820	0.003
18,920 to 19,700	0.003

¹Television translator relay stations shall maintain a frequency tolerance of 0.002%.

²Stations licensed pursuant to an application filed before March 17, 2005, for tolerance values exceeding those specified above, may continue to operate indefinitely in accordance with the terms of their current authorizations, subject to periodic renewal. Existing equipment and equipment of product lines in production before April 16, 2003, authorized via certification or Declaration of Conformity before March 17, 2005, for tolerance values exceeding those specified above, may continue to be manufactured and/or marketed, but may not be authorized for use under station license except at stations licensed pursuant to an application filed before March 17, 2005. Any non-conforming equipment authorized under a station license, and replaced on or after March 17, 2005, must be replaced by conforming equipment.

NOTE 1 TO § 74.661: The Declaration of Conformity procedure has been replaced by Supplier's Declaration of Conformity. See § 2.950 of this chapter.

[52 FR 7143, Mar. 9, 1987, as amended at 68 FR 12772, Mar. 17, 2003; 82 FR 50836, Nov. 2, 2017]

§ 74.662 Frequency monitors and measurements.

The licensee of a television broadcast auxiliary station must provide means for measuring the operating frequency

in order to ensure that the emissions are confined to the authorized channel.

[48 FR 38482, Aug. 24, 1983]

§ 74.663 Modulation limits.

If amplitude modulation is employed, negative modulation peaks shall not exceed 100%.

[45 FR 78694, Nov. 26, 1980]

§ 74.682 Station identification.

(a) Each television broadcast auxiliary station operating with a transmitter output power of 1 watt or more must, when actually transmitting programs, transmit station identification at the beginning and end of each period of operation, and hourly, as close to the hour as feasible, at a natural break in program offerings by one of the following means:

(1) Transmission of its own call sign by visual or aural means or by automatic transmission in international Morse telegraphy.

(2) Visual or aural transmission of the call sign of the TV broadcast station with which it is licensed as an auxiliary.

(3) Visual or aural transmission of the call sign of the TV broadcast station whose signals are being relayed or, where programs are obtained directly from network lines and relayed, the network identification.

(b) Identification transmissions during operation need not be made when to make such transmission would interrupt a single consecutive speech, play, religious service, symphony concert, or any type of production. In such cases, the identification transmission shall be made at the first interruption of the entertainment continuity and at the conclusion thereof.

(c) During occasions when a television pickup station is being used to deliver program material for network distribution it may transmit the network identification in lieu of its own or associated TV station call sign during the actual program pickup. However, if it is providing the network feed

through its own associated TV broadcast station it shall perform the station identification required by paragraph (a) of this section at the beginning and end of each period of operation.

(d) A period of operation is defined as a single uninterrupted transmission or a series of intermittent transmissions from a single location or continuous or intermittent transmission from a television pickup station covering a single event from various locations, within a single broadcast day.

(e) Regardless of the method used for station identification it shall be performed in a manner conducive to prompt association of the signal source with the responsible licensee. In exercising the discretion provided by this rule, licensees are expected to act in a responsible manner to assure that result.

(f) TV microwave booster stations will be assigned individual call signs. However, station identification will be accomplished by the retransmission of identification as provided in paragraph (a) of this section.

[31 FR 15488, Dec. 8, 1966; 32 FR 452, Jan. 17, 1967, as amended at 42 FR 36830, July 18, 1977; 43 FR 1951, Jan. 13, 1978; 44 FR 36041, June 20, 1979; 49 FR 7131, Feb. 27, 1984]

§ 74.690 Transition of the 1990–2025 MHz band from the Broadcast Auxiliary Service to emerging technologies.

(a) New Entrants are collectively defined as those licensees proposing to use emerging technologies to implement Mobile Satellite Services in the 2000–2020 MHz band (MSS licensees), those licensees authorized after July 1, 2004 to implement new Fixed and Mobile services in the 1990–1995 MHz band, and those licensees authorized after September 9, 2004 in the 1995–2000 MHz and 2020–2025 MHz bands. New entrants may negotiate with Broadcast Auxiliary Service licensees operating on a primary basis and fixed service licensees operating on a primary basis in the 1990–2025 MHz band (Existing Licensees) for the purpose of agreeing to terms under which the Existing Licensees would relocate their operations to the 2025–2110 MHz band, to other authorized bands, or to other media; or,

alternatively, would discontinue use of the 1990–2025 MHz band. New licensees in the 1995–2000 MHz and 2020–2025 MHz bands are subject to the specific relocation procedures adopted in WT Docket 04–356.

(b) An Existing Licensee in the 1990–2025 MHz band allocated for licensed emerging technology services will maintain primary status in the band until the Existing Licensee's operations are relocated by a New Entrant, are discontinued under the terms of paragraph (a) of this section, or become secondary under the terms of paragraph (e)(6) of this section or the Existing Licensee indicates to a New Entrant that it declines to be relocated.

(c) The Commission will amend the operating license of the Existing Licensee to secondary status only if the following requirements are met:

(1) The service applicant, provider, licensee, or representative using an emerging technology guarantees payment of all relocation costs, including all engineering, equipment, site and FCC fees, as well as any reasonable additional costs that the relocated Existing Licensee might incur as a result of operation in another authorized band or migration to another medium;

(2) The New Entrant completes all activities necessary for implementing the replacement facilities, including engineering and cost analysis of the relocation procedure and, if radio facilities are used, identifying and obtaining, on the incumbents' behalf, new microwave or Local Television Transmission Service frequencies and frequency coordination.

(3) The New Entrant builds the replacement system and tests it for comparability with the existing system.

(d) The Existing Licensee is not required to relocate until the alternative facilities are available to it for a reasonable time to make adjustments, determine comparability, and ensure a seamless handoff. If, within one year after the relocation to new facilities the Existing Licensee demonstrates that the new facilities are not comparable to the former facilities, the New Entrant must remedy the defects.