

**§ 80.1017**

the vessel, and accessible with not less than 26 cm (10 in.) head room.

(c) Means must be provided for adequately charging any rechargeable batteries used in the vessel's bridge-to-bridge radiotelephone installation. There must be provided a device which will give a continuous indication of the charging current during charging.

[51 FR 31213, Sept. 2, 1986, as amended at 58 FR 44954, Aug. 25, 1993]

**§ 80.1017 Antenna system.**

(a) An antenna must be provided for nonportable bridge-to-bridge radiotelephone installations which is non-directional and vertically polarized. The construction and installation of this antenna must insure proper operation in time of an emergency.

(b) In cases where portable bridge-to-bridge equipment is permanently associated with a vessel, the equipment must be provided with a connector for an external antenna of a type capable of meeting requirements of paragraph (a) of this section and § 80.71. The vessel must be equipped with an external antenna meeting requirements of paragraph (a) of this section and § 80.71, capable of use with the portable equipment during a normal listening watch.

**§ 80.1019 Antenna radio frequency indicator.**

Each nonportable bridge-to-bridge transmitter must be equipped, at each point of control, with a carrier operated device which will provide continuous visual indication when the transmitter is supplying power to the antenna transmission line or, in lieu thereof, a pilot lamp or meter which will provide continuous visual indication when the transmitter control circuits have been placed in a condition to activate the transmitter.

[52 FR 35246, Sept. 18, 1987]

**§ 80.1021 Nameplate.**

A durable nameplate must be mounted on the required radiotelephone or be an integral part of it. When the transmitter and receiver comprise a single unit, one nameplate is sufficient. The nameplate must show at least the name of the manufacturer and the type or model number.

**§ 80.1023 Test of radiotelephone installation.**

Unless normal use of the required radiotelephone installation demonstrates that the equipment is in proper operating condition, a test communication for this purpose must be made by a qualified operator each day the vessel is navigated. If the equipment is not in proper operating condition, the master must be promptly notified. The master must have it restored to effective operating condition as soon as possible.

**Subpart V—Emergency Position Indicating Radiobeacons (EPIRB's)****§ 80.1051 Scope.**

This subpart describes the technical and performance requirements for EPIRB stations.

[73 FR 4488, Jan. 25, 2008]

**§ 80.1053 Prohibition on certification, manufacture, importation, sale or use of Class A, Class B, Class S, and INMARSAT-E EPIRBs.**

The manufacture, importation, sale or use of Class A, Class B, Class S, or INMARSAT-E EPIRBs is prohibited. New Class A, Class B, Class S, or INMARSAT-E EPIRBs will no longer be certified by the Commission.

[81 FR 90748, Dec. 15, 2016]

**§§ 80.1055–80.1059 [Reserved]****§ 80.1061 Special requirements for 406.0–406.1 MHz EPIRB stations.**

(a) Notwithstanding the provisions in paragraph (b) of this section, 406.0–406.1 MHz EPIRBs must meet all the technical and performance standards contained in RTCM 11000 (incorporated by reference, *see* § 80.7), and must also comply with the standards specified in § 80.1101(c)(5). Beginning January 17, 2018, all new applications for certification of 406.0–406.1 MHz EPIRBs must demonstrate compliance with the requirements of RTCM 11000. 406.0–406.1 MHz EPIRBs that do not meet the requirements of RTCM 11000 shall not be manufactured, imported, or sold in the United States beginning January 17, 2020. Operation of 406.0–406.1 MHz