partitionee shall operate on a secondary, non-interference basis to stations licensed as of March 13, 2002 other than the earliest licensee. Coordination with government users is required for partitioning of spectrum the licensing of which is subject to coordination with government users.

- (b) Technical standards—(1) Partitioning. In the case of partitioning, all requests for authorization for partial assignment of a license must include, as an attachment, a description of the partitioned service area. The partitioned service area shall be defined by coordinate points at every 3 degrees along the partitioned service area unless an FCC-recognized service area is utilized (e.g., Metropolitan Service Area, Rural Service Area, or Economic Area) or county lines are used. The geographic coordinates must be specified in degrees, minutes, and seconds to the nearest second of latitude and longitude, and must be based upon the 1983 North American Datum (NAD83). In a case where an FCC-recognized service area or county lines are utilized, applicants need only list the specific area(s) (through use of FCC designations or county names) that constitute the partitioned area.
- (2) Disaggregation. VHF (156–162 MHz) spectrum may only be disaggregated according to frequency pairs. AMTS spectrum may be disaggregated in any amount.
- (3) Combined partitioning and disaggregation. The Commission will consider requests for partial assignment of licenses that propose combinations of partitioning and disaggregation.
- (c) *License term*. The license term for a partitioned license area and for disaggregated spectrum shall be the remainder of the original licensee's term as provided for in §80.25 of this part.
- (d) Partitioning and disaggregation construction requirements for site-based AMTS, and nationwide or multi-region LF, MF, and HF public coast. Parties seeking to acquire a partitioned license or disaggregated spectrum from a site-based AMTS, or nationwide or multi-region LF, MF, and HF public coast licensee will be required to construct and commence "service to subscribers" in all facilities acquired through such

transactions within the original construction deadline for each facility as set forth in §80.49. Failure to meet the individual construction deadline will result in the automatic termination of the facility's authorization.

[63 FR 40063, July 27, 1998, as amended at 67 FR 48563, July 25, 2002; 69 FR 64671, Nov. 8, 2004; 82 FR 41548, Sept. 1, 2017]

### Subpart C—Operating Requirements and Procedures

STATION REQUIREMENTS—GENERAL

#### § 80.61 Commission inspection of stations.

All stations and required station records must be made available for inspection by authorized representatives of the Commission.

# §80.63 Maintenance of transmitter power.

- (a) The power of each radio transmitter must not be more than that necessary to carry on the service for which the station is licensed.
- (b) Except for transmitters using single sideband and independent sideband emissions, each radio transmitter rated by the manufacturer for carrier power in excess of 100 watts must contain the instruments necessary to determine the transmitter power during its operation

# STATION REQUIREMENTS—LAND STATIONS

# § 80.67 General facilities requirements for coast stations.

- (a) All coast stations licensed to transmit in the band 156-162 MHz must be able to transmit and receive on 156.800 MHz and at least one working frequency in the band.
- (b) All coast stations that operate telephony on frequencies in the 1605–3500 kHz band must be able to transmit and receive using J3E emission on the frequency 2182 kHz and at least one working frequency in the band.
- [51 FR 31213, Sept. 2, 1986, as amended at 68 FR 46960, Aug. 7, 2003]