

## **§ 95.1935**

### **§ 95.1935 Station identification.**

No RTU or CTS is required to transmit a station identification announcement.

### **§ 95.1937 Station inspection.**

Upon request by an authorized Commission representative, the 218–219 MHz Service system licensee must make any component CTS available for inspection.

### **§ 95.1951 Certification.**

Each CTS and RTU transmitter must be certified for use in the 218–219 MHz Service in accordance with subpart J of part 2 of this chapter.

### **§ 95.1953 Frequency segments.**

There are two frequency segments available for assignment to the 218–219 MHz Service in each service area. Frequency segment A is 218.000–218.500 MHz. Frequency segment B is 218.501–219.000 MHz.

### **§ 95.1955 Transmitter effective radiated power limitation.**

The effective radiated power (ERP) of each CTS and RTU shall be limited to the minimum necessary for successful communications. No CTS or fixed RTU may transmit with an ERP exceeding 20 Watts. No mobile RTU may transmit with an ERP exceeding 4 Watts.

### **§ 95.1957 Emission standards.**

(a) All transmissions by each CTS and by each RTU shall use an emission type that complies with the following standard for unnecessary radiation.

(b) All spurious and out-of-band emissions shall be attenuated:

(1) Zero dB on any frequency within the authorized frequency segment.

(2) At least 28 dB on any frequency removed from the midpoint of the assigned frequency segment by more than 250 kHz up to and including 750 kHz;

(3) At least 35 dB on any frequency removed from the midpoint of the assigned frequency segment by more than 750 kHz up to and including 1250 kHz;

(4) At least 43 plus 10 log (base 10) (mean power in Watts) dB on any frequency removed from the midpoint of

## **47 CFR Ch. I (10–1–20 Edition)**

the assigned frequency segment by more than 1250 kHz.

(c) When testing for certification, all measurements of unnecessary radiation are performed using a carrier frequency as close to the edge of the authorized frequency segment as the transmitter is designed to be capable of operating.

(d) The reference bandwidth of the instrumentation used to measure the emission power shall be 100 Hz for measuring emissions up to and including 250 kHz from the edge of the authorized frequency segment, and 10 kHz for measuring emissions more than 250 kHz from the edge of the authorized frequency segment. If a video filter is used, its bandwidth shall not be less than the reference bandwidth. The power level of the highest emission within the frequency segment, to which the attenuation is referenced, shall be remeasured for each change in reference bandwidth.

### **§ 95.1959 Antennas.**

(a) The overall height from ground to topmost tip of the CTS antenna shall not exceed the height necessary to assure adequate service. Certain CTS antennas must be individually licensed to the 218–219 MHz System licensee (*see* § 95.1911(b) of this part). CTS antennas must also meet the requirements in § 95.317 regarding menaces to air navigation. *See* 47 CFR 95.317 and consult part 17 of the FCC's Rules for more information (47 CFR part 17).

(b) [Reserved]

(c) The RTU may be connected to an external antenna not more than 6.1 m (20 feet) above ground or above an existing man-made structure (other than an antenna structure). Connectors that are used to connect RTUs to an external antenna shall not be of the types generally known as “F-type” or “BNC type.” Use of an external antenna is subject to § 95.1961.

### **§ 95.1961 Interference.**

(a) When a 218–219 MHz Service system suffers harmful interference within its service area or causes harmful interference to another 218–219 MHz Service system, the licensees of both systems must cooperate and resolve the