

# Corrections

Federal Register

Vol. 64, No. 135

Thursday, July 15, 1999

This section of the FEDERAL REGISTER contains editorial corrections of previously published Presidential, Rule, Proposed Rule, and Notice documents. These corrections are prepared by the Office of the Federal Register. Agency prepared corrections are issued as signed documents and appear in the appropriate document categories elsewhere in the issue.

## ENVIRONMENTAL PROTECTION AGENCY

### 40 CFR Part 60

[FRL-6337-1]

RIN 2060-AH97

### Test Methods: Three New Methods for Velocity and Volumetric Flow Rate Determination in Stacks or Ducts

#### Correction

In the rule correction C9-11796, printed on page 37196 in the issue of

Friday, July 9, 1999 (and rule document 99-11796 beginning on page 26484 in the issue of Friday, May 14, 1999), make the following correction:

#### Appendix A to Part 60-[Corrected]

#### Method 2H-Determination of Stack Gas Velocity Taking Into Account Velocity Decay Near the Stack Wall [Corrected]

On page 37196, third column, instruction 35 (and at 64 FR 26558, May 14, 1999, in the first column, equation 2H-10 is) corrected to read as follows:

$$Q_{d_1 \rightarrow d_{last}} = \sum_{d=1}^{d_{last}} Q_d \quad \text{Eq. 2H-10}$$

[FR Doc. C9-11796 Filed 7-14-99; 8:45 am]

BILLING CODE 1505-01-D