the nylon straps with new straps; as applicable. Accomplishment of the actions specified in the service bulletin is intended to adequately address the identified unsafe condition.

### Explanation of Requirements of Proposed Rule

Since an unsafe condition has been identified that is likely to exist or develop on other products of this same type design, the proposed AD would require accomplishment of the actions specified in the service bulletin described previously.

# **Cost Impact**

There are approximately 321 Model 767 series airplanes of the affected design in the worldwide fleet. The FAA estimates that 136 airplanes of U.S. registry would be affected by this proposed AD, that it would take approximately 1 work hour per airplane to accomplish the proposed actions, and that the average labor rate is \$60 per work hour. Required parts would cost approximately \$4,718 per airplane. Based on these figures, the cost impact of the proposed AD on U.S. operators is estimated to be \$649,808, or \$4,778 per airplane.

The cost impact figure discussed above is based on assumptions that no operator has vet accomplished any of the proposed requirements of this AD action, and that no operator would accomplish those actions in the future if this proposed AD were not adopted. The cost impact figures discussed in AD rulemaking actions represent only the time necessary to perform the specific actions actually required by the AD. These figures typically do not include incidental costs, such as the time required to gain access and close up, planning time, or time necessitated by other administrative actions.

# **Regulatory Impact**

The regulations proposed herein would not have a substantial direct effect on the States, on the relationship between the national Government and the States, or on the distribution of power and responsibilities among the various levels of government. Therefore, it is determined that this proposal would not have federalism implications under Executive Order 13132.

For the reasons discussed above, I certify that this proposed regulation (1) is not a "significant regulatory action" under Executive Order 12866; (2) is not a "significant rule" under the DOT Regulatory Policies and Procedures (44 FR 11034, February 26, 1979); and (3) if promulgated, will not have a significant economic impact, positive or negative, on a substantial number of small entities under the criteria of the Regulatory flexibility Act. A copy of the draft regulatory evaluation prepared for this action is contained in the Rules Docket. A copy of it may be obtained by contacting the Rules docket at the location provided under the caption **ADDRESSES.** 

### List of Subjects in 14 CFR Part 39

Air transportation, Aircraft, Aviation safety, Safety.

# **The Proposed Amendment**

Accordingly, pursuant to the authority delegated to me by the Administrator, the Federal Aviation Administration proposes to amend part 39 of the Federal Aviation regulations (14 CFR part 39) as follows:

# PART 39—AIRWORTHINESS DIRECTIVES

1. The authority citation for part 39 continues to read as follows:

Authority: 49 U.S.C. 106(g), 40113, 44701.

### §39.13 [Amended]

2. Section 39.13 is amended by adding the following new airworthiness directive:

Boeing: Docket 2000-NM-116-AD.

Applicability: Model 767 series airplanes, as listed in Boeing Alert Service Bulletin 767–25A0265, dated May 27, 1999; certificated in any category.

Note 1: This AD applies to each airplane identified in the preceding applicability provision, regardless of whether it has been modified, altered, or repaired in the area subject to the requirements of this AD. For airplanes that have been modified, altered, or repaired so that the performance of the requirements of this AD is affected, the owner/operator must request approval for an alternative method of compliance in accordance with paragraph (b) of this AD. The request should include an assessment of the effect of the modification, alteration, or repair on the unsafe condition addressed by this AD; and, if the unsafe condition has not been eliminated, the request should include specific proposed actions to address it.

*Compliance:* Required as indicated, unless accomplished previously.

To ensure that flight crew members safely reach the ground from a flight compartment window in the event of an emergency evacuation, accomplish the following:

### Replacement

(a) Within 18 months after the effective date of this AD, do the actions specified in paragraphs (a)(1) and (a)(2) of this AD, as applicable, per Boeing Alert Service Bulletin 767–25A0265, dated May 27, 1999.

(1) For all airplanes: Remove the two existing escape ropes and install new escape ropes, bags, and placards, as applicable, in the flight compartment. (2) For airplanes having serial numbers 1 through 107 inclusive; on which Boeing Service Bulletin 767–25–0149, dated March 7, 1991 has been accomplished; or on which neither Boeing Service Bulletin 767–25– 0149, dated March 7, 1991, nor 767– 25A0242, dated October 31, 1996, has been accomplished: Replace the nylon straps with new straps.

### **Alternative Methods of Compliance**

(b) An alternative method of compliance or adjustment of the compliance time that provides an acceptable level of safety may be used if approved by the Manager, Seattle Aircraft Certification Office (ACO), FAA. Operators shall submit their requests through an appropriate FAA Principal Maintenance Inspector, who may add comments and then send it to the Manager, Seattle ACO.

**Note 2:** Information concerning the existence of approved alternative methods of compliance with this AD, if any, may be obtained from the Seattle ACO.

#### **Special Flight Permit**

(c) Special flight permits may be issued in accordance with sections 21.197 and 21.199 of the Federal Aviation Regulations (14 CFR 21.197 and 21.199) to operate the airplane to a location where the requirements of this AD can be accomplished.

Issued in Renton, Washington, on January 9, 2001.

### Donald L. Riggin,

Acting Manager, Transport Airplane Directorate, Aircraft Certification Service. [FR Doc. 01–1238 Filed 1–12–01; 8:45 am] BILLING CODE 4910–13–U

## DEPARTMENT OF TRANSPORTATION

**Federal Aviation Administration** 

#### 14 CFR Part 39

[Docket No. 2000-NM-178-AD]

RIN 2120-AA64

# Airworthiness Directives; Saab Model SAAB 2000 Series Airplanes

**AGENCY:** Federal Aviation Administration, DOT. **ACTION:** Notice of proposed rulemaking (NPRM).

**SUMMARY:** This document proposes the adoption of a new airworthiness directive (AD) that is applicable to certain Saab Model SAAB 2000 series airplanes. This proposal would require a modification involving nondestructive test inspections of the 34 fastener holes in each rear wing spar, corrective action, if necessary, and cold working of the holes to increase fatigue life of the rear spar web. This proposal is prompted by issuance of mandatory continuing airworthiness information by a foreign civil airworthiness authority. The

actions specified by the proposed AD are intended to prevent fatigue cracking, which could result in fuel leakage and reduced structural integrity of the wings.

**DATES:** Comments must be received by February 15, 2001.

ADDRESSES: Submit comments in triplicate to the Federal Aviation Administration (FAA), Transport Airplane Directorate, ANM–114, Attention: Rules Docket No. 2000-NM-178-AD, 1601 Lind Avenue, SW., Renton, Washington 98055-4056. Comments may be inspected at this location between 9 a.m. and 3 p.m., Monday through Friday, except Federal holidays. Comments may be submitted via fax to (425) 227-1232. Comments may also be sent via the Internet using the following address: 9-anmnprmcomment@faa.gov. Comments sent via fax or the Internet must contain "Docket No. 2000-NM-178-AD" in the subject line and need not be submitted in triplicate. Comments sent via the Internet as attached electronic files must be formatted in Microsoft Word 97 for Windows or ASCII text.

The service information referenced in the proposed rule may be obtained from Saab Aircraft AB, SAAB Aircraft Product Support, S–581.88, Linkping, Sweden. This information may be examined at the FAA, Transport Airplane Directorate, 1601 Lind Avenue, SW., Renton, Washington 98055–4056; telephone (425) 227–2110; fax (425) 227–1149.

FOR FURTHER INFORMATION CONTACT: Dan Rodina, Aerospace Engineer, International Branch, ANM–116, FAA, Transport Airplane Directorate, 1601 Lind Avenue, SW., Renton, Washington 98055–4056; telephone (425) 227–2125; fax (425) 227–1149.

# SUPPLEMENTARY INFORMATION:

# **Comments Invited**

Interested persons are invited to participate in the making of the proposed rule by submitting such written data, views, or arguments as they may desire. Communications shall identify the Rules Docket number and be submitted in triplicate to the address specified above. All communications received on or before the closing date for comments, specified above, will be considered before taking action on the proposed rule. The proposals contained in this action may be changed in light of the comments received.

Submit comments using the following format:

• Organize comments issue-by-issue. For example, discuss a request to change the compliance time and a request to change the service bulletin reference as two separate issues.

• For each issue, state what specific change to the proposed AD is being requested.

• Include justification (*e.g.,* reasons or data) for each request.

Comments are specifically invited on the overall regulatory, economic, environmental, and energy aspects of the proposed rule. All comments submitted will be available, both before and after the closing date for comments, in the Rules Docket for examination by interested persons. A report summarizing each FAA-public contact concerned with the substance of this proposal will be filed in the Rules Docket.

Commenters wishing the FAA to acknowledge receipt of their comments submitted in response to this action must submit a self-addressed, stamped postcard on which the following statement is made: "Comments to Docket Number 2000–NM–178–AD." The postcard will be date stamped and returned to the commenter.

### Availability of NPRMs

Any person may obtain a copy of this NPRM by submitting a request to the FAA, Transport Airplane Directorate, ANM–114, Attention: Rules Docket No. 2000–NM–178–AD, 1601 Lind Avenue, SW., Renton, Washington 98055–4056.

### Discussion

The Luftfartsverket (LFV), which is the airworthiness authority for Sweden, notified the FAA that an unsafe condition may exist on certain Saab Model SAAB 2000 series airplanes. The LFV advises that, during fatigue tests, cracks have been detected at some fastener holes in the lower trailing edge support angles on both wings. This cracking condition, if not corrected, could result in fuel leakage and reduced structural integrity of the wing.

# Explanation of Relevant Service Information

Saab has issued Service Bulletin 2000-57-037, dated April 13, 2000, which describes procedures for a modification involving nondestructive test inspections of the 34 fastener holes in each rear wing spar to detect discrepancies (including cracking, scratches, or other damage, and incorrect hole size) and cold working of the holes to increase fatigue life. Accomplishment of the actions specified in the service bulletin is intended to adequately address the identified unsafe condition. The LFV classified this service bulletin as mandatory and issued Swedish

airworthiness directive 1–157, dated April 13, 2000, in order to assure the continued airworthiness of these airplanes in Sweden.

# **FAA's Conclusions**

This airplane model is manufactured in Sweden and is type certificated for operation in the United States under the provisions of section 21.29 of the Federal Aviation Regulations (14 CFR 21.29) and the applicable bilateral airworthiness agreement. Pursuant to this bilateral airworthiness agreement, the LFV has kept the FAA informed of the situation described above. The FAA has examined the findings of the LFV, reviewed all available information, and determined that AD action is necessary for products of this type design that are certificated for operation in the United States.

# Explanation of Requirements of Proposed Rule

Since an unsafe condition has been identified that is likely to exist or develop on other airplanes of the same type design registered in the United States, the proposed AD would require accomplishment of the actions specified in the service bulletin described previously, except as discussed below.

# Differences Between Proposed Rule and Service Bulletin

Operators should note that, although the service bulletin specifies that the manufacturer may be contacted for disposition of certain repair conditions, this proposal would require the repair of those conditions to be accomplished in accordance with a method approved by either the FAA, or the LFV (or its delegated agent). In light of the type of repair that would be required to address the identified unsafe condition, and in consonance with existing bilateral airworthiness agreements, the FAA has determined that, for this proposed AD, a repair approved by either the FAA or the LFV would be acceptable for compliance with this proposed AD.

# **Cost Impact**

The FAA estimates that 3 airplanes of U.S. registry would be affected by this proposed AD, that it would take approximately 64 work hours per airplane to accomplish the proposed inspections and modification, and that the average labor rate is \$60 per work hour. Required parts would be supplied by the manufacturer without cost to the operators. Based on these figures, the cost impact of the proposed AD on U.S. operators is estimated to be \$11,520, or \$3,840 per airplane.

The cost impact figure discussed above is based on assumptions that no operator has yet accomplished any of the proposed requirements of this AD action, and that no operator would accomplish those actions in the future if this proposed AD were not adopted. The cost impact figures discussed in AD rulemaking actions represent only the time necessary to perform the specific actions actually required by the AD. These figures typically do not include incidental costs, such as the time required to gain access and close up, planning time, or time necessitated by other administrative actions.

# **Regulatory Impact**

The regulations proposed herein would not have a substantial direct effect on the States, on the relationship between the national Government and the States, or on the distribution of power and responsibilities among the various levels of government. Therefore, it is determined that this proposal would not have federalism implications under Executive Order 13132.

For the reasons discussed above, I certify that this proposed regulation (1) is not a "significant regulatory action" under Executive Order 12866; (2) is not a "significant rule" under the DOT Regulatory Policies and Procedures (44 FR 11034, February 26, 1979); and (3) if promulgated, will not have a significant economic impact, positive or negative, on a substantial number of small entities under the criteria of the Regulatory Flexibility Act. A copy of the draft regulatory evaluation prepared for this action is contained in the Rules Docket. A copy of it may be obtained by contacting the Rules Docket at the location provided under the caption ADDRESSES.

### List of Subjects in 14 CFR Part 39

Air transportation, Aircraft, Aviation safety, Safety.

## The Proposed Amendment

Accordingly, pursuant to the authority delegated to me by the Administrator, the Federal Aviation Administration proposes to amend part 39 of the Federal Aviation Regulations (14 CFR part 39) as follows:

## PART 39—AIRWORTHINESS DIRECTIVES

1. The authority citation for part 39 continues to read as follows:

Authority: 49 U.S.C. 106(g), 40113, 44701.

# §39.13 [Amended]

2. Section 39.13 is amended by adding the following new airworthiness directive:

### Saab Aircraft AB: Docket 2000-NM-178-AD.

Applicability: Model SAAB 2000 series airplanes, certificated in any category, serial numbers –003 through –063 inclusive.

Note 1: This AD applies to each airplane identified in the preceding applicability provision, regardless of whether it has been modified, altered, or repaired in the area subject to the requirements of this AD. For airplanes that have been modified, altered, or repaired so that the performance of the requirements of this AD is affected, the owner/operator must request approval for an alternative method of compliance in accordance with paragraph (c) of this AD. The request should include an assessment of the effect of the modification, alteration, or repair on the unsafe condition addressed by this AD; and, if the unsafe condition has not been eliminated, the request should include specific proposed actions to address it.

*Compliance:* Required as indicated, unless accomplished previously.

To prevent fuel leakage and reduced structural integrity of the wings due to fatigue cracking, accomplish the following:

### Modification

(a) Except as required by paragraph (b) of this AD: Prior to the accumulation of 13,000 total flight cycles, accomplish the modification of the rear spar on both wings [including applicable nondestructive test inspections to detect discrepancies (including cracking, scratches, or other damage, and incorrect hole size) and cold working of fastener holes] in accordance with Saab Service Bulletin 2000–57–037, dated April 13, 2000.

Note 2: For the purposes of this AD, a detailed visual inspection is defined as: "An intensive visual examination of a specific structural area, system, installation, or assembly to detect damage, failure, or irregularity. Available lighting is normally supplemented with a direct source of good lighting at intensity deemed appropriate by the inspector. Inspection aids such as mirror, magnifying lenses, etc., may be used. Surface cleaning and elaborate access procedures may be required."

### Repair

(b) If any discrepancy is found during any inspection required by paragraph (a) of this AD, prior to further flight, repair in accordance with a method approved by the Manager, International Branch, ANM-116, FAA, Transport Airplane Directorate, or the Luftfartsverket (LFV) (or its delegated agent). For a repair method to be approved by the Manager, International Branch, ANM-116, as required by this paragraph, the Manager's approval letter must specifically reference this AD.

### **Methods of Compliance**

(c) An alternative method of compliance or adjustment of the compliance time that provides an acceptable level of safety may be used if approved by the Manager, International Branch, ANM-116. Operators shall submit their requests through an appropriate FAA Principal Maintenance Inspector, who may add comments and who will then send the requests and comments to the Manager, International Branch, ANM– 116.

**Note 3:** Information concerning the existence of approved alternative methods of compliance with this AD, if any, may be obtained from the International Branch, ANM-116.

### **Special Flight Permits**

(d) Special flight permits may be issued in accordance with sections 21.197 and 21.199 of the Federal Aviation Regulations (14 CFR 21.197 and 21.199) to operate the airplane to a location where the requirements of this AD can be accomplished.

**Note 4:** The subject of this AD is addressed in Swedish airworthiness directive 1–157, dated April 13, 2000.

Issued in Renton, Washington, on January 9, 2001.

### Donald L. Riggin,

Acting Manager, Transport Airplane Directorate, Aircraft Certification Service. [FR Doc. 01–1237 Filed 1–12–01; 8:45 am] BILLING CODE 4910–13–P

# DEPARTMENT OF TRANSPORTATION

### **Federal Aviation Administration**

# 14 CFR Part 39

[Docket No. 2000-NM-290-AD]

### RIN 2120-AA64

# Airworthiness Directives; Fokker Model F.28 Mark 0070 and Mark 0100 Series Airplanes

**AGENCY:** Federal Aviation Administration, DOT.

**ACTION:** Notice of proposed rulemaking (NPRM).

SUMMARY: This document proposes the supersedure of an existing airworthiness directive (AD), applicable to all Fokker Model F.28 Mark 0070 and Mark 0100 series airplanes, that currently requires revising the Airplane Flight Manual (AFM) to provide the flightcrew with instructions not to arm the liftdumper system prior to commanding the landing gear to extend. For Model F.28 Mark 0100 series airplanes, the existing AD also requires modification of the grounds of the shielding of the wheelspeed sensor wiring of the main landing gear (MLG) and installation of new electrical grounds for the wheelspeed sensor channel of the antiskid control box of the MLG. The proposed AD would remove the previous revision of the AFM and would require a new limitation and a new warning. This proposal is prompted by issuance of mandatory continuing airworthiness information by